Kernel driver lm92
==================

Supported chips:
  * National Semiconductor LM92
    Prefix: 'lm92'
    Addresses scanned: I2C 0x48 - 0x4b
    Datasheet: http://www.national.com/pf/LM/LM92.html
  * National Semiconductor LM76
    Prefix: 'lm92'
    Addresses scanned: none, force parameter needed
    Datasheet: http://www.national.com/pf/LM/LM76.html
  * Maxim MAX6633/MAX6634/MAX6635
    Prefix: 'lm92'
    Addresses scanned: I2C 0x48 - 0x4b
    MAX6633 with address in 0x40 - 0x47, 0x4c - 0x4f needs force parameter
    and MAX6634 with address in 0x4c - 0x4f needs force parameter
    Datasheet: http://www.maxim-ic.com/quick_view2.cfm/qv_pk/3074

Authors:
        Abraham van der Merwe <abraham@2d3d.co.za>
        Jean Delvare <khali@linux-fr.org>

Description

This driver implements support for the National Semiconductor LM92
temperature sensor.

Each LM92 temperature sensor supports a single temperature sensor. There are
alarms for high, low, and critical thresholds. There's also an hysteresis to
control the thresholds for resetting alarms.

Support was added later for the LM76 and Maxim MAX6633/MAX6634/MAX6635,
which are mostly compatible. They have not all been tested, so you
may need to use the force parameter.