

Copyright 2004 Linus Torvalds
 Copyright 2004 Pavel Machek <pavel@suse.cz>
 Copyright 2006 Bob Copeland <me@bobcopeland.com>

~~~~~Using sparse for typechecking~~~~~

"__bitwise" is a type attribute, so you have to do something like this:

```
typedef int __bitwise pm_request_t;

enum pm_request {
    PM_SUSPEND = (__force pm_request_t) 1,
    PM_RESUME = (__force pm_request_t) 2
};
```

which makes PM_SUSPEND and PM_RESUME "bitwise" integers (the "__force" is there because sparse will complain about casting to/from a bitwise type, but in this case we really do want to force the conversion). And because the enum values are all the same type, now "enum pm_request" will be that type too.

And with gcc, all the __bitwise/__force stuff goes away, and it all ends up looking just like integers to gcc.

Quite frankly, you don't need the enum there. The above all really just boils down to one special "int __bitwise" type.

So the simpler way is to just do

```
typedef int __bitwise pm_request_t;

#define PM_SUSPEND ((__force pm_request_t) 1)
#define PM_RESUME ((__force pm_request_t) 2)
```

and you now have all the infrastructure needed for strict typechecking.

One small note: the constant integer "0" is special. You can use a constant zero as a bitwise integer type without sparse ever complaining. This is because "bitwise" (as the name implies) was designed for making sure that bitwise types don't get mixed up (little-endian vs big-endian vs cpu-endian vs whatever), and there the constant "0" really is special.

__bitwise__ - to be used for relatively compact stuff (gfp_t, etc.) that is mostly warning-free and is supposed to stay that way. Warnings will be generated without __CHECK_ENDIAN__.

__bitwise - noisy stuff; in particular, __le*/__be* are that. We really don't want to drown in noise unless we'd explicitly asked for it.

~~~~~Getting sparse~~~~~

You can get latest released versions from the Sparse homepage at

sparse.txt

https://sparse.wiki.kernel.org/index.php/Main_Page

Alternatively, you can get snapshots of the latest development version of sparse using git to clone..

`git://git.kernel.org/pub/scm/devel/sparse/sparse.git`

DaveJ has hourly generated tarballs of the git tree available at..

<http://www.codemonkey.org.uk/projects/git-snapshots/sparse/>

Once you have it, just do

```
make
make install
```

as a regular user, and it will install sparse in your ~/bin directory.

Using sparse

Do a kernel make with "make C=1" to run sparse on all the C files that get recompiled, or use "make C=2" to run sparse on the files whether they need to be recompiled or not. The latter is a fast way to check the whole tree if you have already built it.

The optional make variable CF can be used to pass arguments to sparse. The build system passes -Wbitwise to sparse automatically. To perform endianness checks, you may define __CHECK_ENDIAN__:

```
make C=2 CF="-D__CHECK_ENDIAN__"
```

These checks are disabled by default as they generate a host of warnings.