Kernel driver 1m70

Supported chips:

* National Semiconductor LM70

Datasheet: http://www.national.com/pf/LM/LM70.html

* Texas Instruments TMP121/TMP123

Information: http://focus.ti.com/docs/prod/folders/print/tmp121.html

Author:

Kaiwan N Billimoria <kaiwan@designergraphix.com>

Description

This driver implements support for the National Semiconductor LM70 temperature sensor.

The LM70 temperature sensor chip supports a single temperature sensor. It communicates with a host processor (or microcontroller) via an SPI/Microwire Bus interface.

Communication with the LM70 is simple: when the temperature is to be sensed, the driver accesses the LM70 using SPI communication: 16 SCLK cycles comprise the MOSI/MISO loop. At the end of the transfer, the 11-bit 2's complement digital temperature (sent via the SIO line), is available in the driver for interpretation. This driver makes use of the kernel's in-core SPI support.

As a real (in-tree) example of this "SPI protocol driver" interfacing with a "SPI master controller driver", see drivers/spi/spi_lm701lp.c and its associated documentation.

The TMP121/TMP123 are very similar; main differences are 4 wire SPI interface (read only) and 13-bit temperature data (0.0625 degrees celsius resolution).

Thanks to

Jean Delvare khali@linux-fr.org for mentoring the hwmon-side driver development.