

What: /sys/class/pktcdvd/  
 Date: Oct. 2006  
 KernelVersion: 2.6.20  
 Contact: Thomas Maier <balagi@justmail.de>  
 Description:

## sysfs interface

---

The pktcdvd module (packet writing driver) creates  
 these files in the sysfs:  
 (<devid> is in format major:minor )

```

/sys/class/pktcdvd/
  add          (0200) Write a block device id (major:minor)
                  to create a new pktcdvd device and map
                  it to the block device.

  remove       (0200) Write the pktcdvd device id (major:minor)
                  to it to remove the pktcdvd device.

  device_map   (0444) Shows the device mapping in format:
                  pktcdvd[0-7] <pktdevid> <blkdevid>

/sys/class/pktcdvd/pktcdvd[0-7]/
  dev          (0444) Device id
  uevent       (0200) To send an uevent.

/sys/class/pktcdvd/pktcdvd[0-7]/stat/
  packets_started (0444) Number of started packets.
  packets_finished (0444) Number of finished packets.

  kb_written     (0444) kBytes written.
  kb_read        (0444) kBytes read.
  kb_read_gather (0444) kBytes read to fill write packets.

  reset          (0200) Write any value to it to reset
                  pktcdvd device statistic values, like
                  bytes read/written.

/sys/class/pktcdvd/pktcdvd[0-7]/write_queue/
  size          (0444) Contains the size of the bio write
                  queue.

  congestion_off (0644) If bio write queue size is below
                  this mark, accept new bio requests
                  from the block layer.

  congestion_on  (0644) If bio write queue size is higher
                  as this mark, do no longer accept
                  bio write requests from the block
                  layer and wait till the pktcdvd
                  device has processed enough bio's
                  so that bio write queue size is
                  below congestion off mark.
                  A value of <= 0 disables congestion
  
```

sysfs-class-pktcdvd..txt  
control.

Example:  
-----

To use the pktcdvd sysfs interface directly, you can do:

```
# create a new pktcdvd device mapped to /dev/hdc
echo "22:0" >/sys/class/pktcdvd/add
cat /sys/class/pktcdvd/device_map
# assuming device pktcdvd0 was created, look at stat's
cat /sys/class/pktcdvd/pktcdvd0/stat/kb_written
# print the device id of the mapped block device
fgrep pktcdvd0 /sys/class/pktcdvd/device_map
# remove device, using pktcdvd0 device id 253:0
echo "253:0" >/sys/class/pktcdvd/remove
```