

Kernel driver i2c-sis630

Supported adapters:

- * Silicon Integrated Systems Corp (SiS)
630 chipset (Datasheet: available at
<http://amalysh.bei.t-online.de/docs/SIS/>)
730 chipset
- * Possible other SiS chipsets ?

Author: Alexander Malysh <amalysh@web.de>

Module Parameters

- * force = [1|0] Forcibly enable the SIS630. DANGEROUS!
This can be interesting for chipsets not named
above to check if it works for you chipset, but DANGEROUS!
- * high_clock = [1|0] Forcibly set Host Master Clock to 56KHz (default,
what your BIOS use). DANGEROUS! This should be a bit
faster, but freeze some systems (i.e. my Laptop).

Description

This SMBus only driver is known to work on motherboards with the above
named chipsets.

If you see something like this:

```
00:00.0 Host bridge: Silicon Integrated Systems [SiS] 630 Host (rev 31)
00:01.0 ISA bridge: Silicon Integrated Systems [SiS] 85C503/5513
```

or like this:

```
00:00.0 Host bridge: Silicon Integrated Systems [SiS] 730 Host (rev 02)
00:01.0 ISA bridge: Silicon Integrated Systems [SiS] 85C503/5513
```

in your 'lspci' output , then this driver is for your chipset.

Thank You

Philip Edelbrock <phil@netroedge.com>
- testing SiS730 support
Mark M. Hoffman <mhoffman@lightlink.com>
- bug fixes

To anyone else which I forgot here ;), thanks!