OLVM 4.5 DISCOVERED INVENTORY

Recovery Discovery Report – Generated on 2026-05-15 05:40:55Z

HOSTS DISCOVERED	VIRTUAL MACHINES	LOGICAL NETWORKS	STORAGE DOMAIN METADATA FILES	OVF / META CANDIDATES
2	3	3	2	34
All Scanned	All on kvm1	Across Hosts	Shared NFS Path	Potential Imports

HOSTS SUMMARY

Host	Hostname (FQDN)	OS	VMs	Storage Metadata
kvm1	demo-kvm1.sub[redacted] vcn[redacted].oraclevcn.com	Oracle Linux Server 8.10	3	1
kvm2	demo-kvm2.subn[redacted]. vcn[redacted]2.oraclevcn.com	Oracle Linux Server 8.10	0	1

Key Notes

- Both hosts scanned successfully.
- All VMs are currently running on kvm1.
- No libvirt storage pools detected.

OLVM INFRASTRUCTURE OVERVIEW

High Level Topology

Data Center (Discovered)

Cluster (Discovered)

kvm1
demo-kvm1.subne[redacted]2. vcn[redacted]oraclevcn.com
3 VMs
Oracle Linux Server 8.10

kvm2
demo-kvm2.subne[redacted]. vcn[redacted]oraclevcn.com
0 VMs
Oracle Linux Server 8.10

Shared Storage Domain (NFS)
/rhev/data-center/mnt/
1[redacted].156.2:_nfs_olv__ovirt_oci__block__volume/
b22afc50-69ac-4128-8674-f348d344e8c2/dom_md/metadata

VIRTUAL MACHINES (Visible via libvirt)

VM Name	UUID	State	Seen On Host(s)	vCPU	Disks	NICs
DemoDB01	278a9c64-b91a-4df0-ada5-9488df61ba7d	Running	kvm1	64	2	1
DemoVM	ef739098-5cc2-4fb8-a591-7a8e75f186c9	Running	kvm1	16	2	1
dhcp-server	2dff60c9-af3a-45bc-b120-d20dbdaffe9a	Running	kvm1	16	2	1

All 3 virtual machines are currently running on kvm1.

LOGICAL NETWORKS (Discovered)

Network Name / Bridge	Seen On Hosts	Bridge(s)	Forward Mode	Type
;vdsmdummy;	kvm1, kvm2	;vdsmdummy;	bridge	Internal
default	kvm1, kvm2	virbr0	nat	NAT
vdsm-ovirtmgmt	kvm1	ovirtmgmt	bridge	Management

Network XML definitions captured from both hosts.

STORAGE FINDINGS

- Storage-domain metadata files: **2**
- OVF / Meta candidate files: **34**
- Libvirt storage pools: **0**

Shared Storage Domain (NFS)

First storage-domain metadata paths discovered:

/rhev/data-center/mnt/
144.24[redacted]_nfs_olv__ovirt_
oci__block__volume/
b22afc50-69ac-4128-8674-
f348d344e8c2/dom_md/metadata

Present on: kvm1, kvm2

The same storage-domain metadata path is accessible from both hosts.

DISCOVERED ARTIFACTS & FILE STRUCTURE

```
olvm-recovery-20260515-054004Z
├── engine_api_bootstrap_template.py
├── olvm-recovery-manifest.json
├── olvm-recovery-plan.md
└── hosts
    ├── kvm1
    │   ├── networks (3 XML)
    │   ├── vms (3 XML)
    │   └── storage-pools (0)
    └── kvm2
        ├── networks (2 XML)
        ├── vms (0)
        └── storage-pools (0)
```

Files Generated

VM XML files	3
Network XML files	5
Storage pool XML files	0
Other artifacts	4

Notable

- kvm1 has 3 networks & 3 VMs
- kvm2 has 2 networks & 0 VMs
- No libvirt storage pools found on either host

FRESH ENGINE REBUILD – HIGH LEVEL SEQUENCE

1. **Check Backup** – Try official engine-backup restore first (if available).
2. **Deploy Fresh Engine** – Install OLVM 4.5 Engine on the same FQDN (if possible).
3. **Create DC & Cluster** – Create data center and cluster(s) matching old compatibility & CPU family.
4. **Recreate Networks** – Recreate logical networks; VLANs/bridges/bonds) using captured information.
5. **Add Hosts** – Add hosts one by one. Handle VDSM cert/ bootstrap cleanup if required.
6. **Import Storage** – Attach/import existing storage domains via Administration Portal or API. Do NOT initialize/wipe.
7. **Import VMs** – Import/register VMs & templates. Validate disks, NICs, MACs, boot order, HA.
8. **Recreate Configs** – Recreate users, roles, quotas, affinities, policies, fencing/PM, MAC pools, providers.

RECOVERY BOUNDARY

Do NOT rebuild the Engine database by manually inserting rows into PostgreSQL. Use supported OLVM restore/import workflows only.

OUTPUT LOCATION

olvm-recovery-20260515-054004Z

Manifest, plan, and all discovered XML artifacts are available in the output directory.

NEXT STEP

Review the recovery plan and discovered inventory before making any changes to a fresh Engine.