

Grocerra Database Architecture & Data Dictionary (V9 - With Descriptions & Demo Data)

Overview

This document serves as the complete, exhaustive reference for the Grocerra platform database. It is designed to scale to millions of users, handle massive transactional load seamlessly, and provide a "God's Eye" level of auditability.

Note: V9 includes both detailed column descriptions AND practical Demo Data examples so Junior Developers understand exactly what data to insert.

1. Architectural Pillars

1.1 UUIDv7 Primary Keys

- **The Decision:** We use UUIDv7 instead of sequential Integers or UUIDv4 for all primary keys.
- **Why:** UUIDv7 is time-sorted. It inserts sequentially like an Integer, keeping the database extremely fast, while remaining cryptographically secure.

1.2 The Hybrid JSONB Catalog

- **The Decision:** We use a `JSONB` column named `config` in the `products` table to handle variables.
- **Why:** By keeping core data strict (name, price) and variable data flexible in a JSONB column, we achieve lightning-fast reads with infinite flexibility.

1.3 Strategic Denormalization (Historical Receipts)

- **The Decision:** The `order_items` table physically copies the `price` and `name` of the product at the moment of purchase.

1.4 Strict Inventory Ledgers

- **The Decision:** Inventory isn't just an integer that goes up and down. A dedicated `inventory_ledgers` table acts like a bank ledger, logging every single stock movement (sale, spoilage, restock). This completely eliminates race conditions when two users buy the last item at the exact same millisecond.
-

2. Complete Data Dictionary (38 Tables)

2.1 Enums (State Machines)

- `order_status` : pending, accepted, preparing, ready_for_pickup, out_for_delivery, delivered, cancelled, refunded
 - `product_type` : standard, weighted, catering, digital
 - `transaction_type` : authorize, capture, refund, payout
 - `transaction_status` : pending, succeeded, failed, requires_action
 - `delivery_provider` : uber_direct, doordash_drive, merchant_internal
-

2.2 Core Identity, RBAC, & Devices

Table: users

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `email` (VARCHAR 255, Unique): Login email. Ex: 'john.doe@gmail.com'
- `phone` (VARCHAR 20, Unique): Contact number. Ex: '+61412345678'
- `full_name` (VARCHAR 255): Display name. Ex: 'John Doe'
- `status` (VARCHAR 50): Account status (default: 'active'). Ex: 'active', 'banned'
- `created_at` , `updated_at` , `deleted_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'

Table: roles

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `name` (VARCHAR 50, Unique): Role name. Ex: 'superadmin', 'store_manager'
- `permissions` (JSONB): Granular permission flags. Ex: `{"can_edit_products": true, "can_refund_orders": false}`

Table: user_roles

- `user_id` (UUID, FK): The user. *Ex: '018b8f2a-...' *
- `role_id` (UUID, FK): The assigned role. *Ex: '018b8f2a-...' *
- `store_id` (UUID, nullable): Scopes role to a store. Ex: '018b8f2a-...' (Null if Superadmin)

Table: user_addresses

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `user_id` (UUID, FK): The owning user. *Ex: '018b8f2a-...' *
- `formatted_address` (TEXT): Full string address. Ex: '123 Fake Street, Sydney NSW 2000'
- `lat` (DECIMAL 10,8), `lng` (DECIMAL 11,8): Exact GPS for couriers. Ex: -33.86881970, 151.20929550
- `delivery_instructions` (TEXT): Details for driver. Ex: 'Gate code is 1234. Leave at front door.'
- `is_default` (BOOLEAN): Is primary address. Ex: `true`
- `created_at` (TIMESTAMP): Audit timestamp. Ex: '2026-10-10 01:25:00+00'

Table: user_devices

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `user_id` (UUID, FK): The owning user. *Ex: '018b8f2a-...' *
- `device_token` (TEXT, Unique): FCM/APNS push token. Ex: 'fcm_token_xyz123abc'
- `platform` (VARCHAR 50): OS platform. Ex: 'ios', 'android'
- `last_active_at` (TIMESTAMP): Last ping. Ex: '2026-10-10 01:25:00+00'

2.3 Merchant / Store Domain

Table: stores

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `name` (VARCHAR 255): Store display name. Ex: 'Sydney Fresh Meats'
- `slug` (VARCHAR 255, Unique): URL friendly slug. Ex: 'sydney-fresh-meats'
- `description` (TEXT): Store bio. Ex: 'The best premium wagyu beef in Sydney.'
- `logo_url` , `banner_url` (VARCHAR 500): Branding imagery. Ex: '<https://cdn.grocerria.com/stores/logo.jpg>'
- `status` (VARCHAR 50): Store lifecycle. Ex: 'active', 'pending_approval'
- `commission_rate` (DECIMAL 5,2): Platform cut. Ex: 4.50 (Represents 4.5%)

- `tax_id` (VARCHAR 100): ABN/Tax identifier. *Ex: 'ABN 12 345 678 901'*
- `stripe_account_id` (VARCHAR 255): Stripe Connect routing ID. *Ex: 'acct_1032D82eB69'*
- `created_at` , `updated_at` , `deleted_at` (TIMESTAMP): Audit timestamps. *Ex: '2026-10-10 01:25:00+00'*

Table: `store_locations`

- `id` (UUIDv7, PK): Unique identifier. **Ex: '018b8f2a-...' **
- `store_id` (UUID, FK): Owning store. **Ex: '018b8f2a-...' **
- `address` (TEXT): Physical string address. *Ex: '45 Butcher Ave, Sydney NSW 2000'*
- `lat` (DECIMAL 10,8), `lng` (DECIMAL 11,8): GPS coordinates. *Ex: -33.8688, 151.2092*
- `pickup_instructions` (TEXT): Directions for Uber drivers. *Ex: 'Drivers must park at the back alley loading dock.'*

Table: `store_operating_hours`

- `id` (UUIDv7, PK): Unique identifier. **Ex: '018b8f2a-...' **
- `store_id` (UUID, FK): Owning store. **Ex: '018b8f2a-...' **
- `day_of_week` (INT): 0 (Sun) to 6 (Sat). *Ex: 1 (Monday)*
- `open_time` , `close_time` (TIME): Operating window. *Ex: '08:00:00', '22:00:00'*

Table: `store_delivery_zones`

- `id` (UUIDv7, PK): Unique identifier. **Ex: '018b8f2a-...' **
- `store_id` (UUID, FK): Owning store. **Ex: '018b8f2a-...' **
- `polygon_data` (JSONB): GeoJSON for geofencing. *Ex: {"type": "Polygon", "coordinates": [[[151.2, -33.8], [151.3, -33.9]]]}*
- `max_radius_km` (DECIMAL 5,2): Fallback maximum radius. *Ex: 15.50*

Table: `store_settings`

- `store_id` (UUID, PK, FK): Owning store. **Ex: '018b8f2a-...' **
- `auto_accept_orders` (BOOLEAN): Bypass manual accept. *Ex: true (Orders go straight to kitchen)*
- `min_order_amount` (DECIMAL 10,2): Minimum cart value. *Ex: 25.00*
- `packaging_fee` (DECIMAL 10,2): Fixed bag fee. *Ex: 1.50 (For eco-bags)*
- `prep_time_minutes` (INT): Used for Uber API quotes. *Ex: 15 (Tells Uber when to arrive)*
- `updated_at` (TIMESTAMP): Audit timestamp. *Ex: '2026-10-10 01:25:00+00'*

2.4 Catalog Domain

Table: `categories`

- `id` (UUIDv7, PK): Unique identifier. **Ex: '018b8f2a-...' **
- `parent_id` (UUID, FK): For sub-categories. *Ex: '018b8f2a-...' (Null if top-level)*
- `name` (VARCHAR 255): Category display name. *Ex: 'Fresh Meat'*
- `slug` (VARCHAR 255, Unique): URL friendly slug. *Ex: 'fresh-meat'*
- `icon_url` (VARCHAR 500): UI icon. *Ex: '<https://cdn.grocerra.com/icons/meat.png>'*
- `sort_order` (INT): UI ordering. *Ex: 1*

Table: `products`

- `id` (UUIDv7, PK): Unique identifier. **Ex: '018b8f2a-...' **
- `store_id` (UUID, FK): Owning store. **Ex: '018b8f2a-...' **

- `name` (VARCHAR 255), `slug` (VARCHAR 255): Display and URL names. Ex: 'Premium Wagyu Ribeye', 'premium-wagyu-ribeye'
- `description` (TEXT): Product details. Ex: '500g of MS9 grade wagyu.'
- `base_price` (DECIMAL 10,2): Current price. Ex: 65.00
- `compare_at_price` (DECIMAL 10,2): For 'sale' UI strikethroughs. Ex: 80.00 (UI shows \$80 crossed out)
- `stock_quantity` (INT): Current inventory. Ex: 15
- `is_taxable` (BOOLEAN): Applies GST logic (default: true). Ex: false (Fresh food has 0% GST)
- `type` (product_type ENUM): Type constraint. Ex: 'weighted'
- `config` (JSONB): Dynamic attributes. Ex: {"weight_variance_percent": 10, "unit": "kg"}
- `status` (VARCHAR 50): Visibility status. Ex: 'active', 'draft'
- `created_at`, `updated_at`, `deleted_at` (TIMESTAMP): Audit. Ex: '2026-10-10 01:25:00+00'

Table: product_images

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `product_id` (UUID, FK): Owning product. *Ex: '018b8f2a-...' *
- `url` (VARCHAR 500): Cloud Storage URL. Ex: <https://cdn.grocerra.com/products/wagyu1.jpg>
- `is_primary` (BOOLEAN): Main thumbnail flag. Ex: true
- `sort_order` (INT): Gallery order. Ex: 1

Table: product_categories

- `product_id` (UUID, FK), `category_id` (UUID, FK): Many-to-Many join table. (Composite PK). Ex: ('018b8...', '018b8...')

Table: product_variants

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `product_id` (UUID, FK): Owning product. *Ex: '018b8f2a-...' *
- `sku` (VARCHAR 100): Barcode/SKU. Ex: 'WAGYU-500G-THICK'
- `price` (DECIMAL 10,2): Override price. Ex: 75.00
- `stock_quantity` (INT): Variant specific stock. Ex: 5
- `attributes` (JSONB): Details. Ex: {"Cut": "Thick", "Aging": "30 Days"}

Table: product_modifiers

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `product_id` (UUID, FK): Owning product. *Ex: '018b8f2a-...' *
- `name` (VARCHAR 255): Group name. Ex: 'Choose Marinade'
- `is_required` (BOOLEAN): Forces user selection. Ex: false
- `max_selections` (INT): Limit logic. Ex: 2

Table: product_modifier_options

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `modifier_id` (UUID, FK): Owning modifier group. *Ex: '018b8f2a-...' *
- `name` (VARCHAR 255): Specific option. Ex: 'Teriyaki Glaze'
- `additional_price` (DECIMAL 10,2): Surcharge. Ex: 2.50

2.5 Orders & Fulfillment Domain

Table: carts

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `user_id` (UUID, FK): Owning user. *Ex: '018b8f2a-...' *
- `session_id` (VARCHAR 255): For logged-out guest carts. Ex: 'sess_987abc'
- `store_id` (UUID, FK): Scope cart to one store. *Ex: '018b8f2a-...' *
- `status` (VARCHAR 50): Cart state. Ex: 'active', 'converted'
- `created_at` , `updated_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'

Table: `cart_items`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `cart_id` (UUID, FK): Owning cart. *Ex: '018b8f2a-...' *
- `product_id` (UUID, FK): Linked product. *Ex: '018b8f2a-...' *
- `variant_id` (UUID, FK): Optional linked variant. Ex: '018b8f2a-...' (Null if no variant)
- `quantity` (INT): Amount added (Constraint: > 0). Ex: 2
- `config` (JSONB): Selected modifier options. Ex: `{"selected_modifiers": [{"018b...", "018c..."}]}`

Table: `delivery_quotes`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `cart_id` (UUID, FK): Owning cart. *Ex: '018b8f2a-...' *
- `provider` (delivery_provider ENUM): Target provider. Ex: 'uber_direct'
- `quote_id` (VARCHAR 255): API token from provider. Ex: 'ubr_qt_123xyz'
- `fee` (DECIMAL 10,2): Price quoted. Ex: 7.50
- `expires_at` (TIMESTAMP): Quote validity window. Ex: '2026-10-10 01:40:00+00'

Table: `orders`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `order_number` (VARCHAR 50, Unique): Human-readable receipt ID. Ex: 'ORD-2026-9912'
- `user_id` (UUID, FK), `store_id` (UUID, FK): Associations. *Ex: '018b8f2a-...' *
- `status` (order_status ENUM): Current lifecycle state. Ex: 'preparing'
- `subtotal` , `tax` , `delivery_fee` , `platform_fee` , `total_amount` (DECIMAL 10,2): Financial breakdown. Ex: Total: 140.00
- `idempotency_key` (VARCHAR 255, Unique): Prevents double charging. Ex: 'idem_9988abc'
- `created_at` , `updated_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'

Table: `order_items`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `order_id` (UUID, FK): Owning order. *Ex: '018b8f2a-...' *
- `product_id` (UUID, FK), `variant_id` (UUID, FK): Line item mapping. *Ex: '018b8f2a-...' *
- `quantity` (INT): Amount purchased. Ex: 2
- `snapshot_price` (DECIMAL 10,2): Locked price at purchase. Ex: 65.00
- `snapshot_name` (VARCHAR 255): Locked name at purchase. Ex: 'Premium Wagyu Ribeye'

Table: `order_item_modifiers`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `order_item_id` (UUID, FK): Owning line item. *Ex: '018b8f2a-...' *
- `modifier_option_id` (UUID, FK): Exact add-on selected. *Ex: '018b8f2a-...' *
- `snapshot_name` (VARCHAR 255): Locked modifier name. Ex: 'Teriyaki Glaze'
- `snapshot_price` (DECIMAL 10,2): Locked modifier price. Ex: 2.50

Table: deliveries

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
 - `order_id` (UUID, FK): Owning order. *Ex: '018b8f2a-...' *
 - `provider` (delivery_provider ENUM): Courier service used. Ex: 'uber_direct'
 - `provider_delivery_id` (VARCHAR 255): Uber API Tracking ID. Ex: 'del_ubr_9912'
 - `tracking_url` (VARCHAR 500): Public map link. Ex: '<https://track.uber.com/xyz123>'
 - `courier_name` (VARCHAR 255), `courier_phone` (VARCHAR 50): Driver details. Ex: 'Michael T.; '+61498765432'
 - `status` (VARCHAR 50): Courier specific status. Ex: 'en_route_to_pickup'
 - `pickup_time` , `dropoff_time` (TIMESTAMP): Actual transit times. Ex: '2026-10-10 01:45:00+00'
 - `updated_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'
-

2.6 Payment & Finance Domain

Table: transactions

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `order_id` (UUID, FK): Owning order. *Ex: '018b8f2a-...' *
- `type` (transaction_type ENUM): Action taken. Ex: 'authorize'
- `provider` (VARCHAR 50): Payment gateway. Ex: 'stripe'
- `provider_transaction_id` (VARCHAR 255, Unique): Stripe `pi_xxx` . Ex: 'pi_123456789'
- `amount` (DECIMAL 10,2): Money moved. Ex: 140.00
- `currency` (VARCHAR 10): Default 'AUD'. Ex: 'AUD'
- `status` (transaction_status ENUM): Final state. Ex: 'succeeded'
- `created_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'

Table: refunds

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `order_id` (UUID, FK), `transaction_id` (UUID, FK): Audit trails. *Ex: '018b8f2a-...' *
- `amount` (DECIMAL 10,2): Money returned. Ex: 20.00
- `reason` (TEXT): Rationale. Ex: 'Customer reported meat was tough.'
- `status` (transaction_status ENUM): Refund state. Ex: 'succeeded'
- `liabilities` (JSONB): Tracks fault (e.g. 50% merchant, 50% platform). Ex: `{"store_liability": 10.00, "platform_liability": 10.00}`
- `created_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'

Table: payouts

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
 - `store_id` (UUID, FK): Merchant receiving funds. *Ex: '018b8f2a-...' *
 - `stripe_payout_id` (VARCHAR 255, Unique): Stripe `po_xxx` . Ex: 'po_987654321'
 - `amount` (DECIMAL 10,2): Final cut transferred. Ex: 1250.50
 - `status` (transaction_status ENUM): Payout state. Ex: 'succeeded'
 - `period_start` , `period_end` (TIMESTAMP): Reporting window. Ex: '2026-10-01 00:00:00+00'
 - `created_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'
-

2.7 Marketing & Support

Table: promotions

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `store_id` (UUID, FK): Nullable (for platform-wide codes). *Ex: '018b8f2a-...' (Null for platform)*
- `code` (VARCHAR 50, Unique): Coupon string. *Ex: 'MEAT10'*
- `type` (VARCHAR 50): Discount type. *Ex: 'percentage', 'fixed_amount'*
- `value` (DECIMAL 10,2): Discount metric. *Ex: 10.00 (Means 10%)*
- `min_order_value` (DECIMAL 10,2): Eligibility limit. *Ex: 50.00*
- `start_date` , `end_date` (TIMESTAMP): Validity period. *Ex: '2026-10-31 23:59:59+00'*
- `max_uses` (INT): Total global uses. *Ex: 100*
- `current_uses` (INT): Live tracker. *Ex: 45*

Table: `promotion_usages`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `promotion_id` (UUID, FK): Discount consumed. *Ex: '018b8f2a-...' *
- `user_id` (UUID, FK), `order_id` (UUID, FK): Audit trail. *Ex: '018b8f2a-...' *
- `created_at` (TIMESTAMP): Audit timestamp. *Ex: '2026-10-10 01:25:00+00'*

Table: `reviews`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `order_id` (UUID, FK), `user_id` (UUID, FK), `store_id` (UUID, FK): Review context. *Ex: '018b8f2a-...' *
- `rating` (INT): 1 to 5 stars. *Ex: 5*
- `comment` (TEXT): User feedback. *Ex: 'Absolutely delicious wagyu!'*
- `reply` (TEXT): Merchant response. *Ex: 'Thank you for your business!'*
- `status` (VARCHAR 50): Moderation flag. *Ex: 'published', 'flagged'*

Table: `user_favorites`

- `user_id` (UUID, FK), `store_id` (UUID, FK): Bookmarks. (Composite PK). *Ex: ('018b8...', '018b8...')*

Table: `support_tickets`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `user_id` (UUID, FK): Reporting user. *Ex: '018b8f2a-...' *
- `order_id` (UUID, FK): Relevant order context. *Ex: '018b8f2a-...' *
- `subject` (VARCHAR 255): Issue title. *Ex: 'Driver left food in the rain'*
- `status` (VARCHAR 50): Ticket status. *Ex: 'open', 'resolved'*
- `priority` (VARCHAR 50): Priority level. *Ex: 'high'*

Table: `ticket_messages`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `ticket_id` (UUID, FK): Parent ticket. *Ex: '018b8f2a-...' *
- `sender_id` (UUID, FK): User or Admin replying. *Ex: '018b8f2a-...' *
- `message` (TEXT): Body content. *Ex: 'I am so sorry to hear this. Refunding now.'*
- `is_internal_note` (BOOLEAN): Admin-only visibility. *Ex: false*

2.8 Platform Operations (God's Eye)

Table: `notifications`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *

- `user_id` (UUID, FK): Target user. *Ex: '018b8f2a-...' *
- `title` (VARCHAR): Title of notification. Ex: 'Order Preparing'
- `body` (TEXT): Body of notification. Ex: 'The merchant has started preparing your order.'
- `action_url` (VARCHAR 500): Deeplink into the app. Ex: 'groccerra://orders/ORD-2026-9912'
- `is_read` (BOOLEAN): Read status. Ex: *false*

Table: `inventory_ledgers`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `product_id` (UUID, FK): Target product. *Ex: '018b8f2a-...' *
- `variant_id` (UUID, FK): Target variant. Ex: '018b8f2a-...' (Null if no variant)
- `quantity_change` (INT): Positive (restock) or negative (sale). Ex: -2 (for a sale) or +50 (for a restock)
- `reason` (VARCHAR 100): Reason for change. Ex: 'sale', 'spoilage'
- `order_id` (UUID, FK): Link to order if 'sale'. Ex: '018b8f2a-...' (Null if spoilage)

Table: `platform_settings`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `key` (VARCHAR 255, Unique): Config string. Ex: 'PLATFORM_FEE_PERCENT'
- `value` (JSONB): Global config variables. Ex: `{"fee": 2.50}`
- `updated_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'

Table: `webhooks_log`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `provider` (VARCHAR 50): Target provider. Ex: 'stripe'
- `event_type` (VARCHAR 255): Target event. Ex: 'payment_intent.succeeded'
- `payload` (JSONB): Raw request body. Ex: `{"id": "evt_123", "object": "event"}`
- `processed_status` (VARCHAR 50): Job status. Ex: 'success'
- `created_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'

Table: `audit_logs`

- `id` (UUIDv7, PK): Unique identifier. *Ex: '018b8f2a-...' *
- `table_name` (VARCHAR 100): Affected table. Ex: 'products'
- `record_id` (UUID): The row mutated. *Ex: '018b8f2a-...' *
- `action` (VARCHAR 10): 'UPDATE', 'DELETE'. Ex: 'UPDATE'
- `old_data` (JSONB): Exact snapshots before. Ex: `{"base_price": 60.00}`
- `new_data` (JSONB): Exact snapshots after. Ex: `{"base_price": 65.00}`
- `changed_by` (UUID): Traceable ID. Ex: '018b8f2a-...' (The Admin who did it)
- `created_at` (TIMESTAMP): Audit timestamps. Ex: '2026-10-10 01:25:00+00'