

INTRODUCTION TO OS-LEVEL VIRTUALIZATION ON LINUX

Pedro Bruel phrb@ime.usp.br
May 25th, 2020





























OS-LEVEL VIRTUALIZATION

Virtualization

Partially emulates a system:

- Reproducible builds and deployment
- Environment versioning

Virtual Machines

Machine emulation:

- Hardware (helped by OS)
- OS
- File system
- Software stack

OS-Level Virtualization (On Linux) This talk!


Reuses the OS kernel, emulates:

- OS configuration
- File system
- Software stack

OS-LEVEL VIRTUALIZATION: SCOPE OF THIS TALK

Scope


- Why should you use containers?
 - Reproducible builds
 - · Environment versioning
 - It's also easier
- How do containers work?
- What tools are available?
 - LXC, Docker, chroot, Singularity, . . .




OS-LEVEL VIRTUALIZATION: SCOPE OF THIS TALK

Scope


- Why should you use containers?
 - Reproducible builds
 - · Environment versioning
 - · It's also easier
- How do containers work?
- What tools are available?
 - LXC, Docker, chroot, Singularity, . . .




OS-LEVEL VIRTUALIZATION ON LINUX



OS-LEVEL VIRTUALIZATION ON LINUX



How do Containers Work?




HOW DO CONTAINERS WORK?


Images used with permission:



containers = processes













container kernel features

8

containers use these Linux Kernel features

"container" doesn't have a clear definition, but Docker containers use all of these features.

♥ pivot_root ♥

set a process's root directory to a directory with the contents of the the container image

★ cgroups ★

limit memory/CPU usage for a group of processes



🕶 namespaces 💗

allow processes to have their own:

- → network → PIDs
- → mounts
 → users
 + more
- → hostname

- 1

🖈 capabilities 🖈

security: give specific permissions

security: prevent dangerous system calls

★overlay filesystems ★

this is what makes layers work! Sharing layers saves disk space & helps containers start faster

CONTAINERS FROM SCRATCH: OBTAING AN "IMAGE"

#!/usr/bin/bash

```
IMG_DIR="alpine_img"
IMG_REPO="https://us.images.linuxcontainers.org/images"
IMG_URL="$IMG_REPO/alpine/3.11/amd64/default/20200521_13:00/rootfs.tar.xz"
[ ! -d $IMG_DIR ] && \
    mkdir -p $IMG_DIR && \
    curl $IMG_URL | tar xJ -C $IMG_DIR
cd $IMG_DIR
```

CONTAINERS FROM SCRATCH: CREATING CGROUPS AND SETTING LIMITS

```
CGROUP_ID="MAC0475-145"
sudo cgcreate -g "cpu,cpuacct,memory:$CGROUP_ID"
sudo cgset -r cpu.shares=512 "$CGROUP_ID" # 1024 is 100% CPU
sudo cgset -r memory.limit_in_bytes=100000000000 "$CGROUP_ID"
```

CONTAINERS FROM SCRATCH: LAUNCHING THE ALPINE CONTAINER

```
HOSTNAME="alpine-container"
sudo cgexec -g "cpu,cpuacct,memory:$CGROUP_ID" \
    unshare -fmuipn --mount-proc \
    chroot "$PWD/" \
    /bin/sh -c "PATH=/bin && mount -t proc proc /proc && hostname $HOSTNAME && sh"

# Cleanup:
sudo cgdelete cpu,cpuacct:/$CGROUP_ID
sudo cgdelete memory:/$CGROUP_ID
```