

Mod Code Generator Manual

Table of Contents

1 Introduction.....	3
2 Code of practice for modeling in Modelio environment.....	3
2.1 Model Creation.....	3
Create New Project.....	3
Remove Unused Elements.....	3
Rename Model Package.....	3
2.2 Type Package Creation.....	4
Create Type Package.....	4
Create Model Types.....	4
2.3 Model Component Creation.....	5
Create New Component.....	5
Create Component Interfaces.....	5
Create Component Interface Signals.....	5
Create Component Activity.....	6
Define Component Activity.....	6
Create Next Components.....	7
2.4 Model Package Creation.....	7
Create Package Interfaces.....	7
Create Package Interface Signals and Structures.....	8
Create Package Activity.....	8
Define Package Activity.....	8
2.5 Modeling Rules.....	9
Model Rules.....	9
Component Interface Rules.....	10
Component Activity Rules.....	10
Package Interface Rules.....	11
Package Activity Rules.....	12
Naming Convention Rules.....	13
2.6 Naming Convention.....	13
2.7 List of Actions.....	14
3 Mod Code Generator (MCG).....	14
4 Modeling example with code generation.....	14

1 Introduction

2 Code of practice for modeling in Modelio environment

Although Modelio itself is used mainly as UML modeling tool, the modeling environment will be used in different way to allows code generation with MCG, i.e. modeling will be focused more on data flow through model elements and interaction of signals (called signal processing or actions), than on representation of model structure and its elements.

The main objective of model package is to define couplings between different model components (data flow from one component to another). The model package is used also to define main input and output interface of entire model.

Each model component is treated as a separate module and MCG will generate separate C source file for each component. Components are used to define operations between signals (also known as actions).

Type package is used only to define allowed types of signals, which will be used later to define interface signals.

Please see below code of practice for modeling in Modelio environment, which will give you some introduction over modeling rules and as well please see Modeling Rules where you can find list of rules that you have to follow during modeling.

2.1 Model Creation

Create New Project

Open Modelio environment, then select **File → Switch** workspace and select directory, where you would like to place new model.

After that select **File → Create a project**. In **Project name** property type desired project name, then click **Create the project**.

Remove Unused Elements

Select **Configuration → Libraries**, then remove all **Local libraries** and **Remote libraries**.

After that go to **Modules** tab and disable all modules, then close **Project configuration** window.

Expand all model elements in model tree. Find and remove **LocalModule** element.

Rename Model Package.

Locate model package under UML sub-project element, click on it and press F2 on keyboard, then type desired model package name.

2.2 Type Package Creation

Create Type Package

Right-click on UML sub-project element and select **Create element → Package**. Click on new package, press F2 on keyboard and name it as Types.

Create Model Types

Define all data types listed under column **Types** in Table 2.2.1: Applicable Data Types.

Right-click on type package and select **Create element → Data Type**. Click on new data type, press F2 on keyboard and name new data type as per column **Type**. Repeat the process for the rest of required data types.

The table Table 2.2.1: Applicable Data Types points which data types are applicable for specific interface type of Component or Package model element:

Table 2.2.1: Applicable Data Types

Type	Component Interface	Package Interface
INT8	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
INT16	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
INT32	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
INT64	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
UINT8	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
UINT16	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
UINT32	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
UINT64	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces

FLOAT32	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
FLOAT64	Input Interfaces Output Interfaces Local Data	Input Interfaces Output Interfaces
DATA		Local Data

2.3 Model Component Creation

Create New Component

Right-click on model package and select **Create element → Component**. Click on new component element, press F2 on keyboard and then give desired name to it.

Create Component Interfaces

Create all interfaces listed under **Interface Type** column in Table 2.3.1: Component Interface Types

Right-click on component and select **Create element → Interface**. Click on new interface type, press F2 on keyboard and name new interface type as per column **Interface Type**. Repeat the process for the rest of required interface types.

Table 2.3.1: Component Interface Types

Interface Type	Attribute Meaning	Interface Objectives
Input Interface	Signal	Defines input interface of the component, i.e. list of signals, which are inputs to the component.
Output Interface	Signal	Defines output interface of the component, i.e. list of signals, which are outputs from the component.
Local Data	Signal	Defines local signals within the component, i.e. list of signals, which are used internally within the component to exchange data between actions.

Create Component Interface Signals

Right-click on desired interface type and select **Create element → Attribute**. Double-click on new attribute. In **Name** property type desired name and start typing desired type in **Type** property then press “Ctrl + Space” combination on keyboard to see auto-completion list.

Attribute meaning for each interface type is defined by **Attribute Meaning** column in Table 2.3.1: Component Interface Types.

Please refer to Table 2.2.1: Applicable Data Types for list of data types, which could be used under each component interface and please follow Component Interface Rules.

If you wish to pass signal between two components, then source component and target component need to have signal with same name and data type under appropriate interface, i.e. under output interface of source component and input interface of target component.

Create Component Activity

Right-click on component and select **Create diagram**, then select **Activity diagram** from available list of diagram. You should now find **Activity** element under your component. Remove from **Activity** following elements:

1. **this: <component name>**
2. **locals**

Once **Activity** is created, please find **Activity diagram** under **Activity**, click on it and press F2 on keyboard, then enter desired name for **Activity diagram**.

Define Component Activity

This process is composed from following basic steps:

1. Move interface signals into diagram space
2. Define component actions
3. Define first input signal if needed
4. Connect signals and action

During this process please follow Component Activity Rules.

Move interface signals into diagram space

Open **Activity diagram**, then drag and drop all interface signals into diagram space. You can drag and drop signal again if you need to use it more than one time.

Define component actions

Actions define interactions between interface signals. Please see list of allowed actions between signals and their description in Table 2.7.1: Applicable Action Types.

Within **Control nodes** box select **Action – Create an Opaque Action**, then click on diagram space where you wish to place new action. Double-click on new action.

In **Name** property type desired action type from Table 2.7.1: Applicable Action Types.

Define first input signal if needed

Some kind of actions require to distinguish which input signal is first in action equation in order to compute correct result. Please see column ***FIRST* marker needed** in Table 2.7.1: Applicable Action Types to find out which actions require to point first input signal.

As example:

Subtraction action $y=a-b-c$ will give different result than $y=b-a-c$.

If you are using action, which require to point first input signal, then type in **Description** field (you can open it by double-click on action):

FIRST marker, then name of first input signal, then *FIRST* marker again, keeping one white space separation between markers and signal name.

As example:

FIRST first_input_signal_name *FIRST*

Connect signals and actions

Within **Flows** box select **Object Flow – Create an Object Flow**, then connect component elements (signals and actions) on diagram space.

Create Next Components

Once component is defined you can create further components following steps since Create New Component.

2.4 Model Package Creation

Create Package Interfaces

Create all interfaces listed under **Interface Type** column in Table 2.4.1: Package Interface Types

Right-click on package and select **Create element → Interface**. Click on new interface type, press F2 on keyboard and name interface type as per column **Interface Type**. Repeat the process for the rest of required interface types.

Table 2.4.1: Package Interface Types

Interface Type	Attribute Meaning	Interface Objectives
Input Interface	Signal	Defines input interface of the package, i.e. list of signals, which are inputs to the package.
Output Interface	Signal	Defines output interface of the package, i.e. list of signals, which are outputs from the package.
Local Data	Structure	Defines local structures within the package, i.e. list of structures, which are used internally within the package to exchange data between components.

Create Package Interface Signals and Structures

Right-click on desired interface type and select **Create element → Attribute**. Double-click on new attribute. In **Name** property type desired name and start typing desired type in **Type** property then press “Ctrl + Space” combination on keyboard to see auto-completion list.

Attribute meaning for each interface type is defined by **Attribute Meaning** column in Table 2.4.1: Package Interface Types.

Please refer to Table 2.2.1: Applicable Data Types for list of data types, which could be used under each package interface and please follow Package Interface Rules.

Please be aware that meaning of attributes under Local Data interface of model package is different than in case of other interfaces. These attributes are representing names of structures, which will be used to exchange data between model components on activity diagram of model package.

Each component occurrence on activity diagram of model package need to have separate structure, which represents outputs from that component.

At minimum create two attributes under Local Data interface and name them **Input Interface** and **Output Interface**. These attributes will represent Input and Output Interface of model package.

Create Package Activity

Right-click on package and select **Create diagram**, then select **Activity diagram** from available list of diagram. You should now find **Activity** element under your package. Remove from **Activity** following elements:

1. **this: <component name>**
2. **locals**

Once **Activity** is created, please find **Activity diagram** under **Activity**, click on it and press F2 on keyboard, then enter desired name for **Activity diagram**.

Define Package Activity

This process is composed from following basic steps:

1. Move structures and components into diagram space
2. Connect structures and components

During this process please follow Package Activity Rules.

Move structures and components into diagram space

Open **Activity diagram**, then drag and drop all interface structures into diagram space, then drag and drop all components into diagram space. You can drag and drop structure or component again if you need to use it more than one time.

Connect structures and components

Within **Flows** box select **Object Flow – Create an Object Flow**, then connect package elements (structures and components) on diagram space.

Please be aware that connection on activity diagram between two components through structure is not enough to pass data from one component to another. To pass signal from one component to another, apart from connection on activity diagram of model package, the output interface of source component and input interface of target component need to have signal with same name and data type, as pointed in Create Component Interface Signals.

2.5 Modeling Rules

Model Rules

MR#1 RULE

Each model created within Modelio environment **shall** have following generic layout in order to allow proper code generation with MCG:

1. <model package>
 - a) <model component 1>
 - b) <model component 2>
 - c) ...
 - d) <model component n>
2. <type package>

MR#2 RULE

Each model **shall** have exactly one model package.

MR#3 RULE

Each model **shall** have exactly one type package.

MR#4 RULE

Each model package **shall** have at least one model component.

MR#5 RULE

<type package> **shall** be named Types.

MR#6 RULE

<type package> **shall** have following types:

- INT8
- INT16
- INT32
- INT64
- UINT8
- UINT16

- UINT32
- UINT64
- FLOAT32
- FLOAT64
- DATA

Component Interface Rules

CIR#1 RULE

Model component **shall** have all interface types listed in Table 2.3.1: Component Interface Types.

CIR#2 RULE

Output interface of model component **shall** have at least one signal.

CIR#3 RULE

Signals of model component **shall** be created only under interface types pointed in Table 2.3.1: Component Interface Types.

CIR#4 RULE

Signals of model component **shall** use only applicable data types pointed in Table 2.2.1: Applicable Data Types.

CIR#5 RULE

Each input interface signal of model component **shall** have unique name in comparison to other interface signals under the same component.

CIR#6 RULE

Each output interface signal of model component **shall** have unique name in comparison to other interface signals under the same component and output interface signals of other components.

CIR#7 RULE

Each local data interface signal of model component **shall** have unique name in comparison to other interface signals under the same component.

Component Activity Rules

CAR#1 RULE

Actions of model component **shall** use only applicable action types listed in Table 2.7.1: Applicable Action Types.

CAR#2 RULE

Actions of model component **shall** be connected only with interface signals of model component.

CAR#3 RULE

Each action of model component **shall** have required number of input signals and required number of output signals as per its definition under **Definition** column in Table 2.7.1: Applicable Action Types.

CAR#4 RULE

Each action of model component, which require to distinguish first input signal as per ***FIRST* marker needed** column in Table 2.7.1: Applicable Action Types **shall** point first input signal in its **Description** field between ***FIRST*** markers in following way: ***FIRST*** first_input_signal_name ***FIRST***

CAR#5 RULE

There **shall** be exactly one white space separation between ***FIRST*** markers in action **Description** and name of first input signal.

CAR#6 RULE

All interface signals of model component **shall** be connected with other elements on activity diagram of model component.

CAR#7 RULE

Each input interface signal of model component **shall** be connected only as input to another signal or action.

CAR#8 RULE

Each output interface signal of model component **shall** be connected only as output from another signal or action.

CAR#9 RULE

Each local data interface signal of model component **shall** be connected as:

- input to another signal or action, and
- output from another signal or action.

CAR#10 RULE

Any interface signal of model component **shall** have only one input in form of another signal or action, apart from input interface signals, which **shall not** have any input connection.

Package Interface Rules

PIR#1 RULE

Model package **shall** have all interface types listed in Table 2.4.1: Package Interface Types.

PIR#2 RULE

Input and output interface of model package **shall** have at least one signal.

PIR#3 RULE

Local data interface of model package **shall** have at least **Input Interface** and **Output Interface** structures.

PIR#4 RULE

Signals of model package **shall** be created only under input and output interface types pointed in Table 2.4.1: Package Interface Types.

PIR#5 RULE

Structures of model package **shall** be created only under local data interface type pointed in Table 2.4.1: Package Interface Types.

PIR#6 RULE

Signals and structures of model package **shall** use only applicable data types pointed in Table 2.2.1: Applicable Data Types.

PIR#7 RULE

Each input interface signal of model package **shall** have unique name in comparison to other interface signals and structures under the same package.

PIR#8 RULE

Each output interface signal of model package **shall** have unique name in comparison to other interface signals and structures under the same package.

PIR#9 RULE

Each local data interface structure of model package **shall** have unique name in comparison to other interface signals and interface structures under the same package.

PIR#10 RULE

Each local data interface structure of model package **shall** have different name than source component element of the structure.

PIR#11 RULE

Each component occurrence on activity diagram of model package **shall** have individual structure, which represents output from that component.

Package Activity Rules

PAR#1 RULE

Components of model package **shall** be connected only with local data interface structures of model package.

PAR#2 RULE

All local data interface structures of model package **shall** be connected with other elements on activity diagram of model package.

PAR#3 RULE

Input Interface local data interface structure of model package **shall** be connected only as input to component.

PAR#4 RULE

Output Interface local data interface structure of model package **shall** be connected only as output from another structure of component.

PAR#5 RULE

Each other local data interface structure (other than **Input Interface** and **Output Interface** structures) of model package **shall** be connected as:

- input to component or **Output Interface** structure, and
- output from component.

PAR#6 RULE

Any local data interface structure of model package **shall** have only one input in form of component, apart from:

- Input Interface structure, which **shall not** have any input connection, and
- Output Interface structure, which **shall** have at least one input in form of other structure or component.

PAR#7 RULE

To pass signal from one component to another, apart connection between two components via local data interface structure on activity diagram of model package, the output interface of source component and input interface of target component **shall** have signal of same name and data type.

Naming Convention Rules

NCR#1 RULE

Names of model elements **shall** contain only allowed characters listed in Table 2.6.1: Applicable Characters.

NCR#2 RULE

Names of model elements **shall** start with upper or lower case letters only.

NCR#3 RULE

Names of model elements **shall not** contain white spaces.

NCR#4 RULE

Names of model elements shall be different than action types

2.6 Naming Convention

Table 2.6.1: Applicable Characters defines list of applicable characters within name of any model element.

Table 2.6.1: Applicable Characters

Character type	Allowed characters
Upper case letters	A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
Lower case letters	a b c d e f g h i j k l m n o p q r s t u v w x y z
Digits	1 2 3 4 5 6 7 8 9 0
Special characters	_ -

2.7 List of Actions

Table 2.7.1: Applicable Action Types defines list of applicable interactions (actions) between signals on diagram space of component element.

Table 2.7.1: Applicable Action Types

Action type	Definition	*FIRST* marker needed
ADD	Addition arithmetic operation. Requires at least two input signals ¹⁾ . Requires exactly one output signal ²⁾ .	
SUB	Subtraction arithmetic operation. Requires at least two input signals ¹⁾ . Requires exactly one output signal ²⁾ .	Yes

1) Input Interface or Local Data signal could be connected as input signal to that action.

2) Local Data or Output Interface signal could be connected as output signal from that action.

3 Mod Code Generator (MCG)

4 Modeling example with code generation