

SERIES AM-10T  
AIR AMPLIFIERS



GENERAL FEATURES - AM-10T	
Materials	Aluminium
Air inlet port	G-1/8" F
Inlet diameter	Ø 19
Outlet diameter	Ø 19
Air supply pressure	max 7 bar
Recommended hose	Ø 6x1 - Ø 8x1
Weight	95 g

PERFORMANCES AND CONSUMPTION TABLE

OPENING 90°					
SUPPLY PRESSURE bar	CONSUMPTION NI/min	FLOW-RATE NI/min	AMPLIFICATION RATIO	VACUUM mbar	NOISE LEVEL dBA
2	76	349,9	4,6	65	63
3	101	449,8	4,4	100	65
4	126	506,4	4,0	130	66
5	153	558,1	3,6	155	68
6	178	621,4	3,5	185	70
OPENING 180°					
2	158	533,12	3,4	100	76
3	216	643	3,0	155	80
4	283	741,4	2,6	190	85
5	341	816,34	2,4	220	90
6	391	849,6	2,2	240	92

SERIES AM-15T  
AIR AMPLIFIERS



GENERAL FEATURES - AM-15T	
Materials	Aluminium
Air inlet port	G-1/8" F
Inlet diameter	Ø 19
Outlet diameter	Ø 19
Air supply pressure	max 7 bar
Recommended hose	Ø 8x1 - Ø 10x1
Weight	100 g

PERFORMANCES AND CONSUMPTION TABLE

OPENING 90°					
SUPPLY PRESSURE bar	CONSUMPTION NI/min	FLOW-RATE NI/min	AMPLIFICATION RATIO	VACUUM mbar	NOISE LEVEL dBA
2	100	899,6	9,0	30	70
3	133	1132,9	8,5	45	74
4	168	1332,8	7,9	60	76
5	204	1516	7,4	75	78
6	244	1649,3	6,8	90	79
OPENING 180°					
2	225	1366	6,1	60	80
3	299	1666	5,6	95	84
4	373	1949,2	5,2	130	88
5	443	2165,8	4,9	160	89
6	509	2265,8	4,4	180	90