



YC(D)Q2 Series

Compact Cylinder


- In Magnet, Without Magnet
- Female(Standard), Male Thread




YCQ2B-12x5D~YCQ2B-12x30D
YCDQ2B-12x5D~YCDQ2B-12x30D
(ø12, ø16, ø20, ø25)




YCQ2B-12x5DM~YCQ2B-12x30DM
YCDQ2B-12x5DM~YCDQ2B-12x30DM
(ø12, ø16, ø20, ø25)




YCQ2B-32x5D~YCQ2B-32x50D
YCDQ2B-32x5D~YCDQ2B-32x50D
(ø32, ø40)



YCQ2B-32x5DM~YCQ2B-32x50DM
YCDQ2B-32x5DM~YCDQ2B-32x50DM
(ø32, ø40)



YCQ2B-50x10D~YCQ2B-50x50D
YCDQ2B-50x10D~YCDQ2B-50x50D
(ø50, ø63, ø80)



YCQ2B-50x10DM~YCQ2B-50x50DM
YCDQ2B-50x10DM~YCDQ2B-50x50DM
(ø50, ø63, ø80)

SPECIFICATION

Fluids	Air
Certified Pressure	15bar
Maximum Operation Pressure	10bar
Minimum Operation Pressure	0.5bar (ø 12, ø 16 : 0.7bar)
Ambient & Fluid Temp.	5~60°C (41~140°F)
Lubrication	Not Required(Use ISO VG32 #)
Cussion	None
Rod End Screw	Female Nut(standard), male Nut(option)
Tolerance of Screw	2nd grade of KS
Allowance of Stroke Distance	+ 1
Supporting Type	Standard
Mounting	Pierce(Basic), Both Ends Tap(Option)

The Material of Parts

- Tube : Aluminium Extruding
- Piston : Aluminium
- Piston Rod : ø 12~ ø 25-ST304
ø 32~ ø 80-Carbon Iron
- Seals : NBR
- Snap Ring : HSWR1
- Hex Nut : Carbon Iron
- Bush : DU Bush
- Head Cover : Aluminium
- Magnet : Rubber Magnet

※ The specification on each item can be amended without any prenotice to improve a performance.
※ The specification on each item can be different from actual specification.

ORDERING NO.

YCDQ2 B - 20 × 30 D M

Magnet is Attached or Not		Mounting		Tube Diameter	Cylinder Stroke			Operating Method		Rod Type		
YCQ2	Non Built-in	A	Both Ends Tap	12 : 12mm	Cylinder diameter	Cylinder Stroke(mm)		Port Size & Thread	D	Double-acting type	Non-marked	Nut(Basic)
YCDQ2	Built-in	B	Pierce	16 : 16mm	ø 12, ø 16	5, 10, 15, 20, 25, 30					M5×0.8	M
				20 : 20mm	ø 20, ø 25	5, 10, 15, 20, 25, 30, 35, 40, 45, 50						
				25 : 25mm	ø 32, ø 40	5, 10, 15, 20, 25, 30, 35, 40, 45, 50, 75, 100		G 1/8				
				32 : 32mm	ø 50, ø 63	10, 15, 20, 25, 30, 35, 40, 45, 50, 75, 100		G 1/4				
				40 : 40mm	ø 80	10, 15, 20, 25, 30, 35, 40, 45, 50, 75, 100		G 3/8				
				50 : 50mm								
				63 : 63mm								
				80 : 80mm								