

# Stereo Matching Technique using Belief Propagation

Annual Progress Seminar-III

By

**Chitra Suresh**

Under the Guidance of

**Dr.Kushal R.Tuckley**

Department of Electronics Engineering  
Ramrao Adik Institute of Technology,  
Nerul, Navi Mumbai

# Outline

- ➊ Introduction to **Stereo matching or Stereo Vision problem**
- ➋ Mathematical Representation of **Stereo matching**
- ➌ Models used for **Stereo matching**
- ➍ **Belief Propagation (BP) Algorithm**
- ➎ Implementation of **BP Algorithm**
- ➏ **Results & Issues**
- ➐ **Conclusion & Future Work**
- ➑ **Bibliography**

# Introduction to Stereo matching or Stereo Vision problem

- The stereoscopic images or stereo pair consists of two images of the same scene taken slightly horizontally separated points from the left view and the right view.
- The parallax effect also present in stereoscopic images, A parallax is ability to see an object at two different views.
- Due to parallax effect in stereoscopic images , objects near the camera will represent more to the right in the left image and more left in the right image.
- The horizontal displacement of an object left and right view depends on the distance from the object to the camera view points.

# Introduction to Stereo matching or Stereo Vision problem



**Figure:** The principle of stereoscopic images


Objects close to the camera will be placed more to the right in the left image - and more to the left in the right image.

Faraway objects, such as the sun and the cloud, will be located at approximately the same position in both images.

# Introduction to Stereo matching or Stereo Vision problem

- To find the matching pixel in left and right image for stereo pair image is known as **stereo vision, stereo correspondence or stereo matching**.
- In stereo matching aim is to find the matching pixel for a stereo pair image as input image which consists of left and right image and result of finding matching pixel is saved as Depth map or disparity map.
- The disparity is horizontal distance between two matching pixel and horizontal pixel distance for each pixel coordinates is nothing but Disparity map.

# Introduction to Stereo matching or Stereo Vision problem



**Figure:** (a)Left Image (b)Right Image(c)Depth map by Global Method(d)Ground truth

# Classification of Stereo algorithm

- The stereo algorithms based on intensity profile are **Area-based and Feature- based algorithm**
- The constrains in area- based algorithm is to find the optimal size of the window
- The feature-based algorithms is restricted to using only specific feature,that only yield sparse disparity maps
- Global algorithm are based on baysian approach finds disparity as a energy minimization problem
- Global stereo algorithm are **Graph cut and belief propagation**

# Applications of Depth Map or Disparity Map


- View Interpolation can done using stereo pair and Depth map



Input



Depth Map



Novel view

- Image sequence analysis in entertainment, information transfer and for reconstruct 3D model sequences





# Applications of Depth Map or Disparity Map

- Used for robot navigation and depth information is used for object recognition to separate occluded image components



- Scientific applications such as extracts information from aerial surveys and for calculation of contour maps
- Gaze correction for video conferencing

# Mathematical Representation of Stereo matching

- *The stereo matching problem can be expressed in terms of Markov*
- The markov network model is a probability graphical model which consists of undirected graph of 'n' nodes with pair wise potentials as compatibility function
- Y is evidence or observed state node,  $X_s$  is hidden node state, state of each nodes 'i' represent as  $X_i$  for given evidence, To find most likely set of nodes  $\{X_1, X_2, X_n\}$  for given evidence 'Y' and compatibility between neighboring nodes can be expressed as a joint probability distribution function of  $n$  nodes.

$$\begin{aligned} & \bullet P(X_1, X_2, X_n/Y) \\ &= \prod_{\text{All nodes } s} \phi(X_s, Y) \prod_{(s, t) \in \text{All neighboring nodes}} \phi(X_s, X_t) \end{aligned}$$

# Mathematical Representation of Stereo matching

- The stereo matching problem can be expressed in terms of probability theory
- Markov network model is analogous to Bays theorem
- According to Bays theorem :  $P(X/Y) = P(Y/X)*P(X)/P(Y)$
- Y is stereo set and X is disparity map,  $P(Y) = 1$  (assumption)
- The disparity map can be obtained by maximizing probability of disparity map to stereo set i.e.  $P(X/Y)$  and probability can be expressed in terms of Datacost and smoothness cost functions

# Mathematical Representation of stereo Algorithm

**Table:** Stereo matching problem as probability theory and markov network

S.No	Markov network	Probability Theory
1	Maximizing joint probability distribution i.e $P(X_1, X_2, ..X_n/Y)$	Maximizing probability of disparity map to stereo set i.e. $P(X/Y)$
2	Markov state	Set of pixels in with assigned disparity value
3	For given Evidence Y	For given set of stereo images



# Mathematical Representation of Stereo Algorithm

- To find Maximum A Posteriori (MAP) estimation in markov network is NP hard means to get a solution for such problem takes unthinkably long time because each pixel (node) in disparity map can take any value in disparity space (state)
- For example for Tsukuba image of size  $384 \times 288 = 110592$  pixel with 16 disparity levels gives  $16^{110592}$  combinations, So it is difficult to find solution
- Belief Propagation algorithm is approximate solution to estimate Maximum a Posteriori (MAP) in reasonable amount of time


# Model used for Stereo algorithm

- The probability of stereo set to disparity map .i.e.  $P(Y/X)$  and the probability of disparity map i.e.  $P(X)$  is expressed as matching cost term and smoothness cost term.
- The data cost is based on the intensity differences between the two pixels. The Sum of Absolute Difference (ABS) or Sum of Square Difference (SSD) functions are used as data cost
- smoothness cost models are Pott's model, linear and quadratic models
- The Pott's model is a binary penalizing function with a single tunable variable. This value controls how much smoothing is applied.
- The linear and quadratic models have an extra parameter  $K$ .  $K$  is a truncation value that caps the maximum penalty.

# Model used for Stereo algorithm :Pott's model, Linear and Quadratic models



Truncated linear model  $f(n) = \lambda \times \min(|n|, K)$



Truncated quadratic model.  $f(n) = \lambda \times \min(n^2, K)$

# Belief Propagation (BP) Algorithm

- The belief propagation algorithm was proposed by Pearl in 1988 for finding exact marginal's on graphs known as trees that contain no loops. It can be applied to graphs with loops also
- The Loopy belief propagation is an approximate inference algorithm which keep passing the messages around markov state or node until stable belief state is reached, It is iterative algorithm, messages will converge on doing iterations.
- There are three main steps finding Maximum a Posteriori (MAP) estimation or beliefs in Belief Propagation algorithm
  - 1 Normalization
  - 2 Message update or generation
  - 3 Finding belief



# Belief Propagation (BP) Algorithm





Figure: Steps in BP algorithm

# Implementation of BP Algorithm

- Block diagram for implementation of Global Stereo Algorithm using Belief Propagation




- Stereo images(Rectified images) are taken as input
- The software used for simulation is MATLAB version 2015
- The stereo images for testing are from data sets of Middlebury computer vision web site ([vision.middlebury.edu](http://vision.middlebury.edu)).

# Implementation of BP Algorithm

- To find Initial depth map as a preprocessing stage two methods are used.
- First one is using MATLAB inbuild function "DisparityMap" in computer vision toolbox
- Second method is minimum index method by using sum of absolute difference function
- Initial depth map generated by both methods are optimized by Belief Propagation algorithm

# Implementation of BP Algorithm: Results



(a) Left Image


(b) Right Image

(c) Initial Depth Map

(d) Depth Map by BP

(e) Ground Truth

# Implementation of BP Algorithm: Results



(a) Left Image


(b) Right Image

(c) Initial Depth Map

(d) Depth Map by BP

(e) Ground Truth

# Implementation of BP Algorithm: Results



(a) Left Image

(b) Right Image

(c) Initial Depth Map

(d) Depth Map by BP

(e) Ground Truth

# Implementation of BP Algorithm:Results




Figure: Representation of pot stereo image Initial D.M by Minimum Index

# Implementation of BP Algorithm:Issues


- The label or disparity level at present which is fixed to 16
- The issues faced at this stage is that ,after optimizing depth map with Belief Propagation algorithm some portion in depth map are overlapped
- At this stage concluded that logical error exists in the programme and it was difficult to solve
- At this moment ,The depth map generated by minimum index method and standard method are compared ,Manuscript is send to scopus indexed journal,awaiting for acceptance



# Implementation of BP Algorithm

- The manuscript title , " Simplistic approach for Computing Disparity map" is submitted to Malaysian Journal of Computer Science on 14 October 2017
- A simple technique called 'minimum index method' is used for the computation of disparity map which is compared with popular method available in most of standard computation tools in Matlab.
- The standard method used is inbuild function 'DisparityMap' from computer vision tool it box in MATLAB.
- The simulated results shows that in minimum index method objects in depth map are better recognizable than standard method. The mean square error less in minimum index method than standard method.

# Implementation of BP Algorithm: Results



(a) Left Image (b) Right Image (c) Depth map by Semi Global Block method (d) Depth map by Minimum Index Method (e) Ground truth

# Implementation of BP Algorithm:Results

Table: Mean Square Error for both methods for test images

Stereo Image	Minimum Index Method (MSE)	Standard Method (MSE)
Baby	2150	16950
Bowling	3074	19526
Cloth	2177	20137
Pot	3143	17229

# Implementation of BP Algorithm

- The following parameters are used to implement BP on stereo images like Tsukuba and Aloe vera plant
  - 1 The disparity levels or labels are 0 to 15
  - 2 DataCost using linear model ie.sum of absolute difference
  - 3 SmoothnessCost using truncated linear model, truncated at 2,with  $\lambda = 20$
  - 4 Message update is Min-sum Optimization algorithm
  - 5 Number of iterations is 2

# Implementation of BP Algorithm: Results



Depth Map using BP for tsukuba




Ground Truth map for tsukuba

# Implementation of BP Algorithm: Results



Depth Map using BP for aloe Vera plant



Ground Truth map for aloe Vera plant

# Implementation of BP Algorithm: Issues

- To write a code for message update in BP algorithm is challenging one. These messages are vectors and size of this vector depends on disparity level used. In message update function not able to store updated message values.
- The time taken to run iterative BP on stereo images (Tsukuba and Aloe Vera plant) are 2 hours for 1 iterations and moreover run time for 1 iteration is different for different machines
- The pointers used for message update function in MATLAB not able to store the updated messages due to column wise matrix memory in MATLAB

# Implementation of BP Algorithm: Results



Depth Map using BP for 32 iterations



# Conclusion

- Literature survey is done to find Gap, So that to do further research either to reduce runtime of iterative Belief Propagation algorithm or to find better Depth Map
- The clarity of Depth Map not only depends on either linear or quadratic model used as well as depends on the values of parameters like  $\lambda$  (tunable variable) and  $k$  is (truncation variable)
- The challenges faced while programming message update function is solved by using MEX function in message update step
- After using MEX function run time of BP algorithm also reduced, for more than 30 iterations getting refined depth map and it is taking only approximately 1 to 1.5 sec

# Future work

- ① At present Programm for BP is used linear model,It can be tested for Quadratic model also
- ② The belief propagation algorithm can be tested on different stereo images
- ③ The role of parameter in models used for BP Algorithm is important factor to get clear depth map,next is going to work on this task

# Bibliography

-  Tappen,M.F. and Freeman,W.T., “ Comparision of graph cuts with BP for stereo,using identical MRF parameters ”, *In IEEE International conference on computer vision*.
-  Pedro F. Felzenszwalb,Daniel P.Huttenlocher, “A Efficient Belief Propagation For Early Vision”, *International Journal Of Computer Science* , Vol. 41-54, No.2, February, pp, 2006.
-  Yu-Chang Andnelson Chang, “Low Memory Cost Block-Based Belief Propagation For Stereo Correspondence”, *IEEE Transisition*, 1-4244-1017-7187
-  Chia-Kai Liang,Chao-Chung Cheng,Yen-Cheieh Lai, “A Hardware-Efficient Belief Propagation”, *IEEE Transactions On Circuits And Systems For Video Technology* Vol;21,No.5,May,pp, 2011.

# Bibliography

-  Li Zhou, Tao Sun, Yuanzhi Zhan and Jia Wang, "Software and Hardware Implementations of Stereo Matching, ", *International Journal of Electronics and Informatics*, Vol.7, No.4 (2014), pp.37-562, No.1, 2014.
-  <http://nghiaho.com/notes/Markov Random Field,Loopy Belief Propagation,stereovision>.
-  Anders Olofsson, "Modern Stereo Correspondence Algorithms ,Investigation and evalution ",*Department of Electrocral Engineering,Linkoping University*, 581 83 Linkoping,Sweden, June, 2010.
-  J. Sun, N. N. Zheng and H. Y. Shum,"Stereo Matching Using Belief Propagation", *IEEE Trans. Pattern Analysis and Machine Intelligence*, vol. 7, no. 25, (2003), pp. 787-800.

# Thank You...