

Student:
James Collins

Email:
collins222@usf.edu

Time on Task:
0 hours, 36 minutes


Progress:
100%

Report Generated: Saturday, April 11, 2026 at 4:40 PM

Hands-On Demonstration


Part 1: Identifying Failed Logon Attempts on Windows Systems

8. Make a screen capture showing the **Security Event Properties** dialog box on the vWorkstation.




Part 2: Monitoring Network Activity with Snort


17. Make a screen capture showing the updated Pass Lists page.




31. Make a screen capture showing the active Snort status on the LAN interface.



36. Make a screen capture showing the successful ping results.




41. Make a screen capture showing the ICMP alerts in the Snort Active Log.



Applied Learning

Part 1: Identifying Failed Logon Attempts on Linux Systems

11. Make a screen capture showing the edited rsyslog.conf file.



```
# Receive log messages via rsyslogd
#inputModule imtcp
#inputTCPServerRun 514

### GLOBAL DIRECTIVES ###

# Where to place auxiliary files
#WorkDirectory /var/lib/rsyslog

# Use default timestamp format
#ActionFileDefaultTemplate RSDLOG TraditionalFormat

# File syncing capability is disabled by default. This feature is usually not required,
# but useful when an extreme performance hit
#ActionFileDisableSync on

# Include all config files in /etc/rsyslog.d/
#IncludeConfig /etc/rsyslog.d/*.conf

# Turn off message reception via local log socket,
# local messages are retrieved through imjournal now.
#DisableLocalLogging on

# File to store the position in the journal
#IfJournalStateFile imjournal.state

### RULES ###

# Log all kernel messages to the console.
# Logging much also clutters up the screen.
#kern.* /dev/console

# Log anything (except mail) of level info or higher.
# Don't log private authentication messages!
*.info;mail.none;authpriv.none;cron.none /var/log/messages

# The authpriv file has restricted access.
#authpriv.* /var/log/secure

# Log all the mail messages in one place.
#mail.* ~var/log/maillog

# Log cron stuff
#cron.* /var/log/cron

# Everybody gets emergency messages
#emerg.* /dev/console

# Save new errors of level crit and higher in a special file.
#*.crit /var/log/spooler


# Save boot messages also to boot.log
#boot.* /var/log/boot.log

### BEGIN FORWARDING ###
# The statement between the begin... and define a SIMPLE forwarding
# rule. They belong together, do NOT split them. If you create multiple
# forwarding rules, duplicate the whole block!
# Remote logging (in web TCP for reliable delivery)
#
# An on-disk queue is created for this action. If the remote host is
# down, messages are spooled to disk and sent when it is up again.
#ActionQueueFileName fwd(1) # unique name prefix for spool files
#ActionQueueMaxDiskSpace 1g # 1gb space limit (use as much as possible)
#ActionQueueMaxCountDown 50 # save messages to disk on shutdown
#ActionQueueType linkedlist # run asynchronously
#ActionResumeRetryCount -1 # infinite retries if host is down
# Remote host as: name[:port], e.g. 192.168.1.1:514, port optional
#*.* @remote-host:514
#*.* @storage.googleapis.com:514
### END OF THE FORWARDING RULE ###
```


Implementing Security Monitoring and Logging (4e)

Fundamentals of Information Systems Security, Fourth Edition - Lab 08

22. **Make a screen capture** showing the **failed login attempts**.



24. **Make a screen capture** showing the **last 10 log messages**.



Part 2: Monitoring File Integrity with Tripwire

12. Make a screen capture showing the Object Summary section for the Tripwire report.

```

vWorkstation
2026-04-11 16:28:59
James Collins

*** Continuing...
Write report file: /var/lib/tripwire/report/20260411-122812.twr

Open Source Tripwire(R) 2.4.3-7 Integrity Check Report

Report generated by: root
Report created on: Sat 11 Apr 2026 01:20:12 PM PDT
Database last updated on: Never

=====
Report Summary:
=====
Host name: 202601.localdomain
Host IP address: 172.30.0.2
Host ID: None
Policy file used: /etc/tripwire/tw.pol
Configuration file used: /etc/tripwire/tw.cfg
Database file used: /var/lib/tripwire/202601.localdomain.tdb
Command line used: /usr/sbin/tripwire --check

=====
Rule Summary:
=====

# Section: Unix File System

Rule Name          Severity Level  Added  Removed  Modified
-----
* User Binaries          46          0         0         1
Tripwire Binaries       100          0         0         0
Critical configuration files  46          0         0         0
Libraries               46          0         0         1
* Operating System Utilities  100          0         0         1
Critical system boot files  100          0         0         0
File System and Disk Administration Programs  100          0         0         0
Kernel Administration Programs  100          0         0         0
Networking Programs     100          0         0         0
System Administration Programs  100          0         0         0
Hardware and Device Control Programs  100          0         0         0
System Information Programs  100          0         0         0
Application Information Programs  100          0         0         0
Shell Related Programs  100          0         0         0
Critical Utility Sym-Links  100          0         0         0
Shell Binaries          100          0         0         0
* Tripwire Data Files     100          1         0         0
System boot changes      100          0         0         0
OS executables and libraries  100          0         0         0
Security Control         100          0         0         0
Login Scripts            100          0         0         0
Root config files        100          0         0         0
Important Directories    46          0         0         0
Temporary directories    31          0         0         0
Critical Devices         100          0         0         0

Total objects scanned: 28891
Total violations found: 3

=====
Object Summary:
=====


# Section: Unix File System

Rule Name: User binaries (/usr/bin)
Severity Level: 46
```

Challenge and Analysis

Part 1: Identifying Additional Event Types in the Event Viewer

Make a screen capture showing the **Security Event Properties** dialog box for an **Audit Failure** associated with **Event ID 5061**.



Provide a brief explanation of the operation that would generate a security event with Event ID 5061.

Event ID 5061 is generated in the Windows Security Log when a cryptographic operation, like opening, creating, or using a key, is performed by a Key Storage Provider. Specifically the Microsoft Software Key Storage Provider. It signified the system level audit logging for cryptographic key access and indicated if a cryptographic key was accessed, used, or failed to open.

Part 2: Configuring Snort as an Intrusion Prevention System

Implementing Security Monitoring and Logging (4e)

Fundamentals of Information Systems Security, Fourth Edition - Lab 08

Make a screen capture showing the **Legacy Blocking Mode** enabled on the LAN interface.

