1. Importing Libraries

```
import pandas as pd
import numpy as np
```

2. Importing dataset

```
df = pd.read_csv("/content/buddymove_holidayiq.csv")
df
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77	79	69	68	95
1	User 2	2	62	76	76	69	68
2	User 3	2	50	97	87	50	75
3	User 4	2	68	77	95	76	61
4	User 5	2	98	54	59	95	86
...	...	...	...	...	...	...	...
244	User 245	18	139	148	129	129	168
245	User 246	22	114	228	104	84	168
246	User 247	20	124	178	104	158	174
247	User 248	20	133	149	139	144	213
248	User 249	20	143	149	139	159	143

249 rows × 7 columns

3. Taking care of missing data

a) isnull()/ notnull()- Both function help in checking whether a value is NaN or not.

```
df.isnull()
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	False	False	False	False	False	False	False
1	False	False	False	False	False	False	False
2	False	False	False	False	False	False	False
3	False	False	False	False	False	False	False
4	False	False	False	False	False	False	False
...	...	...	...	...	...	...	...
244	False	False	False	False	False	False	False

```
1 print(df.isnull().sum())
```

```
User Id      0
Sports       0
Religious    0
Nature       0
Theatre      0
Shopping     0
Picnic       0
dtype: int64
```

As there are no missing values we will change some values to NAN for the purpose of demonstration

```
1 df=df.replace(59,np.NaN)
2 df=df.replace(76,np.NaN)
3 df
4 print(df.isnull().sum())
```

```
User Id      0
Sports       0
Religious    4
Nature       6
Theatre      4
Shopping     5
Picnic       2
dtype: int64
```

```
1 df.isnull()
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	False	False	False	False	False	False	False
1	False	False	False	True	True	False	False
2	False	False	False	False	False	False	False
3	False	False	False	False	False	True	False
4	False	False	False	False	True	False	False
...	...	...	...	...	...	...	...
244	False	False	False	False	False	False	False

```
1 bool_series = pd.notnull(df)
2 bool_series
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	True	True	True	True	True	True	True
1	True	True	True	False	False	True	True
2	True	True	True	True	True	True	True
3	True	True	True	True	True	False	True
4	True	True	True	True	False	True	True
...	...	...	...	...	...	...	...
244	True	True	True	True	True	True	True
245	True	True	True	True	True	True	True
246	True	True	True	True	True	True	True
247	True	True	True	True	True	True	True
248	True	True	True	True	True	True	True

249 rows × 7 columns

Filling missing values using fillna(), replace() and interpolate() In order to fill null values in a datasets, we use fillna(), replace() and interpolate() function these function replace NaN values with some value of their own.

Filling null values with a single value

```
1 df.fillna(0)
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
1	User 2	2	62.0	0.0	0.0	69.0	68.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
3	User 4	2	68.0	77.0	95.0	0.0	61.0
4	User 5	2	98.0	54.0	0.0	95.0	86.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0

Filling null values with the previous ones

```
1 df.fillna(method ='pad')
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
1	User 2	2	62.0	79.0	69.0	69.0	68.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
3	User 4	2	68.0	77.0	95.0	50.0	61.0
4	User 5	2	98.0	54.0	95.0	95.0	86.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0
248	User 249	20	143.0	149.0	139.0	159.0	143.0

249 rows × 7 columns

Filling null value with the next ones

```
1 df.fillna(method ='bfill')
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
1	User 2	2	62.0	97.0	87.0	69.0	68.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
3	User 4	2	68.0	77.0	95.0	95.0	61.0
4	User 5	2	98.0	54.0	93.0	95.0	86.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0

```
df["Theatre"].fillna("Not present", inplace = True)
df
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
1	User 2	2	62.0	NaN	Not present	69.0	68.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
3	User 4	2	68.0	77.0	95.0	NaN	61.0
4	User 5	2	98.0	54.0	Not present	95.0	86.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0
248	User 249	20	143.0	149.0	139.0	159.0	143.0

249 rows × 7 columns

Filling a null values using replace() method

```
df[10:25]
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
10	User 11	3	107.0	54.0	64.0	103.0	94.0
11	User 12	3	103.0	60.0	63.0	102.0	93.0
12	User 13	3	64.0	82.0	82.0	75.0	69.0
13	User 14	3	93.0	54.0	74.0	103.0	69.0
14	User 15	3	63.0	82.0	81.0	78.0	69.0
15	User 16	3	82.0	79.0	75.0	75.0	82.0
16	User 17	5	NaN	131.0	103.0	54.0	86.0
17	User 18	5	56.0	124.0	108.0	56.0	85.0
18	User 19	4	85.0	67.0	111.0	65.0	72.0
19	User 20	5	114.0	83.0	65.0	114.0	102.0
20	User 21	4	93.0	82.0	79.0	79.0	90.0
21	User 22	4	105.0	52.0	75.0	113.0	78.0
22	User 23	5	69.0	118.0	74.0	66.0	101.0

```
1 df.replace(to_replace = np.nan, value = -99)
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
1	User 2	2	62.0	-99.0	Not present	69.0	68.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
3	User 4	2	68.0	77.0	95.0	-99.0	61.0
4	User 5	2	98.0	54.0	Not present	95.0	86.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0
248	User 249	20	143.0	149.0	139.0	159.0	143.0

249 rows × 7 columns

Using interpolate() function to fill the missing values using linear method.

```
1 df.interpolate(method ='linear', limit_direction ='forward')
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
1	User 2	2	62.0	88.0	Not present	69.0	68.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
3	User 4	2	68.0	77.0	95.0	72.5	61.0
4	User 5	2	98.0	54.0	Not present	95.0	86.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0
248	User 249	20	143.0	149.0	139.0	159.0	143.0

Dropping missing values using dropna()

Drop rows with at least one Nan value

```
1  df.dropna()
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
4	User 5	2	98.0	54.0	Not present	95.0	86.0
6	User 7	3	64.0	85.0	82.0	73.0	69.0
8	User 9	3	64.0	108.0	64.0	54.0	93.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0
248	User 249	20	143.0	149.0	139.0	159.0	143.0

233 rows × 7 columns

Dropping rows if all values in that row are missing.

```
df.dropna(how = 'all')
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
1	User 2	2	62.0	NaN	Not present	69.0	68.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
3	User 4	2	68.0	77.0	95.0	NaN	61.0
4	User 5	2	98.0	54.0	Not present	95.0	86.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0
248	User 249	20	143.0	149.0	139.0	159.0	143.0

249 rows × 7 columns

```
new_data = df.dropna(axis = 0, how ='any')
new_data
```

	User Id	Sports	Religious	Nature	Theatre	Shopping	Picnic
0	User 1	2	77.0	79.0	69.0	68.0	95.0
2	User 3	2	50.0	97.0	87.0	50.0	75.0
6	User 7	3	64.0	85.0	82.0	73.0	69.0
8	User 9	3	64.0	108.0	64.0	54.0	93.0
10	User 11	3	107.0	54.0	64.0	103.0	94.0
...	...	...	...	...	...	...	...
244	User 245	18	139.0	148.0	129.0	129.0	168.0
245	User 246	22	114.0	228.0	104.0	84.0	168.0
246	User 247	20	124.0	178.0	104.0	158.0	174.0
247	User 248	20	133.0	149.0	139.0	144.0	213.0
248	User 249	20	143.0	149.0	139.0	159.0	143.0

230 rows × 7 columns

compare sizes of data frames so that we can come to know how many rows had at least 1 Null value

```
print("Old data frame length:", len(df))
print("New data frame length:", len(new_data))
print("Number of rows with at least 1 NA value: ", (len(df)-len(new_data)))
```

```
Old data frame length: 249
New data frame length: 230
Number of rows with at least 1 NA value:  19
```

✓ 0s completed at 10:57 PM