MIT 8103 Advanced Database Systems

Airline Reservation System · Adedoyin Martins · Student ID 301815898

Case study

My case study is Airline Reservation System. I designed the database for passengers searching for flights and managing their reservations and reservation agents reviewing bookings and seat assignments, with separate tables named passenger, flight and reservation. It supports these operations: search scheduled flights by origin and departure time; create and confirm a passenger reservation; report confirmed reservation counts by flight.

Portfolio 1: Database Design and Modelling

I organised the relational design into 3 tables. Primary keys identify records, foreign keys preserve the links, and checks enforce the stated business rules. A partial unique constraint on flight_id and seat_number applies only when status is confirmed and seat_number is not null, preventing two confirmed reservations from occupying the same seat on one flight. The normalisation examples show the sample data at 1NF, 2NF and 3NF. All 28 deliberately invalid inserts were rejected without changing the valid sample rows.




Figure 1. Tables, keys and relationships. PK: primary key; FK: foreign key; UK: unique value.

Portfolio 2: Query Processing and Optimisation

I ran three SQL queries against the sample records. The join returned 1 rows and included Avery Chen with AX204. For the index comparison, I used 20,000 separate performance rows. The median lookup time changed from 1.186 ms to 0.199 ms. Both phases returned the same records. The measured plan used the new index. These timings apply to this lookup and environment.

Portfolio 3: Transactions and Concurrency

I used a temporary counter on reservation to test COMMIT, ROLLBACK and READ COMMITTED isolation. The uncommitted update remained hidden from the other session, and ROLLBACK restored the earlier committed value. Without locking, two increments left the counter at 2. With SELECT FOR UPDATE, Session B waited for Session A and the final value was 3. The helper is confined to this exercise; the case's original business fields stay unchanged.

Portfolio 4: NoSQL and Advanced Data Models

I used reservation_events for the case's event documents. MongoDB inserted 2 sample events and returned the expected results for 4 queries. Validation rejected an invalid date type and a duplicate event ID. Embedded snapshots keep related details with an event, while the details field can differ by event type. These are fictional events; PostgreSQL continues to enforce its relational rules.

Repository and evidence

https://github.com/deeadeniran-hue/Martins_Adedoyin_301815898

The portfolio folders contain the SQL and JavaScript, explanations, query plans, result tables and screenshots.

Portfolio 5: Distributed and Cloud Database Exercise

I proposed three MongoDB replica members across separate failure zones. The discussion covers primary elections, majority acknowledgement, secondary lag and sharding trade-offs for reservation_events. Replication supports availability, while backups address recovery. PostgreSQL needs its own availability plan. This is the permitted discussion option; no live replica set or failover test was deployed.

Individual reflection

I kept passenger, flight, reservation in separate tables so their details could be maintained without repeating them in every related record. A partial unique constraint on flight_id and seat_number applies only when status is confirmed and seat_number is not null, preventing two confirmed reservations from occupying the same seat on one flight. The constraint tests check this alongside the required values and record links. One issue illustrated by the two-session exercise is that both sessions can read the same value before either update is committed. Locking the row before reading preserves both increments. The index comparison also shows why I need to check the execution plan as well as the final answer: the same result can require different amounts of database work.

AI-use declaration

I used GitHub Copilot and the portfolio generator to help prepare the database model, scripts and explanations. The generator ran the PostgreSQL and MongoDB exercises, checked their outputs and captured the result images. I remain responsible for checking and explaining the submitted work.

References

- PostgreSQL: constraints
- PostgreSQL: EXPLAIN
- PostgreSQL: isolation
- PostgreSQL: row locks
- MongoDB: data modelling
- MongoDB: replication
- MongoDB: sharding
- Mermaid: ER diagrams