

Basic Networking commands1. arp -aOutput:

Interface : 172.16.110.112 - - 0x5

Internal Address	Physical Address	Type
172.16.8.1	7c-6a-1c-cf-be-45	dynamic
172.16.8.3	d4-3d-7e-c7-b5-3c	dynamic
172.16.8.4	d4-3d-7e-ad-3c-bf	dynamic

2. hostname:Output:

DESKTOP - 20V704J

3. Ipconfig/all:Output:

Windows IP configuration

Hostname : DESKTOP - 20V704J

Primary Dns Suffix :

Node Type : Hybrid

IP Routing Enabled : No

WINS Proxy Enabled : No

Ethernet adapter Ethernet 2:

Connection-Specific DNS suffix:

Description: Intel(R) Ethernet

Physical Address: D8-BB-C1-C5-CE-58

DHCP Enabled: No

4. nbstat -a:

Output:

NBSTAT [-a Remote Name] [-A IP address] [-C] [-n]
[-r] [-R] [-RR] [-S] [-s] [interval]

- a (adapter status)
- A (Adaptor status)
- C (cache)
- n (names)
- r (resolved)
- R (Reload)
- S (sessions)
- s (Sessions)
- RR (Release Refresh)

5. netstat:

Output:

Active connections

proto	Local address	Foreign Address	Status
TCP	172.16.10.112:1680	172.16.10.102: 53574	Established
TCP	172.16.10.112: 51297	4-213-25240: https	Established
TCP	172.16.10.112: 51908	172.16.8.127: ssh	Time-wait
TCP	172.16.10.112: 51946	Lebomp-in-glee: 5228	Established

6. nslookup:

Output:

Default Server: Unknown

Address: 172.16.8.1

7. pathping:

Output:

usage: pathping [-g host-list] [-h maximum_hops] [-i
address] [-p period] [-q num-queries] [-w
timeout] [-t] [target_name]

8. ping hostname:

Output:

PING Localhost Localdomain (Localhost (127.0.0.1)) 56 data bytes

64 bytes from Localhost (127.0.0.1): icmp_seq=1 ttl=64

64 bytes from localhost [::1]: icmp_seq=2 ttl=64

64 bytes from localhost [::1]: icmp_seq=3 ttl=64

64 bytes from localhost [::1]: icmp_seq=4 ttl=64

9 route:

Output:

Route [-f] [-P] [-4] [-6] command [destination]
[MASK netmask] [gateway] [METRIC metric]

Command

One of these:

PRINT Prints a route

ADD Adds a route

DELETE Deletes a routes

CHANGE Modifies existing route

Linux Networking Commands:

1. ip:

Output:

[::] To: <LOOKBACK / LOWER-UP> mtu 65536 qdisc
non queue state UNKNOWN group default qlen 1000

link / loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00

pnet 127.0.0.1/8 Scope host co

Valid - EPT forever postponed - EPT forever
inet :: 1/28 scope host

2. ifconfig:

output:

enp3s0: flags = 4163<UP, BROADCAST, RUNNING,
MULTICAST>

inet 172.16.8.127 netmask 255.255.252.0

broadcast 172.16.11.255

inet6 fe80::a6fb:cdb4:131c:6e50

ether 00:27:0e:13:96:d9

3. mtr:

output:

My traceroute [v0.87]

Localhost - Local domain [0.0.0.0] Thu Jul 23 09:26:58

2026

Keys: Help Display mode Restart Statistics order of
fields.

local host	loss %	int	last	avg	best	worst	down
	0.0%	122	0.1	0.2	0.1	1.9	0.2

4) tempdump :

Output :

tempdump : you don't have performance to capture on that devices

Result :

Thus the basic networking and linux commands are studied and learned successfully.