

A Tase Of ATS

Aditya Siram

June 24, 2019

Outline

- An ML with ADTs, pattern matching, tail calls
- Can be exactly as good the C equivalent
 - Control over memory
 - Performance
- And type safe.

- Compiles to *predictable* C
 - Recursion is well supported
- Compiles to *predictable* C
 - Allows C idioms
 - malloc/free, pointers, stack control
- No compiler optimizations except TCO
 - Almost no ...
- Linear/refinement types, proof level language

- Extremely difficult
 - Syntax
 - Errors
- But I want to get into the more interesting features

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
    val b = fopen("test.txt","r")  
    var f = lam@(s:string):void => println! s  
  in (  
    fwithline(a,f);  
    fclose(a);  
    fclose(b)  
  )  
end
```

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
  
  in (  
  
  )  
end
```

```
datatype FileHandle = FileHandle of ()
```



```
fun fopen(path:string,mode:string): FileHandle =  
  let  
    extern castfn toFileHandle(p:ptr0):<> FileHandle  
  in  
    toFileHandle($extfcall(ptr0,"fopen",path,mode))  
end
```

```
fun fopen(path:string,mode:string): FileHandle =  
  let  
  
  in  
      ($extfcall(ptr0,"fopen",path,mode))  
  end
```

```
fun fopen(path:string,mode:string): FileHandle =  
  let  
      toFileHandle(p:ptr0):<> FileHandle  
  in  
      toFileHandle($extfcall(ptr0,"fopen",path,mode))  
end
```

```
fun fopen(path:string,mode:string): FileHandle =  
  let  
    extern castfn toFileHandle(p:ptr0):<> FileHandle  
  in  
    toFileHandle($extfcall(ptr0,"fopen",path,mode))  
end
```

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
  
  in (  
  
  )  
end
```

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
    val b = fopen("test.txt","r")  
  
  in (  
  
  )  
end
```

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
    val b = fopen("test.txt","r")  
    var f = lam@(s:string):void => println! s  
  in (      |  
          +----- stack allocated closure!  
  
    )  
end
```

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
    val b = fopen("test.txt","r")  
    var f = lam@(s:string):void => println! s  
  in (  
    fwithline(a,f);  
  
  )  
end
```



```
fun fwithline(  
  fh: !FileHandle,  
  f: &(string) -> void  
) : void =  
  let
```

```
  in
```

```
end
```

```

fun fwithline(
  fh: !FileHandle,
  f: &(string) -> void
):void =
  let

```

```

    val _ = $extfcall(int,"getline",
in
    ,
    ,
    )

end

```

```

fun fwithline(
  fh: !FileHandle,
  f: &(string) -<clo1> void
):void =
let
  var len = i2sz(0)
  val lenP = addr@len

  val _ = $extfcall(int,"getline",
                    ,lenP,
                    )
in

end

```

```

fun fwithline(
  fh: !FileHandle,
  f: &(string) -<clo1> void
):void =
let
  var len = i2sz(0)
  val lenP = addr@len
  var buffer = the_null_ptr
  val bufferP = addr@buffer

  val _ = $extfcall(int,"getline",bufferP,lenP,
in

end

```

```

fun fwithline(
  fh: !FileHandle,
  f: &(string) -<clo1> void
):void =
let
  var len = i2sz(0)
  val lenP = addr@len
  var buffer = the_null_ptr
  val bufferP = addr@buffer
                toPtr{1:addr}(f: !FileHandle):<> ptr0
  val _ = $extfcall(int,"getline",bufferP,lenP,toPtr(fh))
in

end

```

```

fun fwithline(
  fh: !FileHandle,
  f: &(string) -<clo1> void
):void =
let
  var len = i2sz(0)
  val lenP = addr@len
  var buffer = the_null_ptr
  val bufferP = addr@buffer
  extern castfn toPtr{1:addr}(f: !FileHandle):<> ptr0
  val _ = $extfcall(int,"getline",bufferP,lenP,toPtr(fh))
in

end

```

```

fun fwithline(
  fh: !FileHandle,
  f: &(string) -<clo1> void
):void =
  let

    var buffer = the_null_ptr

  in
    f (
      (buffer))
  end

```

```
fun fwithline(  
  fh: !FileHandle,  
  f: &(string) -> void  
) : void =  
  let  
  
    var buffer = the_null_ptr  
  
  in  
    f ($UN.castvwtp0{string}(buffer))  
end
```



```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
    val b = fopen("test.txt","r")  
    var f = lam@(s:string):void => println! s  
  in (  
    fwithline(a,f);  
  
  )  
end
```

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
    val b = fopen("test.txt","r")  
    var f = lam@(s:string):void => println! s  
  in (  
    fwithline(a,f);  
    fclose(a);  
  
  )  
end
```

```
fun fclose(f:FileHandle):void =  
  let  
    extern castfn fromFH(f:FileHandle):<> ptr0  
  in  
    $extfcall(void,"fclose",fromFH(f))  
  end
```

```
implement main0(argc,argv) =  
  let  
    val a = fopen("test.txt","r")  
    val b = fopen("test.txt","r")  
    var f = lam@(s:string):void => println! s  
  in (  
    fwithline(a,f);  
    fclose(a);  
    fclose(b)  
  )  
end
```

```
fun fwithline(  
    fh: !FileHandle,  
  
    ):void =  
  
fun fclose(f: FileHandle):void =
```