


CprE 530

Lecture 20


Topics

- WWW
- HTTP: Hyper Text Transfer Protocol
 - Requests
 - Responses
 - Headers


World Wide Web



World Wide Web



Web Client/Server



HTTP

- Hypertext Transfer Protocol
- Simple command/response protocol
- ASCII based commands
- Typically a new connection for each command/response exchange
- Server runs on port 80 default

HTTP Request & Response

Request Line
Headers
Blank Line
Optional Request Body

Command Message

Status Line
Headers
Blank Line
Optional Response Body

Response Message

HTTP Requests

- Three parts:
 - Request line
 - Headers
 - Blank line
 - Body (optional)
- Request line looks like this:
Request type <sp> URL <sp> HTTP version
Example: GET <http://www.ibm.com> HTTP/1.1

More on request types later

URL

- Uniform Resource Locator
- A URL follows this format:
method://host:port/path
- The host can be a machine name or IP address
- The port must be specified if the server is running on a port other than 80.
- The path is the directory where data is stored

Request Types

- GET
 - HEAD
 - POST
 - PUT
 - PATCH
 - COPY
 - MOVE
 - DELETE
 - LINK
 - UNLINK
 - OPTION
- Many of these types can pose security problems, since they involve modifying or deleting data.
- Most servers only implement the first three types: GET, HEAD, POST

Request Types

Type	Action
GET	Retrieve a document specified by the URL.
HEAD	Retrieve the headers from the document specified by the URL. (Response does not contain the body.)
POST	Provide data to the server.
PUT	Provide new or replacement document specified by the URL. (Disabled)
PATCH	Provide differences to document specified by the URL in order to change the document. (Disabled)
COPY	Copy the document specified by the URL to the file specified in the header. (Disabled)
MOVE	Move the document specified by the URL to the file specified in the header. (Disabled)
DELETE	Delete the document specified by the URL. (Disabled)
LINK	Create a link to the document specified in the URL. The name of the link is specified in the header. (Disabled)
UNLINK	Remove the link specified in the URL. (Disabled)
OPTION	Ask the server what options are available.

Response Message

- Four parts:
 - Status line
 - Headers
 - Blank line
 - Body
- The status line looks like this:
HTTP version <sp> status code <sp> status phrase
Examples: HTTP/1.1 404 File not found
HTTP/1.1 200 OK


Response Status Codes

- Status codes follow a similar format to FTP and SMTP status codes
- 3 digit ASCII
 - 1xx informational
 - 2xx success
 - 3xx redirection
 - 4xx client error
 - 5xx server error

Example Response Codes

Code	Phrase	Meaning
100	Continue	First part of the request has been received. The client can continue.
200	OK	Successful request
204	No Content	The body contains no content
302	Moved permanently	The document specified by the URL is no longer on the server.
304	Moved temporarily	The document specified by the URL has temporarily moved.
400	Bad request	The request contained a syntax error.
401	Unauthorized	The authentication failed for the requested document.
403	Forbidden	The service requested is not allowed.
404	Not found	The document requested is not found.
405	Method not allowed	The method requested in the URL is not allowed.
500	Internal server error	The server failed.
501	Not implemented	The requested action can not be preformed by the server.
503	Service unavailable	The request cannot be accomplished right now, try again later.

HTTP Headers



Command/Response Message

Header Format

HTTP Headers

- Headers have three parts:
 - General header
 - Request or response header, depending on whether the header precedes a request or a response
 - Entity header
- The general header contains the following fields:

Header	Function
Cache-control	Used to specify information about the client side cache.
Connection	Indicates whether the connection should be closed.
Date	Provides the current date.
MIME-version	Indicated the MIME version being used.
Connection	Use to determine connection type.
Keep-Alive	Used to manage keep-alive connection.

HTTP Headers

- The Request header may contain the following fields (all are optional):

Header	Function
Accept	Indicates which data formats the browser can accept.
Accept-charset	Indicates the character set(s) the browser can accept.
Accept-encoding	Indicates what encoding methods the browser can process.
Accept-language	Indicates what language the browser can accept.
From	Provides the e-mail of the user on the browser.
Host	Provides the host and ephemeral port of the browser.
Referrer	Provides the URL of the linked document.
User-agent	Provides information about the browser software.

HTTP Headers

- The response header may contain the following fields

Header	Function
Accept-range	Indicates the server accepts the range requested by the browser.
Retry-after	Indicates the date when the server will be available.
Server	Provides the server application name and version.

HTTP Headers


- The entity header may contain the following fields:

Header	Function
Allow	Provides a list of methods allowed for the URL.
Content-encoding	Indicates the encoding method for the document.
Content-language	Indicates the language of the document.
Content-length	Indicates the length of the document.
Content-location	Real name of the document requested.
Content-type	Indicates the media type of the document.
Etag	Provides a tag for the document.
Last-modified	The date the document was last modified.

HTTP Summary

- Request:
 - Request line
 - General Header
 - Request Header
 - Entity header
 - Blank line
 - Optional Body
- Response:
 - Status line
 - General header
 - Request header
 - Entity header
 - Blank line
 - Body
- Note: the entity header does not always appear in the request

HTTP Protocol Exchange



HTTP Request

Request Line

GET / HTTP/1.1

General Header

Keep-Alive: 300
Connection: keep-alive

Request Header

Host: spock.ee.iastate.edu
User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.8.0.7)
Gecko/20060909 Firefox/1.5.0.7
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,image/png,*/*;q=0.5
Accept-Language: en-us,en;q=0.5
Accept-Encoding: gzip,deflate
Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.7

No Entity Header

Blank Line

No Body

HTTP Response

Status Line

HTTP/1.1 200 OK

General Header

Date: Sat, 28 Oct 2006 16:01:55 GMT
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive

Response Header

Server: Apache/1.3.33 (Unix)
Accept-Ranges: bytes

Entity Header

Content-Location: index.html.en
Last-Modified: Fri, 04 May 2001 00:00:38 GMT
ETag: "428fd8-5b0-3af1f126;452e43f5"
Content-Length: 1456
Content-Type: text/html
Content-Language: en

Blank Line

HTML document (1456 bytes long)

HTTP Request

Request Line

GET /apache_pb.gif HTTP/1.1

General Header

Keep-Alive: 300
Connection: keep-alive

Request Header

Host: spock.ee.iastate.edu
User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.8.0.7)
Gecko/20060909 Firefox/1.5.0.7
Accept: image/png,*/*;q=0.5
Accept-Language: en-us,en;q=0.5
Accept-Encoding: gzip,deflate
Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.7
Referer: http://spock.ee.iastate.edu/

No Entity Header

Blank Line

No Body

HTTP Response

Status Line

HTTP/1.1 200 OK

General Header

Date: Sat, 28 Oct 2006 16:01:55 GMT
Keep-Alive: timeout=15, max=99
Connection: Keep-Alive

Response Header

Server: Apache/1.3.33 (Unix)
Accept-Ranges: bytes

Entity Header

Last-Modified: Wed, 03 Jul 1996 06:18:15 GMT
ETag: "428fd1-916-31da10a7"
Content-Length: 2326
Content-Type: image/gif

Blank Line

GIF image (2326 bytes long)

HTTP Request

Request Line

GET /favicon.ico HTTP/1.1

General Header

Keep-Alive: 300
Connection: keep-alive

Request Header

Host: spock.ee.iastate.edu
User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.8.0.7)
Gecko/20060909 Firefox/1.5.0.7
Accept: image/png,*/*;q=0.5
Accept-Language: en-us,en;q=0.5
Accept-Encoding: gzip,deflate
Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.7

No Entity Header

Blank Line

No Body

HTTP Response

Status Line

HTTP/1.1 404 Not Found

General Header

Date: Sat, 28 Oct 2006 16:01:55 GMT
Keep-Alive: timeout=15, max=97
Connection: Keep-Alive

Response Header

Server: Apache/1.3.33 (Unix)

Entity Header

Content-Type: text/html; charset=iso-8859-1

Blank Line

HTML Document

Header Based

- Buffer overflow problems
- Server can pass HTTP requests to back-end servers and applications so header problems are not just with the WEB server
- Some header-based attacks facilitate authentication-based attacks
- Accessing hidden pages

Protocol Based

- Not many protocol based attacks since it is a command/response protocol

Authentication Based

- This is the most common method of attack in the WEB.
- The web server uses HTTP to request user credentials.
- Authentication can also be directly with the server side application (to be discussed later)
- Authentication is used to access pages within a directory on the server


WEB Authentication

- Server challenge:
 - WWW-Authenticate: Basic realm="Text String"
- Client Challenge:
 - user-ID and password, separated by a single colon (":") character, within a base64 encoded string.

For example:

- Authorization: Basic
QWxhZGRpbjpvcGVuIHNlc2FtZQ==

HTTP Authentication



HTTP Authentication

Request Header

```
GET /~dougj/private/doc.html HTTP/1.1  
Host: spock.ee.iastate.edu
```

Response Header

```
HTTP/1.1 401 Authorization Required  
Date: Tue, 14 Nov 2006 22:37:47 GMT  
Server: Apache/1.3.33 (Unix)  
WWW-Authenticate: Basic realm="Enter Password"
```

Request Header

```
GET /~dougj/private/doc.html HTTP/1.1  
Host: spock.ee.iastate.edu  
Authorization: Basic bG9yaWVuOmZpcnN0b25l
```

Web Authentication

- Can be sniffed (traffic based attack)
- Can be guessed
- Countermeasures:
 - Encrypted sessions
 - Good passwords


Traffic Based

- Very common attacks
 - Flooding
 - Web Hugging
- HTTP is clear text.
 - HTTP does not support encrypted sessions.
 - Encrypted sessions are supported using transport layer encryption


HTTPS

- Uses the Secure Socket Layer SSL
- Port 443
- Uses public key certificates

HTTPS



HTTPS Certificates



Certificate chain of trust

