

PROFESSIONAL DMR PORTABLE RADIO

HP788

EMPOWER YOUR OPERATION



NEW TECHNOLOGY, NEW EXPERIENCE, NEW FUTURE

As the leading supplier, Hytera has huge experience in R&D and manufacturing of professional digital radios, and received a large number of suggestions and ideas from users of all industries. Having analyzed and extracted users' need, we perceive that it is not enough to improve the status: the radio needs to be more future ready.

Taking inspiration from the feedback received from our users, we are continuously envisioning and exploring better communication within an eco-system of new standards, new technologies, new products and new applications across the innovation chain. The HP788 is our brand new professional digital radio, and represents the future on style and functions that refreshes the standards in digital radios, providing more efficient and more reliable communication with loud and clear audio, powerful battery, remarkable portability and ruggedness for ease of use across multiple environments and industries.



HIGHLIGHTS



THINNER AND LIGHTER

An optimized mechanical design and a compact lithium polymer battery are discreetly made to fit into the HP788's design, making the radio only 29.5mm in thicknesses and 310g in weight. This easy to carry and minimalist design benefits officers by allowing them to keep their focus on the critical mission at hand.



LONGER BATTERY LIFE

HP788 optimizes product design and technologies to reduce power consumption, meanwhile the latest in proven lithium polymer technology is used in the standard battery which is lighter and smaller than ever before.

The new technologies bring a duty cycle of 5/5/90 on achieving a shift life of 24 hours on high transmit power and ensure a full day of delivering key information and calls.



LOUDER AND CLEARER AUDIO

HP788 equips an optimized powerful loudspeaker that can help users to hear clear sounds even in a noisy environment. Water-porting technology is also used to drain out any water that gets into the speaker cavity, ensuring the audio clarity is maintained in case of water.

AI-based noise cancellation technology can decrease 30dB background noise and howling. No matter what noise environment the calling party is in, it ensures that the called party hears a clear sound.



MORE INTUITIVE AND EFFICIENT

HP788 brings a large screen and a brand new intuitive UI to make the operation more efficient. The 2.4-inch colour screen can display more information (i.e. 6 contacts) per page. Its Quick Access Menu allows users to set the radio faster. Messages are listed in conversation for quick reading and review. The Interface Switcher is added to the option of programmable buttons, allowing quick switch between up to four frequently accessed interfaces.



ENHANCED COVERAGE

The HP788 extends the operational range and improves the talk range through high receiver sensitivity and high transmit power, stretching communications into areas where it simply was not possible before. This enhanced coverage improves the user safety and reduces network cost as much as possible.



HIGHER LEVEL OF RUGGEDNESS

HP788 is designed as per the MIL-STD-810H. It is IP68 rated, impervious to water jets and submersible to a depth of 2 meters for 4 hours, and also resilient to 2-meter drops onto concrete. No matter where the mission drives the officer, the HP788 is the partner to count on, because it can stand up to the toughest environment.



FLEXIBLE WIRELESS CONNECTION

HP788 supports the built-in BT 5.0 for wireless connections. The advantages of BT 5.0 are low power consumption, rapid transmission, multiple devices and more rich data applications such as BT earpiece, BT Patrol, BT positioning.

Volume/Channel/Contact Knob

Dedicated Emergency Button



Programmable Buttons




Wear-resistant keys

Loud and clear speaker



Water-porting for draining out the water in the speaker cavity

Sensitive Antenna




2.4-inch color display



Belt clip



Superior li-polymer battery



Micro SD card slot for
• Hardware encryption
• Audio recording



2.4-inch color display



Loud and clear audio



Superior long battery life



AI based noise cancellation



Water-porting design



Global Positioning



BT 5.0 audio and data



Micro SD Card

FEATURES

Supplementary

- Profiles
- QR Code
- Roaming
- Covert Mode
- Radio Check
- Remote Monitor
- Alert Call

Operating Modes

- Analog conventional
- Digital conventional
- Digital trunking

Data Services

- Text Message
- Status Message
- Quick Text Message

Voice Service

- Private Call
- Group Call
- All Call
- PSTN/PABX Call
- Broadcast Call
- Emergency Call
- Call Priority

Connection

- BT Audio
- BT Data
- High Efficiency GNSS
 - GPS
 - GLONASS
- Wide Range of Accessories
- Open API

Safety

- Emergency
- Man Down
- Lone Worker
- Authentication
- Air Interface Encryption
- End-to-End Encryption
- Scrambler
- Disable/Enable
- Micro SD Card(max. 16G)
- Audio recording

Analog Mode


- 2-Tone signaling
- 5-Tone Signalling
- HDC1200

APPLICATIONS



 Transportation



 Manufacturing



 Business



 Public Safety



 Security



 Utility

SPECIFICATIONS


General		
Frequency Range	UHFv : 350-470MHz VHF : 136-174MHz UHF5 : 806-825MHz(only transmit), 851-870MHz(transmit & receive), 896-902MHz(only transmit), 935-941(transmit & receive)	
Channel Capacity	1024	
Zone Capacity	64	
Zone Channel	256	
Channel Spacing	12.5kHz/20kHz/25kHz	
Operating Voltage	7.7V (rated)	
Battery	2400 mAh Li-polymer Smart Battery: 3000 mAh Li-polymer(optional)	
Battery Life (5/5/90 Duty Cycle,High TX Power)	2400 mAh: 24h (GNSS OFF) 20h (GNSS ON)	3000 mAh: 30h (GNSS OFF) 25h (GNSS ON)
Frequency Stability	±0.5ppm	
Antenna Impedance	50Ω	
Dimensions (H x W x D)	2400 mAh: 132 x 55 x 29.5mm 3000 mAh: 132 x 55 x 37.5mm	
Weight(with antenna&battery)	2400mAh: 310g 3000mAh: 345g	
Display	LCD, 320×240 pixel, 262000 colors, 2.4 inch	
BT	BT 5.0 BLE+EDR	
Receiver		
Sensitivity	Analog: 0.18μV (12dB SINAD); 0.16μV (Typical) (12dB SINAD) Digital: 0.18μV/BER5%	
Adjacent Channel Selectivity	TIA-603: 60dB@12.5kHz / 70dB@20/25kHz ETSI: 60dB@12.5kHz / 70dB@20/25kHz	
Intermodulation	TIA-603: 70dB@12.5/20/25kHz ETSI: 65dB@12.5/20/25kHz	
Spurious Response Rejection	TIA-603: 70dB@12.5/20/25kHz ETSI: 70dB@12.5/20/25kHz	
Blocking	TIA-603: 80dB ETSI: 84dB	
Hum and Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz	
Rated Audio Power Output	0.5W	
Rated Audio Distortion	≤3%	
Audio Response	+1 ~ -3dB	
Conducted Spurious Emission	<-57dBm	

Transmitter	
RF Power Output	UHFv : 1/4W VHF : 1/5W UHF5 : 1/3W (806-870MHz) , 1/2.5W (896-941MHz)
FM Modulation	11K0F3E@12.5kHz 14K0F3E@20kHz 16K0F3E@25kHz
4FSK Digital Modulation	12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz; -30dBm >1GHz
Modulation Limiting	± 2.5kHz@12.5kHz; ± 4.0kHz@20kHz; ± 5.0kHz@25kHz
FM Hum&Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz
Adjacent Channel Power	60dB@12.5kHz; 70dB@20/25kHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE+2™/SELP
Digital Protocol	ETSI-TS102 361-1,-2,-3
Environmental	
Operating Temperature	-30°C+~+60°C
Storage Temperature	-40°C~+85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air)
Dust and Water Protection	IEC60529 IP66 IP68
Humidity	Per MIL-STD-810H Standard
Shock and Vibration	Per MIL-STD-810H Standard
Location Services	
Accuracy specs are for long-term tracking(5 satellites visible at nominal -130dBm)	
GNSS	GPS, GLONASS, GPS+GLONASS
TTFF(Time To First Fix) Cold Start	<1 min (Typical)
TTFF (Time To First Fix) Hot Start	<10 sec (Typical)
Horizontal Accuracy	<5m (probable at -130dBm)
*Radio only - Battery -20°C	

Hytera Partner:
VKT Services Private Limited
Syed Jalal Garden, West maredpally ,
Telangana, India - 500026
Ph.No: +91-40-040078310, +91-9989106669

ACCESSORIES

Standard



Charger



Adapter(12V/1A)



Li-polymer battery
2400mAh



Antenna



Belt clip



Strap

Optional



BT Wireless earpiece



Programming cable
(USB port)



BT wireless ring PTT



BT Wireless remote
speaker microphone



Wired earpiece



Multi-unit charger



Li-polymer battery
3000mAh



Respond & Achieve

Hytera Communications Corporation Limited

Address : A-05-02, Block A, Tamarind Square, Persiaran Multimedia, Cyber 11, 63000 Cyberjaya, Selangor, Malaysia.

Tel : +91 040 40078310



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd.

© 2022 Hytera Communications Corp., Ltd. All Rights Reserved.