

CHAMFERING MACHINE



RT-60 & 120 AC

RT-60AC/RT-120AC SINGLE HEAD PIPE CHAMFERING MACHINES (PNEUMATIC & HYDRAULIC MODELS)

PARAMETER TABLE		
MODEL	RT-60 AC	RT-120 AC
APPLICABLE DIAMETER	Φ6-Φ60MM,Φ6-Φ20MM	Φ20-Φ120MM
PROCESSING LENGTH	Φ25MM	Φ40MM
MAIN MOTOR POWER	1.1KW*380V*50HZ	3KW*380V*50HZ
OIL PUMP MOTOR POWER	—	0.75KW/380V/50HZ
WORKING PRESSURE	—	≤30KG
PROCESSING ACCURACY	±0.1MM	±0.1MM
PROCESSING SPEED	3-6S/P	6-8S/P
APPLICABLE MATERIALS	PVC	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR
MACHINE NET WEIGHT	200KG	—
MACHINE DIMENSIONS	600X770X920MM	1100X1400X1400MM



RT-80, 120 & 150/180 AC-Q

RT-80 AC-Q, RT-120 AC-Q, AND RT-150/180 AC-Q PNEUMATIC SINGLE HEAD PIPE CHAMFERING MACHINES

PARAMETER TABLE				
MODEL	RT-80 AC-Q	RT-120A C-Q	RT-150 AC-Q	RT-180 AC-Q
PROCESSING LENGTH	≥35MM	≥40MM	≥50MM	≥50MM
APPLICABLE DIAMETER	Φ6-Φ80MM,Φ8-Φ30MM	Φ30-Φ120MM	Φ20-Φ150MM	Φ20-Φ180MM
WORKING PRESSURE	≤10KG	≤10KG	≤10KG	≤10KG
MAIN MOTOR POWER	1.5KW*380V*50HZ	2.2KW*380V*50HZ	3.0KW	4.0KW
PROCESSING ACCURACY	±0.1MM	±0.1MM	±0.1MM	±0.1MM
PROCESSING SPEED	3-6S/P	6-8S/P	6-8S/P	6-8S/P
APPLICABLE MATERIALS	PVC	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR		
MACHINE NET WEIGHT	220KG	310KG	—	—
MACHINE DIMENSIONS	700X770X1000MM	1250X1250X1350MM	1000X1400X1400MM	1100X1400X1400MM

RT-80, 150/180 & 230 AC-Y

RT-80AC-Y, RT-150/180AC-Y & RT-230AC-Y HYDRAULIC SINGLE HEAD PIPE CHAMFERING MACHINES

PARAMETER TABLE				
MODEL	RT-80 AC-Y	RT-150 AC-Y	RT-180 AC-Y	RT-230 AC-Y
PROCESSING LENGTH	≥35MM	≥50MM	≥50MM	≥70MM
APPLICABLE DIAMETER	Φ6-Φ80MM,Φ2-Φ25MM	Φ20-Φ150MM	Φ20-Φ180MM	Φ30-Φ2300MM
MAIN MOTOR POWER	2.2KW*380V*50HZ	3.0KW	3.0KW	5.5KW
WORKING PRESSURE	≤10KG	≤10KG	≤10KG	≤30KG
OIL PUMP MOTOR POWER	0.75KW/380V/50HZ	—	—	—
OIL RESEARCH VALVE SPECIFICATIONS	DS6-01-2B2-A110-N1	—	—	—
PROCESSING ACCURACY	±0.1MM	±0.1MM	±0.1MM	±0.1MM
PROCESSING SPEED	6-8S/P	6-8S/P	6-8S/P	8-15S/P
APPLICABLE MATERIALS	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR			
MACHINE DIMENSIONS	1100X1400X1400MM	1000X1400X1400MM	1200×1400×1600MM	



RT-60 & 90 CNC-D

DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR SHORT MATERIAL, 2-AXIS, SINGLE MANIPULATOR, STANDARD TYPE



PARAMETER TABLE

MODEL	RT-60 CNC-D	RT-90 CNC-D
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM
APPLICABLE LENGTH	15-200MM/150-300MM	15-200MM/150-300MM
APPLICABLE WALL THICKNESS	≤5MM	≤5MM
WORKING PRESSURE	≤10KG	
WORKING SPEED	≈5S	≈5S
SERVO MOTOR	750W	1000W
MAIN MOTOR	1.5KW/2.2KW	2.2KW/3.0KW
LENGTH ACCURACY	±0.025MM	±0.025MM
VERTICALITY	≤0.05	≤0.05
DIMENSIONS	1804X1020X1870MM	1804X1020X1870MM
WEIGHT	1000KG	1100KG

RT-60, 90 & 120 CNC-D

DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR SHORT MATERIAL, 2-AXIS, SINGLE MANIPULATOR (PRECISION/HEAVY TYPE)

PARAMETER TABLE

MODEL	RT-60 CNC-D	RT-90 CNC-D	RT-120 CNC-D
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM	Φ20-Φ120MM
APPLICABLE LENGTH	15-200MM	15-200MM	15-200MM
APPLICABLE WALL THICKNESS	≤5MM	≤5MM	≤5MM
WORKING PRESSURE	≤10KG	—	—
WORKING SPEED	≈4-5S	≈6-8S	≈6-8S
SERVO MOTOR	750W	1000W	1500W
MAIN MOTOR	1.5KW/2.2KW	3.0KW	4.0KW
LENGTH ACCURACY	±0.02MM	±0.03MM	±0.03MM
VERTICALITY	≤0.05	≤0.05	≤0.05
DIMENSIONS	1900X1200X1640MM		
WEIGHT	1100KG	1200KG	1400KG



RT-60 & 90 CNC-DS

DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR SHORT MATERIAL 3-AXIS DOUBLE MANIPULATOR WITH SCRAP SEPARATION

PARAMETER TABLE

MODEL	RT-60 CNC-DS	RT-90 CNC-DS
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM
APPLICABLE LENGTH	15-200MM	15-200MM
APPLICABLE WALL THICKNESS	≤3MM	≤3MM
WORKING PRESSURE		
WORKING SPEED	≈4-5S	≈5S
SERVO MOTOR	750W	1000W
MAIN MOTOR	1.5KW/2.2KW	2.2KW/3.0KW
LENGTH ACCURACY	±0.025MM	±0.025MM
VERTICALITY	≤0.05	≤0.05
DIMENSIONS	1804X1020X1870MM	1804X1020X1870MM
WEIGHT	1000KG	1100KG



RT-60, 90 & 120 CNC-DS

DOUBLE-HEAD PIPE CHAMFERING MACHINE, SHORT MATERIAL SERIES, 3-AXIS DUAL MANIPULATOR WITH SCRAP SEPARATION

PARAMETER TABLE			
MODEL	RT-60 CNC-DS	RT-90 CNC-DS	RT-120 CNC-DS
APPLICABLE DIAMETER	Φ10-Φ60MM	Φ20-Φ90MM	Φ20-Φ120MM
APPLICABLE LENGTH	15-200MM	15-200MM	15-200MM
APPLICABLE WALL THICKNESS	≤5MM	≤5MM	≤5MM
WORKING PRESSURE			
WORKING SPEED	≈4-5S	≈5-6S	≈6-8S
SERVO MOTOR	750W	1.0KW	1.5KW
MAIN MOTOR	2.2KW	3.0KW	4.0KW
LENGTH ACCURACY	±0.02MM	±0.02MM	±0.025MM
VERTICALITY	≤0.05	≤0.05	≤0.05
DIMENSIONS	1900X1200X1640MM		
WEIGHT	1100KG	1200KG	1400KG



RT-30 FA

DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR SMALL WORKPIECES

PARAMETER TABLE	
MODEL	RT-30 FA
MAIN MOTOR POWER	0.75KW/1.1KW
WORKING PRESSURE	≤10KG
APPLICABLE OUTER DIAMETER	Φ6-Φ30MM, Φ3-Φ15MM
PROCESSING LENGTH	10-300MM
PROCESSING ACCURACY	±0.1MM
PROCESSING SPEED	3-5S/P
APPLICABLE MATERIALS	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR
MACHINE DIMENSIONS	1100X1000X1400MM

RT-80, 100 & 120 FA

HEAVY HYDRAULIC MACHINE FOR THICK-WALL PIPES AND IRON BLOCKS

PARAMETER TABLE			
MODEL	RT-80 FA	RT-100 FA	RT-120 FA
MAIN MOTOR POWER	Φ20-Φ80MM	Φ20-Φ100MM	Φ8-Φ120MM
WORKING PRESSURE	15-200MM	15-200MM	15-200MM
APPLICABLE OUTER DIAMETER	3KW	4KW	5.5KW
PROCESSING LENGTH	2.2KW	2.2KW	2.2KW
PROCESSING ACCURACY	<10KG	<20KG	<20KG
PROCESSING SPEED	5-8S	8-12S	10-15S
APPLICABLE MATERIALS	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR		
MACHINE DIMENSIONS	1400X1250X1550MM		



RT-60 & 90 CNC

DOUBLE-HEAD PIPE CHAMFERING MACHINE 5-AXIS DOUBLE MANIPULATOR WITH SCRAP SEPARATION



PARAMETER TABLE		
MODEL	RT-60 CNC	RT-90 CNC
APPLICABLE DIAMETER	Φ15-Φ60MM	Φ20-Φ90MM
APPLICABLE LENGTH	80-500MM/1000MM	80-500MM/1000MM
APPLICABLE WALL THICKNESS	≤5MM	≤5MM
WORKING PRESSURE		
WORKING SPEED	≈6S	≈6S
SERVO MOTOR	750W	1000W
MAIN MOTOR	2.2KW	3.0KW
LENGTH ACCURACY	±0.025MM	±0.025MM
VERTICALITY	≤0.05	≤0.05
DIMENSIONS	1910X1355X1920MM	1910X1355X1920MM
WEIGHT	1200KG	1400KG

RT-60 & 90 CNC-C

3-AXIS SERVO DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR LONG-LENGTH MATERIAL

PARAMETER TABLE		
MODEL	RT-60 CNC-C	RT-90 CNC-C
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM
APPLICABLE LENGTH	200-700MM/1000MM/1500MM	
APPLICABLE WALL THICKNESS	≤5MM	≤5MM
WORKING PRESSURE	—	—
WORKING SPEED	≈5S	≈5S
SERVO MOTOR	750W	1000W
MAIN MOTOR	1.5KW/2.2KW	2.2KW/3.0KW
LENGTH ACCURACY	±0.025MM	±0.025MM
VERTICALITY	≤0.05	≤0.05
DIMENSIONS	1850X1500X1520MM	1850X1500X1600MM
WEIGHT	1000KG	1200KG



RT-60 & 90 CNC-C

DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR LONG STOCK, 3-AXIS SERVO PRECISION



PARAMETER TABLE		
MODEL	RT-60 CNC-C	RT-90 CNC-C
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM
APPLICABLE LENGTH	200-1000MM	200-1000MM
APPLICABLE WALL THICKNESS	≤3MM	≤3MM
WORKING PRESSURE		
WORKING SPEED	≈5-6S	≈5-6S
SERVO MOTOR	750W	1000W
MAIN MOTOR	2.2KW	3.0KW
LENGTH ACCURACY	±0.02MM	±0.02MM
VERTICALITY	≤0.05	≤0.05
DIMENSIONS	2852X1550X1900MM	2852X1550X1900MM
WEIGHT	1300KG	1500KG

RT-60, 90 & 120 QC

PNEUMATIC DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR LONG STOCK

PARAMETER TABLE			
MODEL	RT-60 QC	RT-90 QC	RT-120 QC
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM	Φ20-Φ120MM
APPLICABLE LENGTH	200-700MM/1000/1500		
APPLICABLE WALL THICKNESS	≤5MM	≤5MM	≤5MM
WORKING PRESSURE			
WORKING SPEED	≈5S	≈5S	≈5S
MAIN MOTOR	1.5KW	2.2KW	3.0KW
LENGTH ACCURACY	±0.1MM	±0.1MM	±0.1MM
VERTICALITY	≤0.1	≤0.1	≤0.1
DIMENSIONS	1850X1500X1520MM	1850X1500X1600MM	2400X1800X1800MM
WEIGHT	1000KG	1200KG	1700KG



RT 60, 90 & 120 YC-C

DUAL-HEAD HYDRAULIC PIPE CHAMFERING MACHINE FOR LONG STOCK



PARAMETER TABLE			
MODEL	RT-60 YC-C	RT-90 YC-C	RT-120 YC-C
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM	Φ20-Φ120MM
APPLICABLE LENGTH	200-700MM/1000/1500		
APPLICABLE WALL THICKNESS	≤5MM	≤5MM	≤5MM
WORKING PRESSURE	<30KG	<30KG	<30KG
WORKING SPEED	≈5-6S	≈6-8S	≈6-8S
MAIN MOTOR	2.2KW	3.0KW	4.0KW
LENGTH ACCURACY	±0.1MM	±0.1MM	±0.1MM
VERTICALITY	≤0.1	≤0.1	≤0.1
DIMENSIONS	1850X1500X1520MM	1850X1500X1600MM	2400X1800X1800MM
WEIGHT	1200KG	1400KG	1900KG

RT 60, 90 & 120 NC-CL

DOUBLE-HEAD PIPE CHAMFERING MACHINE, LONG-LENGTH SERIES, PNEUMATIC EXTENSION TYPE

PARAMETER TABLE			
MODEL	RT-60 NC-CL	RT-90 NC-CL	RT-120 NC-CL
APPLICABLE DIAMETER	Φ8-Φ60MM	Φ20-Φ90MM	Φ20-Φ120MM
APPLICABLE LENGTH	300-2500MM/3000/3500/4000		
APPLICABLE WALL THICKNESS	≤3MM	≤3MM	≤3MM
WORKING PRESSURE			
WORKING SPEED	≈5S	≈5S	≈5S
MAIN MOTOR	2.2KW	3.0KW	4.0KW
LENGTH ACCURACY	±0.1MM	±0.1MM	±0.1MM
VERTICALITY	≤0.1	≤0.1	≤0.1
DIMENSIONS	3400X1000X1600MM		
WEIGHT	2000KG		





RT-30 QC

AUTOMATIC DOUBLE-HEAD CHAMFERING LINE FOR SLENDER MATERIAL

PARAMETER TABLE	
MODEL	RT-30 QC
APPLICABLE DIAMETER	Φ6-Φ30MM
APPLICABLE LENGTH	200-600MM
APPLICABLE WALL THICKNESS	≤3MM
WORKING PRESSURE	
WORKING SPEED	≈8-10S
SERVO MOTOR	750W
MAIN MOTOR	1.5KW
VERTICALITY	±0.1MM, ±0.05MM
DIMENSIONS	5300X3211X1600MM
WEIGHT	3500KG

RT-150 & 200 CNC

DOUBLE-HEAD PIPE CHAMFERING MACHINE, LONG-LENGTH SERVO TYPE

PARAMETER TABLE		
MODEL	RT-150 CNC	RT-200 CNC
APPLICABLE DIAMETER	Φ50-Φ150MM	Φ50-Φ200MM
APPLICABLE LENGTH	200-500MM/1000MM/1500MM	
APPLICABLE WALL THICKNESS	≤3MM	≤3MM
WORKING PRESSURE	—	—
WORKING SPEED	≈10-15S	≈15-20S
SERVO MOTOR	750W-JS	1000W-JS
MAIN MOTOR	4KW	5.5KW
LENGTH ACCURACY	±0.05MM	±0.05MM
VERTICALITY	≤0.05	≤0.05
DIMENSIONS	2500X1840X2000MM	2500X1840X2000MM
WEIGHT	2500KG	3000KG



RT-300 & 350 YC

DOUBLE-HEAD PIPE CHAMFERING MACHINE FOR LONG WORKPIECES

PARAMETER TABLE		
MODEL	RT-300 YC	RT-350 YC
APPLICABLE DIAMETER	Φ100-Φ300MM	Φ100-Φ350MM
APPLICABLE LENGTH	200-500MM/1000MM/1500MM	
APPLICABLE WALL THICKNESS	≤10MM	≤10MM
WORKING PRESSURE	≤30KG	≤30KG
WORKING SPEED	4.0KW	4.0KW
OIL PUMP MOTOR	4.0KW	4.0KW
MAIN MOTOR	7.5KW	11KW
LENGTH ACCURACY	±0.1MM	±0.1MM
DIMENSIONS	2500X1840X2000MM	
WEIGHT	2500KG	3000KG

RT-50, 80 & 100 YC

HYDRAULIC DOUBLE-HEAD PIPE CHAMFERING MACHINE WITH LONG-MATERIAL SUPPORT

PARAMETER TABLE			
MODEL	RT-50 YC	RT-80 YC	RT-100 YC
APPLICABLE DIAMETER	Φ10-Φ50MM	Φ20-Φ80MM	Φ20-Φ100MM
APPLICABLE LENGTH	200-1000MM/1500MM/2000MM/2500MM		
APPLICABLE WALL THICKNESS	≤10MM	≤10MM	≤10MM
WORKING PRESSURE	≤30KG	≤30KG	≤30KG
WORKING SPEED	≈6.8S	≈8-10S	≈10-15S
MAIN MOTOR	2.2KW	3.0KW	4.0KW
LENGTH ACCURACY	±0.1MM	±0.1MM	±0.1MM
DIMENSIONS	2000X1200X1200MM		
WEIGHT	1000KG		



RT 50, 80 & 100 YC

HYDRAULIC DOUBLE-HEAD PIPE CHAMFERING MACHINE, LONG MATERIAL SERIES, 3-4 M



PARAMETER TABLE			
MODEL	RT-50 YC	RT-80 YC	RT-100 YC
APPLICABLE DIAMETER	Φ10-Φ50MM	Φ20-Φ80MM	Φ20-Φ100MM
APPLICABLE LENGTH	200-1000MM/1500MM/2000MM		
APPLICABLE WALL THICKNESS	≤10MM	≤10MM	≤10MM
WORKING PRESSURE	≤30KG	≤30KG	≤30KG
WORKING SPEED	≈6.8S	≈8-10S	≈10-15S
MAIN MOTOR	2.2KW	3.0KW	4.0KW
LENGTH ACCURACY	±0.1	±0.1	±0.1
VERTICALITY	≤0.1	≤0.1	≤0.1
DIMENSIONS	5000X1130X1300MM	5000X1130X1300MM	5300X1300X1450MM
WEIGHT	1300KG	1500KG	1800KG

RT-50, 80, 100, 125 & 150 SM-QP

TWIN-HEAD PNEUMATIC PIPE CHAMFERING MACHINE FOR LONG-LENGTH PIPES

PARAMETER TABLE					
MODEL	RT-50 SM-QP	RT-80 SM-QP	RT-100 SM-QP	RT-125 SM-QP	RT-150 SM-QP
APPLICABLE OUTER DIA.	Φ8-Φ50MM	Φ8-Φ80MM	Φ10-Φ100MM	Φ19-Φ125MM	Φ25-Φ150MM
PROCESSING LENGTH	70-550/1000/1500/2000MM				
WORKING PRESSURE					
PROCESSING ACCURACY	±0.1MM	±0.1MM	±0.1MM	±0.1MM	±0.1MM
PROCESSING SPEED	3-6S/P	3-6S/P	6-15S/P	10-15S/P	15-30S/P
APPLICABLE MATERIALS	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR				
MACHINE DIMENSIONS	1800X1000X1100MM	1800X1100X1150MM	2000X1200X1250MM	2000X1300X1300MM	2200X1500X1500MM





RT-50, 80, 100, 125 & 150 SM-QP

DOUBLE-HEAD PIPE CHAMFERING MACHINE, STANDARD HYDRAULIC TYPE

PARAMETER TABLE					
MODEL	RT-50 SM-QP	RT-80 SM-QP	RT-100 SM-QP	RT-125 SM-QP	RT-150 SM-QP
APPLICABLE OUTER DIA.	Φ8-Φ50MM	Φ20-Φ80MM	Φ20-Φ100MM	Φ20-Φ125MM	Φ25-Φ150MM
PROCESSING LENGTH	70/550/1000/1500/2000MM				
WORKING PRESSURE	≤10KG	≤10KG	≤10KG	≤10KG	≤10KG
PROCESSING ACCURACY	±0.1MM	±0.1MM	±0.1MM	±0.1MM	±0.1MM
PROCESSING SPEED	6-8S/P	6-8S/P	8-12S/P	10-15S/P	15-30S/P
APPLICABLE MATERIALS	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR				
MACHINE DIMENSIONS	1800X1000X1100MM	1800X1100X1150MM	2000X1200X1250MM	2000X1300X1300MM	2200X1500X1500MM

RT-60 AC-V

RT-60 AC-V SERVO PIPE CHAMFERING MACHINE WITH V-CLAMP

PARAMETER TABLE	
MODEL	RT-60 AC-V
APPLICABLE OUTER DIAMETER	Φ3-Φ60MM
PROCESSING LENGTH	≥40MM
WORKING PRESSURE	≤10KG
PROCESSING ACCURACY	±0.1MM
PROCESSING SPEED	3-4S/P
APPLICABLE MATERIALS	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR
MACHINE DIMENSIONS	1100X1000X1300MM



RT-120 & 150 AC-YK

SINGLE-HEAD PIPE CHAMFERING MACHINE WITH HYDRAULIC CHUCK



PARAMETER TABLE		
MODEL	RT-120 AC-YK	RT-150 AC-YK
APPLICABLE OUTER DIAMETER	Φ30-Φ120MM	Φ20-Φ150MM
PROCESSING LENGTH	≥40MM	≥50MM
MAIN MOTOR POWER	3.0KG	4.0KG
WORKING PRESSURE	≤30KG	≤30KG
PROCESSING ACCURACY	±0.1MM	±0.1MM
PROCESSING SPEED	3-5S/P	3-6S/P
APPLICABLE MATERIALS	STEEL PIPE, IRON PIPE, STAINLESS STEEL PIPE, ALUMINUM PIPE, COPPER PIPE, PLASTIC PIPE, NYLON PIPE, ROUND BAR	
MACHINE NET WEIGHT	310KG	
MACHINE DIMENSIONS	1100X1000X1300MM	1100X1000X1300MM

SAMPLES



-MEBA-
sawing solutions.

+91-86850-00843 info@mebaindia.com www.mebaindia.com

Plot No-160 ,DLF Industrial Estate,Phase-1, Village Atmadpur, Faridabad-121003