BIO ADSORBENT FOR ENVIRONMENTAL APPLICATIONS

Project report

under the supervision of Prof. Gopal Das for the degree of

Bachelor of Technology

in

Chemical Science and Technology

By

DEEPAK KUMAR MANDAL

(Roll No. 170122014)



DEPARTMENT OF CHEMISTRY INDIAN INSTITUTE OF TECHNOLOGY, GUWAHATI

November, 2020

BIO ADSORBENT FOR ENVIRONMENTAL APPLICATIONS


Contents:

- 1. A brief introduction to the "Bio Adsorbent for Environmental Applications" that are going to be present in the article.
- 2. Background of the "Bio adsorbent for the adsorption of heavy metal ions and toxic dyes".
 - ➤ Different Types of Bio adsorbent
 - ➤ Advantages of Bio adsorbent in comparison of Chemical adsorbent
- 3. Recent Advances to promote Bio Adsorbent for Environmental Applications.
 - ➤ Usage of Bio adsorbent for the adsorption of toxic heavy metal ions
 - ➤ Usage of Bio adsorbent for the adsorption of toxic dyes molecule
- 4. Conclusion/Summary
- 5. References/Bibliography

INTRODUCTION

Bio adsorption or Biosorption refers to the ability of biological materials to preferentially concentrate specific substance or molecular species such as heavy metals ion, dyes from the medium or solution by the way metabolically mediated or physical and chemical pathway of uptake. The materials or substances, on the surface of which the biosorption occurs, is known as bio adsorbent.

The bio adsorption mechanism of metal ions by adsorbent is usually complex and involves one or combinations of various different processes. [1]



As we know, Heavy metals are a toxic pollutant, that commonly present in aqueous solution or waste-water. Let's understand from where these heavy metal ions come into our environment. So, basically there are following source of introduction of metal ions which includes lead (Pb), arsenic (As), mercury (Hg), nickel (Ni), chromium (Cr), zinc (Zn), cadmium (Cd), and copper (Cu):-

- i. Natural source such as volcanic emissions, deep-sea vents, forest fires, etc.
- ii. Anthropogenic source such as mining activities, pesticides, petroleum refinery, smelting, metal-manufacturing plants, battery manufacturing, pigment, painting and coating industries, etc. [2]


Another common pollutant is Dyes, which typically come from textile industries. Ike heavy metals they are also toxic, not bio-degradable thus, are dangerous for the health of humans as well as the environment.

BACKGROUNG **O**F **T**HE **F**IELD


There are following two types of Bio adsorbent [3]:-

- i. Living organic materials
- ii. Non-living organic materials
- i.) Further, Living organic materials have been classified into four parts:
 - a) Bacterial bio adsorption:- The structure of bacteria is shown in scheme 1. The cell wall of Bacterium consists of various functional groups such as amine (-NH₂), hydroxyl (-OH), sulfate (-SO₄H), carboxyl (-CO₂H), phosphate(PO₄³⁻), which is responsible for binding with heavy metal ions and/or dyes.

The mechanisms which is responsible for bio adsorption is may be one or the combination of complexation, electrostatic interaction, ion exchange, chelation, coordination, microprecipitation. [4]




b) Bio adsorption by yeast:- The most common example of yeast is "Saccharomyces cerevisiae". The biomass of yeast consists of the element like Carbon (C), Oxygen (O), Sodium (Na), Magnesium (Mg), Phosphorus (P), Potassium (K). Here, Bio adsorption of metal ion takes place mainly by the ion exchange mechanism. [5]




Scheme 3: Structure of Yeast, Saccharomyces cerevisiae

c) Bio adsorption by algae:- Algae is an aquatic plant that have no true stems and roots. The cell wall of algae consists of functional groups such as amino, hydroxyl, imidazole (C₃H₄N₂), sulfate, phosphate and amine. The mechanism of metal uptake in algae cells is the same as that of bacteria. [3]



d) Bio adsorption by fungi:- The fungi is eukaryotic living organisms such as mushrooms, yeasts etc. The mechanism involved in bio adsorption by fungi are either by bioaccumulation or metal uptake process by cell wall of the fungi that have functional group like uronic acids, phosphate, nitrogen containing ligand, carboxyl, proteins, chitin, chitosan.



ii.) And Non-living organic materials are basically the wastes of food industries or agricultural by-products such as cotton seed hulls, rice husk, corn cobs, activated charcoal or fruits peels. It contains cellulosic materials in their cell wall which has carboxylic (-COOH) or phenolic (-OH) as a functional group.

The binding of heavy metal ions with the functional groups by cation exchange process results in bio adsorption and hence, removal of heavy metal ions takes place from the medium.





Figure 2: The pictorial representation of few waste of agricultural or food industry which may be used as bio adsorbent.

Advantage of Bio Adsorbent in Comparison of Chemical Adsorbent: [3, 6]

- ✔ Bio adsorbent is relatively inexpensive in comparison to the chemical adsorbent.
- ✔ Bio adsorbent has features like high selectivity and efficiency or great performance.
- ✓ As a Bio adsorbent, we use either living or non-living materials which is basically biological sludge for adsorption purpose and it is an eco-friendly. Hence, we are minimizing the use of chemical substances, and that acts as an edge of Bio adsorption over Chemical adsorption.
- ✔ Regeneration or renewal of bio adsorbent.
- Production to no extent of toxic substances. Therefore, bio adsorbent involves much greener approach to adsorption of toxic heavy metal ions and toxic dye molecule in comparison to chemical adsorbent.

There are few basic facts that are involved in the adsorption process where the activated carbon-based bio adsorbent is used for adsorption of toxic heavy metal ions.

Activated carbon has prepared from the Pistachio shells, and one can get these shells from the pistachio trees.

Now we are going to see some basic terms that have been used throughout the adsorption process of cellulose-keratin based bio adsorbent which is used for adsorption of toxic dyes molecules.

<u>Dyes</u>:- It is used to color the substrates, to which they have an affinity. Dye has a complex structure and thus, it is stable and not biodegradable in the environment [8]. It includes a variety of functional group such as azo (-N=N-), carbonyl (=C=O), nitro (-NO or =NO-OH), carbon (=C=C=), nitroso (-NO or N-OH), sulfur (=C=S) etc., which are different color properties.

There are following few examples of commercial dyes and their chemical structures:-

From figure 1, we can say that, a typical hen feather contains functional groups such as -COOH, -OH, -(NH)-(CO)-, and that can play an important role in various interaction between adsorbent and dye molecule that leads them to be separated.




Figure 1: Chemical Structures of a typical feather and cotton

Keratin could be get from butchery wastes like feathers, low quality wood, animal hairs or waste fabrics from textile industries. It includes functional groups such as amino (-NH₂), carboxyl (-COOH) groups on its molecule, which play crucial role in adsorption of dye molecules because it acts as active adsorption sites for removal of toxic dyes. [8]

RECENT ADVANCES TO PROMOTE BIO ADSORBENT


Let's take an example of bio adsorbent for the adsorption of toxic heavy metal ions.

A modified bio adsorbent which has been prepared by the loading of Fe₃O₄ nano-particles and immobilization of 1,4-butane sultone (-SO₃H) on the surface of activated carbon. [7]

There are following two steps involved in the synthesis of modified activated carbon-based bio adsorbent (as shown in scheme 6):-

1. The Activated Carbon (AC) is produced from the agriculture wastes. It is a natural resource of Carbon. By Supporting Fe₃O₄ nano particles onto activated carbon, we get the modified resulting surface which has a large number of active sites, that can increase the chemical


- adsorption or chemisorption. Hence, modified activated carbon chemistry has been developed, which has the presence of functional group containing oxygen atom that plays essential role for the removal of heavy metals. Because these groups can form complex with heavy metal ions. Here, the reaction has to be done in the ultrasonic probe.
- 2. Fe₃O₄ nano-particle activated carbon can be separated by using an external magnet. Further, this is subjected to 1, 4 butane sultone via ring-opening reaction, followed by sonication under mild condition, to enhance the acidic functional groups on the Fe₃O₄ nano-particle activated carbon. That will result into nanocomposite which is termed as Fe₃O₄ NPs@AC@C₄H₈SO₃H composites. Here 1, 4 butane sultone is a reagent and strong chelating or complexing agent which helps in achieving the desired objective of separation of heavy metals, because it includes sulfur and oxygen atoms that could be strongly combined with heavy metal ions and cause them to separated.



(Step 1) synthesis of Fe_3O_4 @AC (Step 2) synthesis of Fe_3O_4 NPs@AC@C $_4H_8SO_3H$ composites. Scheme 1.1: The synthesis processes of nanocomposites and their structures.

The Mechanism for adsorption of heavy metal ions:

According to given mechanism (as shown just above in Scheme 7), the heavy metal ions forms complex with the sulfonic acid (- SO_3H), hydroxyl (-OH), and carboxyl (- CO_2H) group presents on the surface of Fe₃O₄ NPs@AC@C₄H₈SO₃H composites. This is what the major factor that causes the sepration or adsorption of the heavy metals from aq. Solutions.




Scheme 7: Mechanism for adsorption of toxic metal ions on the surface of bio adsorbent.

The adsorption of toxic heavy metal ions on this nanocomposite bio-adsorbent depends upon various factor such as:-

- The pH of the solution
- > Temperature
- > Dosage or amount of adsorbent
- The initial concentration of the metal ions like As(III), Cd(II), Pb(II).
- > Time of contact with adsorbent in the aqueous solution.

From figure 3 as shown below, which is a graph of "pH Vs amount of metal ion adsorbed onto the adsorbent", We can analyse that on increasing the value of pH, the efficiency of adsorption of the heavy metal ions onto nano-composite have increased.



The reason behind is, when we increase the value of pH, deprotonation of the sulfonic acid (-SO₃H), hydroxyl (-OH), and carboxyl (-CO₂H) groups on the surface of adsorbent takes place, which will have resulted into electrostatic interaction enhancement between the heavy metal ions and active sites of the nanocomposite.

The *Recyclization process* could be performed by just desorbing the metal ions from the adsorbent. The nano-composite biosorbent contained heavy metal ions is stirred in HCL solutions, followed by neutralization with sodium hydroxide(dil.) solution. And then it is recovered by using an external magnet. Further, it is subjected to the adsorption processes to determine its reusability.


Usage: This modified bio adsorbent can be used for adsorption of heavy metal ions such as Lead: Pb(II), Cadmium: Cd(II), and Arsenic: As(III) from aqueous solutions at an industrial scale.

Now, Let's take an example of bio adsorbent for the adsorption of toxic dye molecules.

Cellulose nano crystal – reinforced keratin bio adsorbent for adsorption of dye molecules from aqueous solution. [8]

There are following steps involved in the preparation of cellulose-keratin based bio adsorbent (as shown below in Scheme 8):-

- At first, Keratin solution is prepared from feathers by immersing into urea (CH₄N₂O) solution with cysteine (HO₂CCHCH₂SH) followed by removal of undissolved feathers. This process is termed as Extraction.
- We get Cellulose nano-crystal (CNC) by the hydrolysis of cotton fabric with sulfuric acid (H₂SO₄).
- CNC is added into keratin solution by using the ultrasonication process, followed by the addition of crosslinking agent. Here, Glutaraldehyde (C₅H₈O₂) is act as a crosslinking agent.
- Cellulose nano crystal reinforced keratin adsorbent is fabricated by the freeze-dried process.
 This process enhances the crosslinking reaction. Thus, we get the water stable bio adsorbent.




Scheme 8: Synthesis of cellulose-keratin based bio adsorbent and their structure.

The Mechanism for adsorption of toxic dyes molecule:

From the mechanism as shown in Scheme 9, we can analyse that the separation of dye molecules from aqueous solution takes place due to the various interaction between the dye molecule and the

functional groups like amino (-NH₂), hydroxyl (-OH), and carboxyl (-COOH) group presents in the cellulose nanocrystal-reinforced keratin bio adsorbent:-

- i. Formation of hydrogen bonds
- ii. Van der waals forces of interaction
- iii. Electrostatic force of interaction



Scheme 9: Mechanism for adsorption of dyes molecule in the cellulose-keratin based bio adsorbent.

Mechanical Property of adsorbent plays an important role in recyclization or regeneration. We can increase the mechanical strength of bio adsorbent, by reinforcing the cellulose nano crystal in the keratin sponge matrix. So, basically it results in homogeneous dispersion of CNC nanoparticles with a huge number of point-to-point connection (which has been shown in diagram with red line). Thus, improvement in the performance of the bio adsorbent.

Hence, we can say that Cellulose Nano-Crystal acts as a nano-filler to provide the dimensional stability and structural integrity to the bio adsorbent.




Figure 4: Strain Vs Stress Curve which shows structural shrinkage in two cases.

This fabricated bio adsorbent has large specific surface areas, enhanced mechanical property with high porosity which shows excellent performance for adsorption of dye molecules.

The **recyclization** of cellulose-keratin based bio adsorbent is executed by immersing the dyes contained adsorbent into sodium hydroxide solution with firmly press of compress. then the adsorbent is drawn out from the NaOH solution. Further, it is used again for adsorption of toxic dyes molecules from an aqueous solution. In this way regeneration of adsorbent leads to the high efficiencies of desorption after adsorption of dyes molecules, and thus provides good reusability.

Usage: This bio adsorbent is used for adsorption of dyes such as Reactive Black 5 (RB5), and Direct Red 80 (DR80) from aqueous solution or wastewater.

CONCLUSION

The Best part here is - Apart from having a high adsorption capacity, these bio adsorbent exhibits advantages such as green synthesis, recyclization, low-cost, and more importantly easy separation with the technically feasible method. So, these bio adsorbents could be a suitable option for the adsorption of toxic heavy metal ions and toxic dyes. In this way, we could also put value added to the waste biomass.

That's what makes it sustainable, renewal, and environmentally friendly alternative adsorbent for environmental applications.

REFERENCES

- 1. ^ A review on Bio adsorption (2018). DOI: 10.3390/md16020065
- 2. ^A master survivalist in the harsh and anthropogenic environment. DOI: http://sci-hub.do/10.1371/journal.pone.0010433
- 3. ^Bio adsorption of Heavy Metal ions; 2018. DOI: http://sci-hub.do/10.5772/intechopen.72099
- 4 ^ A review paper on biosorption and bacterial biosorbent. DOI: https://sci-hub.do/10.1016/j.biotechadv.2008.02.002
- 5 ^Bio adsorption by Saccharomyces cerevisiae yeast biomass (2019). DOI: https://doi.org/10.1016/j.btre.2019.e00315
- 6 ^ Introduction to the Adsorption; Basic analysis with applications by Chi Tien, Syracuse University (2018).
- 7. ^A modified Activated Carbon-based bio adsorbent for adsorption of toxic heavy metals by using sultone; 2019. DOI: https://doi.org/10.1016/j.msec.2019.03.081

8. $^{\wedge}$ Cellulose nano crystal – reinforced keratin bio adsorbent for adsorption of dye molecules from
aqueous solutions; 2017. DOI: http://dx.doi.org/10.1016/j.biortech.2017.01.070
BTP (Phase-1), 2017-21