PIZZA Sales SQL Queries

A.KPI's

1.Total Revenue:

```
SELECT SUM(total_price) AS Total_Revenue from pizza_sales
```

Results | Messages

	Total_Revenue
1	817860.05083847

2.Average Order Value:

```
SELECT SUM(total_price) / COUNT(DISTINCT order_id)as Avg_Order_Value
from pizza_sales
```

Results | Messages

	Avg_Order_Value
1	38.3072623343546

3.Total Pizza Sold:

```
SELECT SUM(quantity) as Total_Pizza_Sold from pizza_sales
```

Results | Messages

	Total_Pizza_Sold
1	49574

4.Total Orders:

```
SELECT COUNT(DISTINCT order_id) AS Total_Orders from pizza_sales
```

Results | Messages

	Total_Orders
1	21350

5.Avg Pizzas Per Order:

```
SELECT CAST(CAST(SUM(quantity) AS Decimal(10,2)) /
CAST(COUNT(DISTINCt order_id)AS Decimal(10,2)) AS Decimal(10,2)) As
Avg_Pizzas_per_Order from pizza_sales
```

Results | Messages

	Avg_Pizzas_per_Order
1	2.32

B. Charts Requirment

1. Total Trend for total orders:

```
SELECT DATENAME(DW, order_date) as order_day, COUNT(DISTINCT
order_id) as Total_Orders
from pizza_sales
GROUP BY DATENAME(DW, order_date)
```

Results | Messages

	order_day	Total_Orders
1	Saturday	3158
2	Wednesday	3024
3	Monday	2794
4	Sunday	2624
5	Friday	3538
6	Thursday	3239
7	Tuesday	2973

2.Monthly Trends for Orders:

```
SELECT DATENAME(MONTH, order_date) AS Month_Name,
COUNT(DISTINCT order_id) AS Total_Orders
from pizza_sales
GROUP By DATENAME(MONTH, order_date)
ORDER BY Total_Orders DESC
```

Results | Messages

	Month_Name	Total_Orders
1	July	1935
2	May	1853
3	January	1845
4	August	1841
5	March	1840
6	April	1799
7	November	1792
8	June	1773
9	February	1685
10	December	1680
11	September	1661
12	October	1646

3. Percentage of Sales by Pizza Category:

```
SELECT pizza_category, sum(total_price) as Total_Sales, sum(total_price) * 100 /
(SELECT sum(total_price) from pizza_sales WHERE MONTH(order_date) = 1)
AS PCT_Total_Sales
from pizza_sales
WHERE MONTH(order_date) = 1
GROUP BY pizza_category
```

Results | Messages

	pizza_category	Total_Sales	PCT_Total_Sales
1	Chicken	16188.75	23.1952780348435
2	Supreme	17929.7499866486	25.6897867985821
3	Classic	18619.4000015259	26.6779189176038
4	Veggie	17055.4000778198	24.4370162489706

4.Percentage of Sales By Pizza Size:

```
SELECT pizza_size,CAST(sum(total_price)as Decimal(10,2)) as Total_Sales,
CAST(sum(total_price) * 100 /

(SELECT sum(total_price) from pizza_sales Where
Datepart(QUARTER,order_date) = 1) AS Decimal(10,2)) AS PCT
from pizza_sales
Where Datepart(QUARTER,order_date) = 1
GROUP BY pizza_size
Order By PCT DESC
```

Results | Messages

	pizza_size	Total_Sales	PCT
1	L	95229.65	46.37
2	M	61159.00	29.78
3	S	45384.25	22.10
4	XL	3289.50	1.60
5	XXL	287.60	0.14

5. Total Pizzas Sold by Category:

```
SELECT pizza_category, SUM(quantity) as Total_Quantity_Sold
FROM pizza_sales
WHERE MONTH(order_date) = 2
GROUP BY pizza_category
ORDER BY Total_Quantity_Sold DESC
```

6. Top 5 Pizzas by Revenue:

```
SELECT Top 5 pizza_name, sum(total_price) as Total_Revenue from pizza_sales
GROUP BY pizza_name
Order By Total_Revenue DESC
```

	pizza_name	Total_Revenue
1	The Thai Chicken Pizza	43434.25
2	The Barbecue Chicken Pizza	42768
3	The California Chicken Pizza	41409.5
4	The Classic Deluxe Pizza	38180.5
5	The Spicy Italian Pizza	34831.25

7. Bottom 5 Pizzas by Revenue:

```
SELECT Top 5 pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Revenue
```

	pizza_name	Total_Revenue
1	The Brie Carre Pizza	11588.4998130798
2	The Green Garden Pizza	13955.75
3	The Spinach Supreme Pizza	15277.75
4	The Mediterranean Pizza	15360.5
5	The Spinach Pesto Pizza	15596

9. Top 5 Pizzas by Quantity

```
SELECT Top 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold DESC
```

	pizza_name	Total_Pizza_Sold
1	The Classic Deluxe Pizza	2453
2	The Barbecue Chicken Pizza	2432
3	The Hawaiian Pizza	2422
4	The Pepperoni Pizza	2418
5	The Thai Chicken Pizza	2371

10. Bottom 5 Pizzas by Quantity

```
SELECT TOP 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold

FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold
```

Results Messages

	pizza_name	Total_Pizza_Sold
1	The Brie Carre Pizza	490
2	The Mediterranean Pizza	934
3	The Calabrese Pizza	937
4	The Spinach Supreme Pizza	950
5	The Soppressata Pizza	961

11. Top 5 Pizzas by Total Orders

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
```

```
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders DESC
```

Results | Messages

	pizza_name	Total_Orders
1	The Classic Deluxe Pizza	2329
2	The Hawaiian Pizza	2280
3	The Pepperoni Pizza	2278
4	The Barbecue Chicken Pizza	2273
5	The Thai Chicken Pizza	2225

12. Borrom 5 Pizzas by Total Orders

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders
```

	pizza_name	Total_Orders
1	The Brie Carre Pizza	480
2	The Mediterranean Pizza	912
3	The Spinach Supreme Pizza	918
4	The Calabrese Pizza	918
5	The Chicken Pesto Pizza	938

NOTE

If you want to apply the pizza_category or pizza_size filters to the above queries you can use WHERE clause. Follow some of below examples

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
WHERE pizza_category = 'Classic'
GROUP BY pizza_name
ORDER BY Total_Orders ASC
```