14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

Attn:	**Ranjit**
Company:	**Growth Built**
Address:	**Marion St Leichhardt**
Specification	**Waterproofing Specification**
Email:	**web@xoroglobal.com**
Date:	**07/04/2022**
Reference id:	**DTSPEC 22-07-230**

DUROTECH INDUSTRIES

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

JAS-ANZ ISO 9001 Quality Certified System ISO 14001 Environment Certified System ISO 45001 Health and Safety Certified System

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

Scope

Prepare and apply a waterproofing or protective coating system to areas listed below.

Waterproofing

- DWPS 10.1 – WATERPROOFINGFOR INTERNALWET AREAS
- DWPS 10.2 – WATERPROOFING FOR BALCONIES
- DWPS 10.3 – WATERPROOFING FOR ROOF SLAB
- DWPS 10.4 – WATERPROOFINGFOR LIFT PITS
- DWPS 10.5 – WATERPROOFINGFOR WATERTANKS
- DWPS 10.6 – EPOXY FLOORING FOR SERVICE AREAS
- DWPS 10.7 – CONCRETE SEALER
- DWPS 10.8 – WATERPROOFING FOR PLANTER BOXES

Scope Requirements

This specification details the substrate preparation, priming and installation details of Enviro 200P Ultra, Enviro 700X, Enviro Hydrostatic 1 (waterproofing membranes); Enviro Shield, Enviro Epoxy B-LV, Enviro Prime SB (primers); Enviro 800 TC. Application is to be by accredited applicators only and strictly in accordance with the product data sheet.

Please refer to the respective Product Data Sheets for further information including product description, typical uses and application details.

Alternatively, and dependent of substrate conditions, primer can be selected in consultation with Envirosystems depending on environmental conditions.

All warranty periods quoted are when installation is by Envirosystems accredited applicators.details.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

Substrate Preparation

Ensure that the concrete substrate is free from contaminants by mechanical profiling such as captive shot blast cleaning or vacuum grinding.

Fill all bug holes and defects in concrete with the Enviro Epoxy B range of concrete repair products and allow curing.

Vee out cracks and fill with a polyurethane joint sealant such as Enviro Flex PRO or Enviro Flex FC. Moisture content of concrete is to be below 10%

Use Enviro DeSalin range to prepare substrate, such as, Enviro DeSalin AM to disinfect the surface from any mould, algae or microorganisms; Enviro DeSalin DG to remove any grease, oil, grime; Enviro DeSalin C to remove residues, salt deposits and efflorescence.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

ISO 9001 Quality Certified System
ISO 14001 Environment Certified System
ISO 45001 Health and Safety Certified System

DUROTECH
Waterproofing • Sealants • Adhesives

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 101 – WATERPROOFINGFOR INTERNALWET AREAS	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Enviro Shield	Primer(belowscreed)	Enviro Shield is a two-part
	Enviro FL + Deck Web	Bond Breaker	The coverage of Enviro Flex FL
	Enviro 700X	Membrane(below screed)	Enviro 700X is a single component
	Enviro Shield	Primer (walls)	Enviro Shield is a two-part, water-based epoxy
	10 Years	Warranty Period	15 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

DUROTECH
Waterproofing • Sealants • Adhesives

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 102 – WATERPROOFING FOR BALCONIES	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Enviro Shield	Primer (below screed)	Enviro Shield is a two-part, water-based epoxy
	Enviro FL + Deck Web	Bond Breaker	The coverage of Enviro Flex FL
	Enviro 700X	Membrane (below screed)	Enviro 700X is a single component
	10 Years	Warranty Period	15 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

JAS-ANZ
ISO 9001 Quality Certified System
ISO 14001 Environment Certified System
ISO 45001 Health and Safety Certified System

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 103 – WATERPROOFING FOR ROOF SLAB	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Enviro Shield	Primer	Enviro Shield is a two-part,
	Enviro FL + Deck Web	Bond Breaker	The coverage of Enviro Flex FL will depend on the type of substrate
	Enviro 700X	Membrane	Enviro 700X is a single component
	Enviro 800 TC	Topcoat	Enviro 800PUR T.C. is a 2-part, flexible
	10 Years	Warranty Period	15 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

DUROTECH
Waterproofing • Sealants • Adhesives

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 104 – WATERPROOFINGFOR LIFT PITS	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Hydrostatic 1	Membrane	Enviro Hydrostatic 1 is a single component
	Enviro FL + Deck Web	Bond Breaker	The coverage of Enviro Flex FL will depend on the type of substrate, the substrate conditions and the size of the cove
	Enviro Joint Band	Joint bandage	Enviro Joint Band is a wet area grade elastic joint bandage designed for use in waterproofing wall/floor junctions of internal and external wet areas and most other waterproofing applications.
	10 Years	WarrantyPeriod	15 years for Envirosystems accredited applicators

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

DUROTECH
Waterproofing • Sealants • Adhesives

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 105 – WATERPROOFINGFOR WATERTANKS	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Enviro Shield	Primer	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side
	Enviro FL + Deck Web	Bond Breaker	The coverage of Enviro Flex FL will depend on the type of substrate, the substrate conditions and the size of the cove
	Enviro 200PULTRA	Membrane	Enviro 200P ULTRA is an ultra-flexible,
	10 Years	WarrantyPeriod	10 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 106 – EPOXY FLOORING FOR SERVICE AREAS	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Epoxy B-LV	Primer	Enviro Epoxy B-LV can be used as a primer over dense concrete, as a bonding agent for both epoxy resin systems and cementitious, mortars and as a crackinjection material.
	Enviro Ultra Tuff	Epoxy Floor	Enviro Ultra Tuff Coating is a solvent free,
	10 Years	WarrantyPeriod	10 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 107 – CONCRETE SEALER	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	-	Surface preparation	Surfaces must be clean, dry, and free from contamination such as dust, laitance, grease, coatings and curing compounds.
	EnviroSeal WB	Floor sealant	Enviroseal WB is a water-based copolymer floor hardening and sealing compound for use on concrete floors, driveways and pedestrian surfaces.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

DUROTECH
Waterproofing • Sealants • Adhesives

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
DWPS 108 – WATERPROOFING FOR PLANTER BOXES	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Enviro Shield	Primer	Enviro Shield is a two-part
	Enviro FL + Deck Web	Bond Breaker	The coverage of Enviro Flex FL will depend on the type of substrate
	Enviro 700X	Membrane	Enviro 700X is a single componen
	Enviro 800 TC	Topcoat(where membrane exposed to UV)	Enviro 800PUR T.C. is a 2-part, flexible
	Enviro drainage cell	Drainage and protection	
	Enviro drainage cell	Drainage and protection	
	10 Years	WarrantyPeriod	10 years for Envirosystems accredited applicators

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.