14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

Attn:	**Ranjit**
Company:	**Kodexglobal**
Address:	**E-121**
Specification	**Waterproofing**
Email:	**Web@xoroglobal.com**
Date:	**01/05/2022**
Reference id:	**DTSPEC-20**

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

Scope

Prepare and apply a waterproofing or protective coating system to areas listed below.

Waterproofing

- WPS 101 – Waterproofing for internal wet areas (bathrooms and laundries)
- WPS 102 – Waterproofing for balconies
- WPS 103 – Waterproofing for roof slab
- WPS 104 – Waterproofing for lift pit
- WPS 105 – Waterproofing for water tanks
- WPS 106 – Epoxy flooring for service areas
- WPS 107 – Concrete Sealer
- WPS 108 – Planter Boxes

Scope Requirements

This specification details the substrate preparation, priming and installation details of Enviro 200P Ultra, Enviro 700X, Enviro Hydrostatic 1 (waterproofing membranes); Enviro Shield, Enviro Epoxy B-LV, Enviro Prime SB (primers); Enviro 800 TC. Application is to be by accredited applicators only and strictly in accordance with the product data sheet.

Please refer to the respective Product Data Sheets for further information including product description, typical uses and application details.

Alternatively, and dependent of substrate conditions, primer can be selected in consultation with Envirosystems depending on environmental conditions.

All warranty periods quoted are when installation is by Envirosystems accredited applicators.details.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

Substrate Preparation

Ensure that the concrete substrate is free from contaminants by mechanical profiling such as captive shot blast cleaning or vacuum grinding.

Fill all bug holes and defects in concrete with the Enviro Epoxy B range of concrete repair products and allow curing.

Vee out cracks and fill with a polyurethane joint sealant such as Enviro Flex PRO or Enviro Flex FC. Moisture content of concrete is to be below 10%

Use Enviro DeSalin range to prepare substrate, such as, Enviro DeSalin AM to disinfect the surface from any mould, algae or microorganisms; Enviro DeSalin DG to remove any grease, oil, grime; Enviro DeSalin C to remove residues, salt deposits and efflorescence.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

ISO 9001 Quality Certified System
ISO 14001 Environment Certified System
ISO 45001 Health and Safety Certified System

DUROTECH
Waterproofing • Sealants • Adhesives

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
WPS 100 – WATERPROOFING FOR INTERNAL WET AREAS	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Bond Breaker	Enviro FL + Deck Web	The coverage of Enviro Flex FL will depend on the type of substrate, the substrate conditions and the size of the cove. When prepared and primed in accordance with the instructions above, the following coverage rates should be expected.
	Membrane(below screed)	Enviro 700X	Enviro 700X is a single component, low odour polyurethane elastomer waterproofing membrane. It is to be applied to the prepared and primed substrate to a minimum dry film thickness (DFT) of 1.5mm (typically achieved in 2 coats).
	Primer (walls)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Membrane (walls)	Enviro 200P ULTRA	Enviro 200P ULTRA is an ultra-flexible, class III waterproofing membrane formulated on a water-based copolymer system that is urethane modified. It is fast drying and exhibits very good elasticity, excellent adhesion and outstanding elongation. It is to be applied to the primed substrate at a rate of 1.5 L/m² to a dry film thickness (DFT) of 1.0mm in 2 coats.
	Warranty Period	10 Years	15 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

DUROTECH
Waterproofing • Sealants • Adhesives

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
WPS 101 – WATERPROOFING FOR INTERNAL WET AREAS	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Bond Breaker	Enviro FL + Deck Web	The coverage of Enviro Flex FL will depend on the type of substrate, the substrate conditions and the size of the cove. When prepared and primed in accordance with the instructions above, the following coverage rates should be expected.
	Membrane(below screed)	Enviro 700X	Enviro 700X is a single component, low odour polyurethane elastomer waterproofing membrane. It is to be applied to the prepared and primed substrate to a minimum dry film thickness (DFT) of 1.5mm (typically achieved in 2 coats).
	Primer (walls)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Membrane (walls)	Enviro 200P ULTRA	Enviro 200P ULTRA is an ultra-flexible, class III waterproofing membrane formulated on a water-based copolymer system that is urethane modified. It is fast drying and exhibits very good elasticity, excellent adhesion and outstanding elongation. It is to be applied to the primed substrate at a rate of 1.5 L/m² to a dry film thickness (DFT) of 1.0mm in 2 coats.
	Warranty Period	10 Years	15 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

DUROTECH
Waterproofing • Sealants • Adhesives

SINCE 1977

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

	SYSTEM	ENVIROSYSTEMS PRODUCT	DESCRIPTION
WPS 102 – WATERPROOFING FOR INTERNAL WET AREAS	Primer (below screed)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Bond Breaker	Enviro FL + Deck Web	The coverage of Enviro Flex FL will depend on the type of substrate, the substrate conditions and the size of the cove. When prepared and primed in accordance with the instructions above, the following coverage rates should be expected.
	Membrane(below screed)	Enviro 700X	Enviro 700X is a single component, low odour polyurethane elastomer waterproofing membrane. It is to be applied to the prepared and primed substrate to a minimum dry film thickness (DFT) of 1.5mm (typically achieved in 2 coats).
	Primer (walls)	Enviro Shield	Enviro Shield is a two-part, water-based epoxy that acts as a hydrostatic barrier and primer coating in applications requiring a protection against water ingress from the negative side. In addition, Enviro Shield can also be used as a moisture tolerant primer. It is to be applied at a rate of 0.32 L/m² to a dry film thickness (DFT) of 0.150mm.
	Membrane (walls)	Enviro 200P ULTRA	Enviro 200P ULTRA is an ultra-flexible, class III waterproofing membrane formulated on a water-based copolymer system that is urethane modified. It is fast drying and exhibits very good elasticity, excellent adhesion and outstanding elongation. It is to be applied to the primed substrate at a rate of 1.5 L/m² to a dry film thickness (DFT) of 1.0mm in 2 coats.
	Warranty Period	10 Years	15 years for Envirosystems accredited applicators.

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses." Any information provided by DUROTECH in this document in relation to DUROTECH's goods or their use is given in good faith and is believed by DUROTECH to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. DUROTECH makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

JAS-ANZ
ISO 9001 Quality Certified System
ISO 14001 Environment Certified System
ISO 45001 Health and Safety Certified System