PRODUCT DATA SHEET

DURO DRAINAGE CELL

DUROTECH
Engineered Construction Chemicals
Made In Australia For Over 45 Years

DESCRIPTION

Duro Drainage Cell is a two-core drainage sheet consisting of a non-woven geotextile filter layer thermally welded to a water impermeable, recycled HDPE (High Density Polyethylene) drainage membrane. Duro Drainage Cell provides outstanding drainage and protection to the outside face of basement walls, preventing the build-up of water pressure and protecting the structure from aggressive water, chemicals and toxins.

Recommended for:

- As the drainage layer of an externally applied waterproofing system when used in conjunction with sheet applied or liquid applied external tanking membrane.
- Protection of the structure from aggressive chemicals in the ground water
- To prevent the build-up of ground water to retaining walls

Features

- Recycled and recyclable HDPE core
- Prevents water pressure from bearing against the structure
- Resistant to all chemicals normally found in the ground
- Withstands stresses and movement acting as a slip membrane as the backfill settles
- Very high compressive strength
- ECO manufactured with no production waste
- Suspended soil particles (fines) are filtered out by the geotextile layer
- Quick and easy to install with a range of ancillary fixing and installation products

TECHNICAL INFORMATION

Appearance	Sheet Membrane
Material	Recycled HDPE
Colour	Black
Thickness	8.5 mm
Vertcal water flow	2.29 l/m^2/s
Compressive strength	>190kN/m^2
Crack bridging	2.0 mm
Service temperature	-40°C / +80°C

NEW-BUILD WATERPROOFING DESIGN

- Use Durotech Waterstop at construction joints as part of an effective multi-staged approach to the waterproofing.
- Carry out a geotechnical survey to evaluate soil characteristics and groundwater conditions. Great care should be taken when considering waterproofing that requires the permanent removal of the ground water to be effective.
- Slotted or perforated drainage pipes should be maintainable.
- Include accessible jetting ports at regular intervals with at least one jetting port to each elevation.

SINCE 1977

INSTALLATION PROCEDURE

- Duro Drainage Cell is supplied in 1.1m wide sheets. If the foundation wall is less than 1.1m in height it is possible to fix Duro Drainage Cell horizontally with no laps. For walls over 1.1m fix Duro Drainage Cell in vertical sheets with the Geotextile fabric layer facing the operative and the black drainage layer against the wall being treated. Ensure that the membrane is fitted level.

- Overlap subsequent sheets of Duro Drainage Cell ensuring that the filter fabric of the next sheet overlaps the previous studded core - a section of filter fabric is separated from the drainage core for this purpose.

- Place slotted or perforated drainage pipe to the base of the foundation so that the top of the drain is below the top of the internal slab level. Place the drain within a bed of clean graded 20mm stone surrounded by a sheet of Geotextile filter fabric ensuring that enough Geotextile is available to lap to the Duro Drainage Cell to give continuity of the filter fabric.

- Ensure the slotted or perforated drainage pipe drains freely to a safe collection point. If gravity drainage is to be used ensure that the drainage terminates below the level of the internal slab so that drainage surcharge cannot prevent the removal of water from the system.

- Carefully place the filter fabric to the face of the Duro Drainage Cell so that it is held in place by the back fill.

- Use Durotech Pressure Seal to the top edge of the membrane to prevent debris and back-fill from entering the cavity between the drainage core and the filter fabric.

- Carefully backfill the excavation. If graded stone is used, a protection board is not required but the stone should be placed in controlled layers of no more than 600mm to prevent slump to the membrane. If the removed soil is re-used, ensure that it does not contain sharp stones and ensure that the soil is compacted every 600mm. If sharp stones exist within the re-used soil a protection board will be required.

LIMITATIONS

Do not use Duro Drainage Cell:

- As a primary waterproofing membrane.
- To de-water permanently high water levels.
- As stand-alone product if water or damp and vapour control is required by the specification.

Packaging

Duro Drainage Cell is available in 1.1 x 12.5m rolls.

Coverage

Total coverage is 15.25m^2 per roll.

Shelf Life

Duro Drainage Cell should be stored away from direct sunlight. Rolls should be stored in the upright position.

Durotech Industries Pty Ltd

Address	14 Essex Street, P.O Box 5092, Minto, NSW 2566
Phone	+61 2 9603 1177
Fax	+61 2 9475 5059
Email	sales@durotechindustries.com.au
Web	www.durotechindustries.com.au



"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses."

JAS-ANZ ©

ISO 9001 Quality Certified System IQNet
ISO 14001 Environment Certified System IQNet
ISO 45001 Health and Safety Certified System IQNet