PRODUCT DATA SHEET

# DUROBOND A935

DUROTECH
Engineered Construction Chemicals
Made In Australia For Over 45 Years

## Description

Durobond A935 contact adhesive is a fast curing formula with an excellent high coverage rate. Durobond A935 contact adhesives 50% of the final strength immediately, with full strength achieved in 24 hours. It has a good moisture and weather resistance against high temperature exposure.

## Usage

Double sided application to both substrate and PVC membrane surfaces to bond DuroPVC membrane directly to substrate.

## Application

Roller apply directly over PVC membrane and substrate. Apply evenly over both surfaces and push together to bond into place.

WARNING:- Avoid direct flame or exposure to excessive heat. Do not store at temperatures over 30°C.

## Physical Properties

| | |
|---|---|
| **Solids:** | 60% - 90% |
| **Appearance** | Red |
| **Environmental** | Dichloromethane |
| **Shelf Life** | 12 Months |
| **Sizes** | 20 Litre |
| **Coverage** | 10m$^2$ approximately (depending on application and substrate) |
| **Open Time** | 10 minutes at 20°C |
| **Temperature Resistance** | -30 - 100°C |
| **Application Temperature** | 5 - 30°C |



*"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses."*

JAS-ANZ

ISO 9001 Quality Certified System
ISO 14001 Environment Certified System
ISO 45001 Health and Safety Certified System