PRODUCT DATA SHEET

DUROINJECT HYDROPHILIC

MDI based Water Stop Grout

DUROTECH
Engineered Construction Chemicals
Made In Australia For Over 45 Years

DESCRIPTION

Duroinject hydrophilic is a moisture curing prepolymer based on diphenylmethane diisocyanate (MDI). The polymer backbone has been specially formulated to provide excellent water compatibility and retention properties. The polymer will react on contact with water to form a flexible closed cell polyurethane seal.

TYPICAL LIQUID PROPERTIES

Appearance	Brown coloured liquid
Specific Gravity	1.1
Viscosity, mPaS (21°C)	400-700
Isocyanate (NCO) Value: % by wt. NCO groups (group wt = 42)	6.7%
Expansion Properties	700-800%

TYPICAL REACTION DATA (21°C)

After Mixing 1:1 Water

Cream Time:	30 seconds
Gel Time:	2 minutes
Tack free time:	3 minutes

STORAGE AND HANDLING PRECAUTIONS

Containers of Duroinject hydrophilic should be kept properly closed and stored indoors in a well-ventilated area under normal factory conditions. Storage at room temperature (20-25°C) also provides a convenient viscosity for handling. Storage at low temperatures (below 15 C) is not recommended because it may lead to some crystallisation. If crystallisation does occur, meltout at 70-80C will be necessary. Storage at temperatures above 50C is not recommended since this can lead to the formation of insoluble solids, and also increases the rate of viscosity increase on extended storage. During handling Duroinject hydrophilic must be protected from water ingress and atmospheric moisture. Isocyanates react with water to form insoluble urea's and carbon dioxide gas which can result in pressure buildup in closed containers. Containers must be resealed immediately after each sampling. Containers used for Duroinject hydrophilic must be absolutely dry. Under the recommended storage conditions, and in properly sealed containers Duroinject hydrophilic has a storage life of 12 months.

Durotech Industries Pty Ltd

Address	14 Essex Street, P.O Box 5092, Minto, NSW 2566
Phone	+61 2 9603 1177
Fax	+61 2 9475 5059
Email	sales@durotechindustries.com.au
Web	www.durotechindustries.com.au

DUROTECH INDUSTRIES

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses."

JAS-ANZ

ISO 9001 Quality Certified System
ISO 14001 Environment Certified System
ISO 45001 Health and Safety Certified System