PRODUCT DATA SHEET

DUROPRIME ASBESTOS SEAL

WATERBORNE PENETRATING TREATMENT FOR ASBESTOS CEMENT SHEETING.

DUROTECH
Engineered Construction Chemicals
Made In Australia For Over 45 Years

DESCRIPTION

Duroprime Asbestos Seal is a waterborne penetrating treatment for weathered asbestos cement sheeting that soaks through lichen and degraded asbestos down to sound base material, binding these unstable element. When used together with Dutotech topcoat, the product forms part of the Durotech system, a proven encapsulation system used throughout Australia since 1990.

FEATURES

- Binds weathered asbestos cement sheet fibres.

AREA OF USE

- Weathered asbestos cement product.

SUBSTRATES

- Weathered asbestos cement product.

TYPICAL PHYSICAL PROPERTIES

Technical Data (@25°C)	1-2
Coverage (per coat)	3m²/L
Wet Film (per coat)	330 microns
Recoat	2 hours
Full cure	7days
Colour	Clear
Clean up	Water
Shelf life	12 months

SUBSTRATE PREPARATION AND PRIMING

Prior to commencing any work ensure all requirements applicable to the relevant state Occupational Health and Safety legislation are complied with.

- Remove large lumps of lichen and moss growth manually and clean loose growth away with an approved industrial vacuum cleaner.
- Assess the degree of weathering of the asbestos fibres by applying a length of self-adhesive tape to the surface. Adhere completely and then pull off in one swift motion. This is used as a basis to determine the amount of Durotech Primer required.

APPLICATION CONDITIONS

- Substrate must be dry. The use of suitable moisture meter is recommended.
- Application temperature between 7°C – 35°C.
- Do not apply if relative humidity is above 85% during initial cure phases, or if rain is expected before cure

Note: In humid conditions, air flow should be maximised with the use of fans to assist cure.

SINCE 1977

APPLICATION

- Apply Durotech primer with low pressure spray.
- Apply one coat of Durotech primer, as per recommended coverage rates.
- Assess the complete binding of the asbestos fibres by Durotech Primer using a self-adhesive tape pull off test'. If fibres appear of the adhesive surface apply a second coar. Reassess

CLEAN UP

- Wash all equipment in warm water and a small amount of detergent immediately after use.

PRECAUTIONS

- Ensure all requirements applicable to the relevant state Occupational Health and Safety legislation are complies with.
- When working on weathered asbestos roofs, refer to NOHSC Codes of practice 2018(2005) Management and Control of Asbestos in Workplaces.

TRANSPORT AND STORAGE

Size: 15L

DG Class: N/A

UN Number: N/A

Poisons Schedule: 5

Weight: 17kg

Flash Point: N/A

Cool and dry storage.

SAFETY

- Ensure good ventilation and avoid breathing vapours.
- Avoid skin and eye contact. Wear gloves and eye protection. Remove splashes on skin immediately and remove contaminated clothing.
- Keep out of reach of children.
- Keep container sealed when not in use.
- Do not swallow.

PRECAUTIONS

- If poisoning occurs, contact a doctor or poisons information centre.
- If swallowed, do not induce vomiting. Give a glass of water to drink.
- If in eyes, hold eyes open and flood with water for at least 15 minutes.
- If not breathing, apply artificial respiration.

Durotech Industries Pty Ltd

Address	14 Essex Street, P.O Box 5092, Minto, NSW 2566
Phone	+61 2 9603 1177
Fax	+61 2 9475 5059
Email	sales@durotechindustries.com.au
Web	www.durotechindustries.com.au

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses."

JAS-ANZ

ISO 9001 Quality Certified System IKVOA

ISO 14001 Environment Certified System IKVOA

ISO 45001 Health and Safety Certified System IKVOA