PRODUCT DATA SHEET

DUROPPRIME SUPER MC

MINERAL/CONCRETE PRIMER

DUROTECH
Engineered Construction Chemicals
Made In Australia For Over 45 Years

DESCRIPTION

Duroprime Super MC is a water based, ready-to-use silicate/acrylic primer which is highly versatile for priming, stabilising, consolidating and sealing porous and dense mineral substrates like masonry, concrete, screeds, lime and cement renders, bricks and stone surfaces prior to painting with water-based coatings and membranes. It penetrates and binds mineral and cementitious substrates by chemical reaction called "Silification" to produce uniform inseparable bonding with the mineral substrate.

can be applied by brush, roller or low-pressure spray.

FEATURES

- Single component which easily spreads and quick drying
- Helps stop efflorescence
- Binds and consolidate friable cementitious substrate
- Enhances adhesion and bond of the waterproofing membranes to the mineral substrate
- Good wetting and adhesion properties
- Non-flammable
- Reduces substrate porosity through crystalline technology
- Increases strength within cementitious substrates

USE AREA

- As a primer on concrete roof tiles, concrete, fibro, and other mineral/cementitious surfaces prior to the application of membrane products for exterior and interior applications.
- Stabilize and consolidate aged and dusty concrete surfaces
- Encapsulation of asbestos cement sheeting/ asbestos containing substrates

TYPICAL PHYSICAL PROPERTIES

Appearance	Milky white, water-thin
Odour	mild_
Solids Content , wt %	25%
Density	1.05 kg/L
Tack Free Time (@ 25°C)	10 minutes
Recoat time	45 mins
VOC (calculated)	34 g/L

LIMITATIONS

- Not to be used as a primer for solvent-based products
- Repriming may be required if left more than 72 hours or if the area has been introduced to site contaminates that would interfere with proper adhesion.
- Not suitable to prime, metals, wood materials (MDF, OSB), plastics and non-adhesive, plastic-elastic old paints.
- Not suitable for use or as waterproofing membrane / coating.

PACKAGING

Available in a 4L tin, 20L pail or 200L drum

COLOURS

When wet: milky white

When dry: transparent clear

SINCE 1977

PRODUCT INFORMATION

Coverage rate will depend on the porosity of the substrate.

Approximately 13m2/L at 75 um wft

SHELF LIFE

Approximately 12 months in unopened containers stored in a cool, dry place.

SURFACE PREPARATION

- Surfaces must be clean, smooth, dry and free from laitance, grease, oil, wax or any loose contaminating material.
- 4 Moisture Meter. Additional concrete testing maybe be required depending on concrete construction and job site location.
- Sand & cement screeds and polymer modified renders must have cured for a minimum 7 days.

MIX PREPARATION

Mix Process
Ready -to-use

APPLICATION

- Apply primer according to the recommended coverage rate with paintbrush or roller or spray. Allow the primer to dry for a minimum of 45 minutes and a maximum of 2 hours, at temperatures of 25°C and above; the primer must be touch dry. Longer drying times will be required at lower temperatures. Priming should only be carried out on surfaces which will be covered with membrane on the same day.
- Drying times will vary depending on humidity, surface temperature and porosity of substrates.

CLEAN-UP & RETURN TO SERVICE

Water can be used to clean up excess product, spills and tools while product is wet. When fully cured, tools and spills can be only removed mechanically or by solvent.

HEALTH & SAFETY PRECAUTIONS

- Duroprime Super MC is a non-hazardous and non-dangerous product.
- The Safety Data Sheet (SDS) must be read and understood prior to use.

Durotech Industries Pty Ltd

Address	14 Essex Street, P.O Box 5092, Minto, NSW 2566
Phone	+61 2 9603 1177
Fax	+61 2 9475 5059
Email	sales@durotechindustries.com.au
Web	www.durotechindustries.com.au

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses."

JAS-ANZ

ISO 9001 Quality Certified System IQNet
ISO 14001 Environment Certified System IQNet
ISO 45001 Health and Safety Certified System IQNet