DUROTECH

Duroproof PU Primer LVS

One component, polyurethane based primer material. Contains solvent. Mainly used before polyurethane based materials's applications. Duroproof PU Primer LVS used for increasing corrosion resistance of mineral based surfaces. Give high adhere power before the application of polyurethane coatings.

FEATURES

- Easy application
- Low cost
- Perfect adhesion to minerals and concrete surfaces.
- Solvent
- Transparent
- High resistance to all weather conditions (-30ºC /+120ºC)
- Decraese the water absorb of the concrete.
- Get harden of the concrete surface
- Support two grade protection
- Water resistance

USE AREA

- There is no need to any other components. It is ready to use in its package.
- Apply with roller or brush.
- Surface should protect from water, rain for 3-4 hours

TECHNICAL INFORMATION

Component	one (ready to use)
Base	Polyurethane
Application temperature	Above +5ºC
Water resistance	+
Corrosion resistance	+
Consumption	0,100 gr.- 0,200 gr/m²
Dry	3-8 hours
Package	4 kg galon, 15 kg drum

SURFACE

Careful surface preparation is essential for optimum finish and durability so application surface need to be dry, clean and hard. It should be cleaned out from dirt, oil, paint, dust. According to absorbent of the surface, application should done 2 layer. Dry time between layers is; 2-3 hours.

STORAGE

Pails should be stored in a dry and cool rooms for up to 9 months. Protect the material against moisture and direct sunlight. Production date is on label. Packages should be stored upward.

CAUTION

Do not apply in closed areas because of solvent scent .It is flammable so do not come closer with a flame. Do not smoke while application. Application should be done at open areas or air conditioned places. Use eye shield, glove and protector clothes. If it touches with skin wash with water and soap. Do not use the empty packages for the storage of nutriment.

The information and recommendations contained herein are based on the current state of our knowledge. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained here.

DUROTECH

14 Essex Street, P.O Box 5092, Minto, NSW 2566

+61 2 9603 1177 | +61 2 9475 5059 | 1300 791 177 | sales@durotechindustries.com.au

www.durotechindustries.com.au

The information provided in this data sheet is correct at the time of printing (albeit is subject to change at any time) and is intended to give a simple description of the product and its capabilities. In practice, the substrate, intended surface to be treated and environmental conditions vary widely, making it essential for the user to determine the products suitability for a particular application and to ensure that the product is not used beyond its physical limitations. If in doubt contact the manufacturer. The product will perform as described herein provided it is applied in accordance with the manufacturer's instructions as stated in this data sheet and provided that the building and installation is structurally sound and the application is carried out competently. Durotech terms and conditions of sale apply.