PRODUCT DATA SHEET

DUROMASTIC WAM 400 FR

High performance FIBRE reinforced flexible water based polyurethane Membrane

DUROTECH
Engineered Construction Chemicals
Made In Australia For Over 45 Years

DESCRIPTION

Duromastic WAM 400 FR is a polyurethane modified copolymer acrylic waterproofing membrane specifically formulated for bathrooms, laundries, balconies, terraces and other wet areas. Use Duromastic WAM 400 FR prior to installing mortar beds, render or tiling. The membrane forms a blue coloured water resistant elastomeric film with excellent durability.

FEATURES

- Water based. Non hazardous and non – flammable
- Highly durable – water, oxidation, UV and weather resistant
- Compatible with polymer modified tile adhesives
- Paintable with acrylic coatings
- Complies with the requirements of AS4858 Class III and AS3740
- Extends to over 600%
- Application by brush, or roller (10-12mm nap)
- Easy clean-up with water (while wet)

USE AREA

- Internal wet areas and shower recesses
- External balconies and Decks
- Tanking (Contact Durotech)
- Roofs – Topcoat with Duromastic AC (UV Coating) or Ac Non Slip or SR.
- Water Features

SURFACE

- Concrete and concrete blockwork
- Masonry, brick and sandstone
- Existing acrylic coatings
- Plasterboard
- Fibrous and asbestos cement sheeting
- Zincalume and galvanised iron

PACKAGING

- 15 Litre

SINCE 1977

APPLICATION

Coverage minimum recommended 1.0 Litre/m2 per coat, applied as 2 or more coats. This will give a recommended dry film thickness of 1.1mm total.

PREPARATION

Remove dirt, dust, loose particles, old adhesives and coatings, grime and unsound concrete. Where possible wash down oily, dirt contaminated, or powdery surfaces with dilute detergent, then rinse and dry thoroughly. Allow new concrete and render to fully cure cure. Ensure all sheeting and surfaces are dry, stable, sound and fully secured. Fix any rising damp problems beforehand. For timber floor surfaces use fibre cement sheeting as a replacement or cover. Remove or flatten all sharp concrete edges, mortar droppings, screw and nail heads. Prime wall and floor surfaces with Durotech Waterproofing Primer. Etch PVC fittings with plumbers PVC primer. For larger cracks, expansion joints, floor and pipe penetrations wall or hob junctions, seal neatly with neutral cure silicone sealant (smooth curved 12mm bead), and when cured apply membrane fabric reinforcement as explained below.

APPLICATION

Do not apply externally if rain is expected presently. Do not apply below 100C or above 300C externally. Ensure that the primer coat is completely dry. Apply evenly and check for missed areas and pin-holes. Apply further coats from cross directions after 4 to 6 hours. Do not apply as one coat. Apply down into drainage outlets. Use reinforcing fabric over expansion joints, cracks, all wall and floor junctions, and pipe penetrations. Apply this by first brushing out a layer of membrane (1-2 mm), next lay in the fabric and ensure there are no air bubbles, and the fabric is fully set in without wrinkles. Then brush over with more membrane. Good air flow and warmth will speed drying.

DRYING TIME

Allow 4 to 6 hours to dry. Flood test after 3 days. Tile or apply mortar bed after 3 to 4 days. Reputable polymer modified tile adhesives and renders are recommended.

CLEAN UP

Before drying, clean up with water. Scrape off when dry or use paint stripper for spot removal.

SHELF SIZE

12 months at 20°C in original unopened containers. Protect from freezing.

Durotech Industries Pty Ltd

Address	14 Essex Street, P.O Box 5092, Minto, NSW 2566
Phone	+61 2 9603 1177
Fax	+61 2 9475 5059
Email	sales@durotechindustries.com.au
Web	www.durotechindustries.com.au



This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses."

JAS-ANZ ©

ISO 9001 Quality Certified System IQNet
ISO 14001 Environment Certified System IQNet
ISO 45001 Health and Safety Certified System IQNet