PRODUCT DATA SHEET

WATERSTOP RX 101

HYDROPHILIC WATERSTOP

DUROTECH
Engineered Construction Chemicals
Made In Australia For Over 45 Years

DESCRIPTION

Waterstop RX101® is a sodium bentonite based waterstop designed to stop water infi ltration through cast-in-place concrete construction joints by expanding upon contact with water to form a positive seal against the concrete. The key to Waterstop RX101 effectiveness is its 75% sodium bentonite content, which provides superior expansion to seal and fi ll voids and cracks in the concrete. Waterstop RX101 is an active bentonite based waterstop that is designed to replace passive PVC/ Rubber waterbars, thereby eliminating the requirement of special pieces, split-forming and seam welding. Waterstop RX101 has been successfully tested by independent testing fi rms to over 70 m of hydrostatic water pressure, under both continuous immersion and wet/dry cycling. Waterstop RX101 is manufactured in lightweight, fl exible coils that are easily installed by a single worker. The product is applied to concrete, steel and PVC (Pipes) with Revofi x Mesh (preferred), and/or RX WB Adhesive. Coil ends are butted together – not overlapped –to form a continuous waterstop.

APPLICATIONS

Applications include both verticaland horizontal non-moving concrete construction joints, new to existing concrete construction, irregular surfaces, and around through-wall penetrations; such as plumbing and utility pipes. Waterstop RX101 works in both continuous hydrostatic and intermittent hydrostatic conditions.

Waterstop RX101 is designed for use in reinforced structural concrete, utilizing two rows of reinforcing steel, with a minimum thickness of 175 mm, providing the RX with no less than 75 mm concrete cover to all sides.

INSTALLATION

Surface Preparation

Construction joint surfaces should be clean and free of standing water. Loose/ fl aking concrete or laitence should be removed (scabbling, brushing, jet-washing etc.) Forming of rebates/chases is not required.

Installing Waterstop RX101 with Revofi x Mesh

After preparing concrete surface, uncoil Waterstop RX101 and leaving the release paper intact; apply exposed/black face against concrete, pushing fi rmly against release paper to force RX101 into concrete undulations. As work proceeds, remove release paper, and locate Revofi x Mesh sections over RX101, lapping the ends just. Nail through laps with fi xings supplied, and provide one additional fi xing in between i.e. fi xings at 300 mm c/c.

End-to-end or end-to-side junctions are created by simple butt joints. Ensure continuity is achieved through Revofi x Mesh, by pressing ends fi rmly together. Start at junctions; do not stretch Waterstop RX101 to fi t. Do not overlap the Waterstop Rx101.

INSTALLING RX101 WITH RX WB ADHESIVE

After preparing concrete surface, brush apply a thin, uniform strip, 25 mm wide, of WB Adhesive onto concrete, working well into undulations, and allow to cure to black (5-20 minutes depending on ambient temperatures). Recoat areas not receiving RX within 6 hours. Uncoil RX, and leaving the release paper intact, apply exposed/black face against concrete, pushing fi rmly against release paper to force RX into concrete undulations. Release paper can remain, as it provides some protection from rainfall, but MUST be removed prior to placing concrete.

SINCE 1977

Waterstop RX101 junctions are as for Installing RX101 with Revofi x Mesh'.

Waterstop RX101 may be installed as puddle fl anges' around cast-in through wall/slab penetrations, using the RX WB Adhesive and/or tie-wire to secure.

On irregular surfaces, make sure Waterstop RX101 remains in direct contact with the substrate along the entire installation on irregular surfaces e.g. old to new slab junctions. Bentoseal can be used to provide a 'bed' for Waterstop RX101, followed by application of Revofi x Mesh (which may require additional nailing to allow it to conform to the surface profile).



LIMITATIONS

Waterstop RX101 is not a self-adhesive product. Revofi x Mesh or WB Adhesive is required to secure Waterstop RX101 to concrete, metal or PVC (Pipes) surfaces.

Waterstop RX101 is not designed, norintended to function as an expansion joint sealant. Contact Manufacturer for precast concrete applications, technical information and approval.

Waterstop RX101 is designed for structural concrete. Waterstop RX101 requires a minimum of 75 mm of concrete cover to all sides. Waterstop RX101 should only be used in applications where the product is completely encapsulated within the concrete.

Waterstop RX101 should not be prehydrated by being subjected to submersion or remain in contact with water prior to concrete pour. If the product exhibits considerable swell prior to confi nement in the joint, it must be replaced with new material.

In conditions where severe ground water chemical contamination exists or is expected, consult manufacturer for compatibility information and approval.

PACKAGING

Waterstop RX101 is supplied in single 5m coils, 30m per box. Revofi x Mesh is supplied in 30 No 1m lengths, 30m per box. RX WB Adhesive is supplied in 3.8 litre tubs (suffi cient for 100 +m of RX application).

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attacchments and suggests that the recipient check this document and any attached files for the presence of viruses."

JAS-ANZ

ISO 9001 Quality Certified System

ISO 14001 Environment Certified System

ISO 45001 Health and Safety Certified System