14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

METHOD STATEMENT

INSTALLATION OF DUROMASTIC P-15 WATERPROOFING MEMBRANE

1.0 RELEVANT STANDARDS:

All waterproofing materials are to adhere to Australian Standard AS 4858: 2004
All materials are to be installed as per Australian Standard As 3740 : 2004.

2.0 MANUFACTURERS/SUPPLIERS

Durotech Australia 14 Essex St Minto NSW.

2.1 PRODUCTS

Duromix Hi Build WBE, Duromastic P-15 Polyurethane membrane, Duroseal 25 LM Sealant,

2.1.1 PRODUCTS DESCRIPTION

Duromix Hi Build WBE is a two-component water based epoxy primer

Duromastic P-15 is a single component water base polyurethane waterproofing membrane

Duroseal 25LM is a low modulus single part polyurethane joint sealant for the caulking of movement and control joints .

Durotech Industries
14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177 +61 2 9475 5059
1300 791 177 sales@durotechindustries.com.au
www.durotechindustries.com.au

"This email message, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to whom it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this email, or its attachments, by any party other than the intended recipient. If you have received this email in error please notify the sender and delete it from your system immediately. No employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries by email. The views or opinions presented in this email are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this email and any attachments and suggests that the recipient check this email and any attached files for the presence of viruses."

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

3.0 INSTALLATION OF POLYURETHANE MEMBRANE TO BATHROOM

The single component liquid applied polyurethane waterproof membrane is to be applied over the primed and prepared substrate to a minimum dry film thickness of 1.2 mm in 2 coats.

3.1 SUBSTRATE PREPARATION

GENERAL
All surfaces should be sound, dry and free from old membranes, dirt, dust, oil, grease, wax, tar, asphalt, mildew, mold, paint, foreign sealers, coatings, curing agents, loose particles, laitance or any other foreign matter that may impede with the bonding of the primer or membrane.

3.1.1 PRIMING

The substrate is to be primed using a suitable epoxy based primer at a rate specified by the manufacturer. NB note over coating times for epoxy primer
(See Technical Data Sheet)
Duromix Hi Build WBE

3.1.2 CAULKING

All vertical and horizontal joints, penetrations and drains in the substrate are to be caulked using a suitable polyurethane joint sealant acting as both sealant and bond breaker.
Duroseal 25LM

3.1.3 MEMBRANE APPLICATION

Two layers of liquid applied single component water based polyurethane membrane are to be applied to the primed substrate as per manufacturer's instructions.
Total dry film thickness is to be not less than 1.2mm (1200 microns)
Duromastic P-15.

"This email message, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to whom it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this email, or its attachments, by any party other than the intended recipient. If you have received this email in error please notify the sender and delete it from your system immediately. No employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries by email. The views or opinions presented in this email are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this email and any attachments and suggests that the recipient check this email and any attached files for the presence of viruses."

14 Essex Street, P.O Box 5092, Minto, NSW 2566
+61 2 9603 1177
+61 2 9475 5059
sales@durotechindustries.com.au
www.durotechindustries.com.au
ABN: 33 738 594 170

3.1.4 DETAILING

The membrane is to be detailed to all joints, perimeters, around any fixings and into drain heads. All details are to be to manufacturer recommendations.

3.1.5 CURING

Allow membrane to cure as per manufacturer recommendations prior to installing tiles.

"This email message, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to whom it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this email, or its attachments, by any party other than the intended recipient. If you have received this email in error please notify the sender and delete it from your system immediately. No employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries by email. The views or opinions presented in this email are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this email and any attachments and suggests that the recipient check this email and any attached files for the presence of viruses."
AUSTRALIAN Technology
SINCE 1977 Trialled • Tested • Approved