

## Different data types we will encounter in Python

- Numeric - Numeric variables take values which are numbers like 9, 3.14, 0, Inf
- String - String variables are used to store textual information
- Boolean - Boolean variables have two modes either True or False. A definite judge of statements!
- Datetime - These variables are used to store date and time values such as 2020-08-01 12:23:54

### ✓ Integers and Floats

#### ✓ Basic Arithmetic

```
# Addition  
2+1
```

```
↔ 3
```

```
# Subtraction  
2-5
```

```
↔ -3
```

```
# Multiplication  
2*2
```

```
↔ 4
```

```
# Division  
3/2
```

```
↔ 1.5
```

```
# Floor Division  
7//2
```

```
↔ 3
```

```
# Exponentiation  
2**5
```

```
↔ 32
```

```
# Modulus  
5%6
```

```
↔ 5
```

```
# Order of Operations followed in Python  
2 + 10 * 10 + 3
```

```
↔ 105
```

```
2+ 10* (10+3)
```

```
↔ 132
```

```
# Scientific Notation for representing large numbers  
4E6
```

```
↔ 4000000.0
```

## ✓ Let's talk about numbers!

- A lot many different types of numbers are supported in Python like integers (int type), real numbers (float type), complex numbers. We will mostly use integer and floating point numbers.
- Integers are just whole numbers, positive or negative. For example: 2 and -2 are examples of integers.
- Floating point numbers in Python are notable because they have a decimal point in them, or use an exponential (E) to define the number. For example 2.0 and -2.1 are examples of floating point numbers. 4E2 (4 times 10 to the power of 2) is also an example of a floating point number in Python.
- In computing, floating-point arithmetic is arithmetic using formulaic representation of real numbers as an approximation to support a trade-off between range and precision. You can always control the number of digits coming after the decimal, hence they are called floating-point numbers

The table below summarises the two numeric data types, Integers and Floats:

Examples	Number "Type"
1,2,-5,1000	Integers
1.2,-0.5,2e2,3E2	Floating-point numbers

## ✓ What is a Variable?

### ✓ VARIABLES are entities which help us store information and retrieve it later.

- A variable with a fixed name can store information of nature like numeric, textual, boolean etc.
- A Python variable is a reserved memory location to store values. In other words, a variable in a python program gives data to the computer for processing.
- The type of data contained in a variable can be changed at user's will.

```
# You can store numbers in variables.  
# The standard rule is you write the variable name followed by = sign and the value it will take
```

```
x=5
```

```
x
```

```
⇒ 5
```

```
y=6.4
```

```
y
```

```
⇒ 6.4
```

```
print(y)
```

```
⇒ 4
```

### ✓ Basic Arithmetic operations we can do on x and y. Later we will be doing operations on thousands of such numbers in one go!

```
# Addition
```

```
z = x+y
```

```
print(z)
```

```
⇒ 11
```

```
# Printing the memory address the variable z occupies
```

```
print(hex(id(z)))
```

```
⇒ 0x7fff2549a250
```

- ✓ A variable can be assigned different values and data types and it will store the last value assigned

```
# Subtraction
z = x-y
```

```
# Use the in-built print function to print the variable
print(z)
```

```
➡ -1.4000000000000004
```

```
# Printing the memory address the variable z occupies
print(hex(id(z)))
```

```
➡ 0x7fff2549a150
```

```
# Find out the data type of variable z
type(y)
```

```
➡ float
```

```
# Multiplication
z = x*y
```

```
print(z) # Print the variable z
type(z) # Get the data type of variable z
```

```
➡ 32.0
float
```

```
# Division
z = x/y
```

```
print(z) # Print the variable z
type(z) # Get the data type of variable z
```

```
➡ 0.78125
float
```

```
# Floor division
z= x//y # Remember x=5, y=6.4
print(z)
```

```
➡ 0.0
```

✓ Waittt! Shouldn't it be 0.75??

- The reason we get this result is because we are using "*floor*" division. The `//` operator (two forward slashes) is the mathematical equivalent of doing `[0.75]` which returns the greatest integer less than or equal to 0.75

```
# Modulo operator
y=5
x=3
```

```
z = y%x # Modulus is denoted by % sign
print(z)
```

```
➡ 2
```

```
# Using powers and exponents
```

```
z = x**y # We did not even need to store it in another variable nor use print command
print(z)
```

```
➡ 243
```

```
# BODMAS nostalgia
some_random_operation =(x+y)/y + (y-x)*x
```

```
print(some_random_operation)
type(some_random_operation)
```

```
7.6
float
```

```
# Storing large integer numbers
avogadro = 6.22E23
```

```
print(avogadro)
```

```
6.22e+23
```

## ✓ Rules for naming a variable in Python

- Variables names must start with a letter or an underscore like `_product` , `product_`
- The remainder of your variable name may consist of letters, numbers and underscores
- `spacy1`, `pyThon`, `machine_learning` are some valid variable names
- Names are case sensitive.
- `case_sensitive`, `CASE_SENSITIVE`, and `Case_Sensitive` are each a different variable.

```
1oNone = 4
```

```
File "<ipython-input-53-5af1d05f4ba0>", line 1
  1oNone = 4
    ^
SyntaxError: invalid syntax
```

```
onone_abc_1 = 5
```

```
list = 5
```

```
list
```

```
5
```

- Names cannot begin with a number. Python will throw an error when you try to do so
- Names can not contain spaces, use `_` instead
- Names can not contain any of these symbols:

```
: ' " , < > / ? | \ ! @ # % ^ & * ~ - +
```

- It is considered best practice that names are lowercase with underscores
- Avoid using Python built-in keywords like `list`, `str` , `def` etc. We will talk more about such conventions later on

## ✓ Boolean Variables

- A Boolean variable only takes two values either `True` or `False`. It is used for comparisons

## ✓ Comparison Operators


- These operators will allow us to compare variables and output a Boolean value (`True` or `False`).
- If you have any sort of background in Math, these operators should be very straight forward.
- First we'll present a table of the comparison operators and then work through some examples:
- In the table below, `a=3` and `b=4`.

Operator	Description	Example
----------	-------------	---------

==	If the values of two operands are equal, then the condition becomes true.	(a == b) is not true.
!=	If values of two operands are not equal, then condition becomes true.	(a != b) is true
>	If the value of left operand is greater than the value of right operand, then condition becomes true.	(a > b) is not true.
<	If the value of left operand is less than the value of right operand, then condition becomes true.	(a < b) is true.
>=	If the value of left operand is greater than or equal to the value of right operand, then condition becomes true.	(a >= b) is not true.
<=	If the value of left operand is less than or equal to the value of right operand, then condition becomes true.	(a <= b) is true.

- Python comes with Booleans (with predefined True and False displays that are basically just the integers 1 and 0). It also has a placeholder object called None. Let's walk through a few quick examples of Booleans (we will dive deeper into them later in this course).

```
# Set object to be a boolean
boolean_variable = False
type(boolean_variable)
```

 bool

```
#Show
boolean_variable
```


 False

## ✓ Equal

```
2 == 3
```

 False

```
2==0
```

 False

- Note that == is a comparison operator, while = is an assignment operator.

## ✓ Not equal

```
2!=0
```

 True

```
2!=2
```

 False

## ✓ Greater than

```
a=3
b=2
a> b
```

 True

```
a == 3
```

 True

```
b > 4
```


 False

## ✓ Less than

$10 < 45$

 True

$4 < 2$

 False

## ✓ Greater than or equal to

$3 \geq 2$

 True

$4 \geq 4$

 True

## ✓ Less than or equal to

$3 \leq 0$

 False

$1 \leq 2$

 True

Start coding or [generate](#) with AI.