

Coloring in Image Segmentation

Presented By

Deepak Dhingan, Roll No. 25524007

Department of IT, NIT Jalandhar

Contents

1. Introduction to Image Segmentation

2. Segmentation in Grey Scale Images

3. Why Coloring in Image Segmentation

4. Segmentation in HSI Color Space

5. Segmentation in RGB Color Space

6. Color Edge Detection Methods


7. Hyperspectral Image Segmentation

8. Summary

9. Applications

Introduction to Image Segmentation

Image segmentation plays a vital role in image processing. Image Segmentation is a process that partitions an image into regions or objects. We can extract meaningful interesting parts of image such as color, shape, structure.



INPUT IMAGE



IMAGE
SEGMENTATION



PARTS OF IMAGE

Main Segmentation Methods for Grayscale Images

In **grayscale images**, each pixel has only **one intensity value** instead of RGB channels. Black - 0, White - 255 and Intensity $I(x,y) = [0,255]$.

1. Thresholding: We choose a threshold value T and decides the dark and bright region. If intensity crosses the threshold then value 1 and region becomes bright otherwise darker region(for 0 value).


$$g(x,y) = \begin{cases} 1 & \text{if } I(x,y) > T \\ 0 & \text{if } I(x,y) \leq T \end{cases}$$



Main Segmentation Methods for Grayscale Images


2. Edge Based Segmentation: We detect **boundaries** where pixel intensity changes suddenly.

$$|\nabla I|$$



Main Segmentation Methods for Grayscale Images

3. Region Based Segmentation: Group pixels with similar intensity. Most of value near mean μ and difference below epsilon ϵ .



Why Coloring In Image Segmentation

Color provides additional information beyond grayscale intensity. Grayscale has only Intensity but color images have (R,G,B) or (H,S,V)

Why Use Color?

Grayscale loses chromatic information — a red apple and green apple may look identical in grey

Color adds extra dimensions that make regions easier to separate

Human perception naturally uses color to distinguish objects

Two primary color spaces are used: HSI and RGB

Different Coloring Approaches

- ***HSI Space*** — intuitive, uses Hue as primary channel. Works well but limited to one color variable.
- ***RGB Space*** — uses all three channels as a vector. More accurate segmentation results.
- ***Color Edge Detection***
- ***Hyperspectral Image Segmentation***

HSI Color Space

H

Hue

Describes the dominant color — measured as an angle (0° – 360° on the color wheel). Red $\approx 0^{\circ}$, Green $\approx 120^{\circ}$, Blue $\approx 240^{\circ}$. The primary channel for color-based segmentation.

S

Saturation

Indicates the purity/vividness of the color. Low S = washed-out/grey. High S = vivid color. Used as a masking image in segmentation — threshold at 10% of maximum value.

I

Intensity


Brightness of the pixel. Completely decoupled from color information. Rarely used for color segmentation because it tells us nothing about what color a region is.

Segmentation in HSI Color Space — Process


If we wish to segment based on color, it is natural to think first of the HSI space because color is conveniently represented in the hue image. (Gonzalez & Woods, Sec. 6.7)

- 1. Convert image to HSI** — Decompose the RGB image into Hue (H), Saturation (S), and Intensity (I) component images.
- 2. Threshold the Saturation image** — Any pixel with $S \geq 10\%$ of the maximum saturation value $\rightarrow$ mask = 1 (keep). Otherwise $\rightarrow$ mask = 0 (discard). This ignores grey/washed-out regions.
- 3. Compute $H \times \text{mask}$** — Multiply the Hue image by the binary mask. Now only colorful pixels retain their hue values. Grey areas are zeroed out.
- 4. Analyse the histogram** — Plot histogram of the product image. Pixels of the target color cluster at high values (near 1.0). This confirms the threshold to apply.
- 5. Threshold the product $\rightarrow$ binary output** — Apply threshold (e.g. 0.9). Pixels above threshold $\rightarrow$ white (target region found). Below $\rightarrow$ black. Final binary segmentation image.

Example 6.14 — Segmentation in HSI Space




(a) **Original** Full-color geological image. Target: reddish region in lower-left.




(c) **Saturation** Source for the binary mask in Step 2.

(d) **Intensity** Carries no color info — not used for segmentation.



(e) **Binary mask** $S \geq 10\% \rightarrow \text{white}=1$, else black=0.

(f) **H × mask** Hue values preserved only in colorful regions.



(g) **Histogram** Target pixels cluster near 1.0 — threshold at 0.9.

(h) **Result** Binary image showing segmented reddish components.

Segmentation in RGB Color Space

Although HSI is more intuitive, segmentation is one area in which better results are generally obtained by using RGB color vectors. (Gonzalez & Woods, Sec. 6.7)

Core Idea

Every pixel is a point in 3-D RGB space. Choose sample pixels from the target color region. Compute the mean color vector $\mathbf{a}$ (the "average target color"). Classify each image pixel by measuring its distance from $\mathbf{a}$. Pixels within a threshold distance D_0 are labelled as belonging to the target color.

Why does RGB outperform HSI here?

- HSI uses only one variable (Hue) $\rightarrow$ misses pixels that match in G and B but not exactly in H
- RGB uses all three channels simultaneously $\rightarrow$ the decision region in 3-D space is much more precise
- The standard deviation of each channel adapts the boundary to the actual color distribution of samples

Distance Measures in RGB Space

1. Euclidean Distance (Eq. 6-48)

$$D(z, a) = \|z - a\| = \sqrt{[(z_R - a_R)^2 + (z_G - a_G)^2 + (z_B - a_B)^2]}$$

Locus of points with $D \leq D_0$ is a sphere of radius D_0 in RGB space (Fig. 6.41a). Simple and fast. Treats all directions equally.

2. Mahalanobis Distance (Eq. 6-49)

$$D(z, a) = \sqrt{[(z - a)^T C^{-1} (z - a)]}$$


C is the 3×3 covariance matrix of the sample pixels. Locus is a 3-D ellipsoid (Fig. 6.41b) aligned with the data spread. When $C = I$, reduces to Euclidean. More accurate but computationally expensive.

3. Bounding Box (Practical — Fig. 6.41c)

Box centered at a with half-widths = $1.25 \times \sigma$ along each axis

Simplest to implement. Check if the pixel colour falls inside the box. Avoids all square root computations. Standard deviation of each colour channel sets the box size. Used in practical implementations.


RGB Enclosure Approaches — Fig. 6.41



*Fig. 6.41 Three approaches for enclosing data regions for RGB vector segmentation.
(a) Sphere — Euclidean distance. (b) Ellipsoid — Mahalanobis distance. (c) Bounding box — standard deviation.*

Key point: Points on the surface or inside the enclosure satisfy the specified colour criterion; points outside do not. Coding inside = white, outside = black produces a binary segmented image.

Example 6.15 — Segmentation in RGB Space (Fig. 6.42)



(a) Original — reddish region of interest shown enclosed in rectangle



(b) Binary result — RGB bounding-box segmentation

Result: RGB segmentation identifies reddish pixels far more accurately than HSI (compare with Fig. 6.40h), because three colour variables were used instead of just hue.

HSI vs. RGB — Comparison

Aspect	HSI Space	RGB Space
<i>Variables used</i>	1 — Hue only	3 — R, G, B simultaneously
<i>Saturation role</i>	Binary mask (10% threshold)	Std. dev. sets bounding box size
<i>Segmentation accuracy</i>	Moderate	Higher — consistently better
<i>Computational load</i>	Lower	Slightly higher
<i>Best suited for</i>	Quick colour detection	Precise colour segmentation

Color Edge Detection

The Problem

Edge detection using the gradient operator (Sec. 3.6) is not defined for vector quantities. Computing the gradient of individual component images (R, G, B separately) then combining them can yield erroneous results because it ignores the direction of change across channels.



FIGURE 6.43 (a)–(c) R, G, and B component images, and (d) resulting RGB color image. (e)–(g) R, G, and B component images, and (h) resulting RGB color image.

Why it fails — example

Image (a–d): R, G, B edges all point in the same direction → combined gradient is strong and correct.

Image (e–h): R and G edges point right, but B edge points up → different directions.

Problem: The composite gradient at the centre pixel is the same in both cases when computed channel-by-channel. We would expect image (d) to have a stronger edge than (h). The component approach fails to capture this — we need a vector gradient definition.

Di Zenzo's Vector Gradient Method

Let $\mathbf{r}$, $\mathbf{g}$, $\mathbf{b}$ be unit vectors along the R, G, B axes. Define gradient vectors $\mathbf{u}$ (x-direction) and $\mathbf{v}$ (y-direction):

$$\mathbf{u} = (\partial R / \partial x) \mathbf{r} + (\partial G / \partial x) \mathbf{g} + (\partial B / \partial x) \mathbf{b} \quad \text{Eq. 6-50}$$

$$\mathbf{v} = (\partial R / \partial y) \mathbf{r} + (\partial G / \partial y) \mathbf{g} + (\partial B / \partial y) \mathbf{b} \quad \text{Eq. 6-51}$$

From $\mathbf{u}$ and $\mathbf{v}$, define three scalar quantities using dot products:

$$\mathbf{g}_{xx} = \mathbf{u} \cdot \mathbf{u} = |\partial R / \partial x|^2 + |\partial G / \partial x|^2 + |\partial B / \partial x|^2 \quad \text{Eq. 6-52}$$

$$\mathbf{g}_{yy} = \mathbf{v} \cdot \mathbf{v} = |\partial R / \partial y|^2 + |\partial G / \partial y|^2 + |\partial B / \partial y|^2 \quad \text{Eq. 6-53}$$

$$\mathbf{g}_{xy} = \mathbf{u} \cdot \mathbf{v} = (\partial R / \partial x)(\partial R / \partial y) + (\partial G / \partial x)(\partial G / \partial y) + (\partial B / \partial x)(\partial B / \partial y) \quad \text{Eq. 6-54}$$

The Sobel operators from Section 3.6 can be used to compute the partial derivatives required.

Gradient Direction and Magnitude (Di Zenzo)

Direction of Maximum Rate of Change

$$\theta(x, y) = \frac{1}{2} \cdot \tan^{-1} \left[\frac{2g_{xy}}{g_{xx} - g_{yy}} \right]$$

Since $\tan(\alpha) = \tan(\alpha \pm \pi)$, if θ_0 is a solution, so is $\theta_0 \pm \pi/2$. Therefore F_θ is computed only for θ in the half-open interval $[0, \pi)$. This equation associates with each pixel (x, y) a pair of orthogonal directions.

Magnitude of Maximum Rate of Change

$$F_\theta(x, y) = \left\{ \frac{1}{2} \left[(g_{xx} + g_{yy}) + (g_{xx} - g_{yy}) \cos 2\theta + 2g_{xy} \sin 2\theta \right] \right\}^{\frac{1}{2}}$$

Along direction θ , F_θ is maximum. Along the orthogonal direction, F_θ is minimum. F_θ is always positive and monotonic — working with F_θ^2 avoids the square root computation.

Example 6.16 (result): The vector gradient image has more complete edge detail than the composite single-plane gradient. Fine details (e.g. around the eye) are better captured by the vector method.

Hyperspectral Image Segmentation

Beyond RGB — hyperspectral cameras capture hundreds of narrow spectral bands per pixel, giving a full spectral fingerprint unique to each material.

Key Concepts

— Each pixel = a spectral vector of 200+ values (wavelength ~400 nm to 2500 nm)

— Spectral signature is unique per material — enables discrimination invisible to RGB

— Same distance/Mahalanobis concepts extend to N-dimensional space

— Dimensionality reduction (PCA, LDA) needed to manage high-dimensional data

Applications

— Remote Sensing — land-use mapping, mineral detection from satellites

— Agriculture — crop disease detection, soil analysis using plant spectral signatures

— Medical Imaging — tissue differentiation and tumour boundary detection

— Defence — camouflage and anomaly detection that RGB cameras miss

Hyperspectral — Challenges and Methods

Challenge

Hughes Phenomenon (Curse of Dimensionality) — With hundreds of bands and limited training samples, classifier accuracy can actually decrease as bands are added.

Challenge

Mixed Pixels — A single pixel often contains multiple materials — pure spectral signatures are rare in practice.

Method

Spectral Angle Mapper (SAM) — Measures the angle between a pixel's spectrum and a reference spectrum. Illumination-independent and straightforward.


Method

PCA + Mahalanobis Segmentation — Reduce dimensionality with PCA to the top K components, then apply the same RGB-style distance-based segmentation in K-dimensional space.


Method

Deep Learning (CNN / Transformer) — Learns spatial-spectral features automatically. Current state-of-the-art for hyperspectral classification and segmentation.


Applications



Medical Imaging



Satellite Imaging



Face Detection

Summary

1.

Segmentation partitions an image into regions. Color adds extra discriminatory dimensions beyond grayscale.

2.

HSI segmentation uses Hue as primary channel with a Saturation binary mask. Intuitive but limited to one variable.

3.

RGB segmentation uses all three channels and distance measures (Euclidean, Mahalanobis, Bounding Box). Consistently more accurate.

4.

Color edge detection using Di Zenzo's vector gradient correctly captures edges across all color channels simultaneously, unlike the component-wise approach.

5.

Hyperspectral imaging extends these concepts to hundreds of spectral bands, enabling precision segmentation in remote sensing, agriculture, and medicine.

Thank You

Kindly Share Your Queries?