Status	Finished
Started	Wednesday, 21 October 2026, 3:29 PM
Completed	Wednesday, 21 October 2026, 3:33 PM
Duration	4 mins 16 secs
Grade	**11.00** out of 15.00 (**73.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following is a Python tuple?

a. ("Wonder")

b. (1,4,5,6,7) ✓

c. {1,3,8,9,41}

d. [1,2,3,4]

Question **2**

Incorrect

Mark 0.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. Computer

b. Error

c. (Computer) ✗

d. ()

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

a. Error

b. (1,2,3,4,5,6) ✓

c. (1,2,3)(4,5,6)

d. (1,2,3,3,2,1)

Question **4**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {1,3,2}

b. {4} ✓

c. {2}

d. {1,3,4}

Question **5**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. (1, 4, 8)

b. [1, 2, 4, 3, 8, 9]

c. [2, 3, 9]

d. [1, 4, 8] ✓

Question **6**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. True ✓

b. False

Question **7**

Incorrect

Mark 0.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, '10', 50, 20, 60, 30}

b. SynatxError: Different types cannot be used with sets

c. {40, 10, 50, 20, 60, 30} ✗

d. {40, 10, '10', 50, 20, 60, 30}

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

a. 2

b. 5

c. Error ✓

d. 1

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
True

b. False
False

c. True ✓
True

d. True
False

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

a. (12)

b. 12

c. Error ✓

d. (55,78,64,25)

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

b. TypeError: update() doesn't allow list as a argument.

c. Name Error

d. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

Question **12**

Incorrect

Mark 0.00 out of 1.00

Find the output of the given Python program?

```
t1 = (55, 44, 33, 22, 11)
x = [t1[i] for i in range(0, len(t1), 2)]
print(x)
```

a. [(55,33,11)] ✗

b. ([55,33,11])

c. [55, 33, 11]

d. (55,33,11)

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

b. (10, 20, 30, 40) (40, 50, 60, 70, 80)

c. (30, 40, 50)(40, 50, 60, 70, 80)

d. (30, 40, 50) (10, 20, 30, 40)

Question **14**

Incorrect

Mark 0.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['2', '3', '8', '30']

b. ['8', '30', '3', '2']

c. ['30', '8', '3', '2'] ✗

d. ['2', '3', '30', '8']

Question **15**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. (16,17,18)

b. (25,19,18,17)

c. Error

d. (16,17,18,19) ✓