

Springboot with RDS

29 July 2026 13:15

Create a springboot project
Include dependency spring jpa, spring web,mysql driver

Product.java

```
package com.SpringBootWithRDS.SpringRDS.entity;

import jakarta.persistence.Entity;
import jakarta.persistence.GeneratedValue;
import jakarta.persistence.GenerationType;
import jakarta.persistence.Id;

@Entity
public class Product {
    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    private Long id;
    private String name;
    private Double price;

    public Double getPrice() {
        return price;
    }

    public void setPrice(Double price) {
        this.price = price;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public Long getId() {
        return id;
    }

    public void setId(Long id) {
        this.id = id;
    }
}
```

ProductRepository.java

```
package com.SpringBootWithRDS.SpringRDS.repository;

import org.springframework.data.jpa.repository.JpaRepository;

import com.SpringBootWithRDS.SpringRDS.entity.Product;

public interface ProductRepository extends JpaRepository<Product, Long> {}
```

ProductController.java

```
package com.SpringBootWithRDS.SpringRDS.controller;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.*;

import com.SpringBootWithRDS.SpringRDS.entity.Product;
import com.SpringBootWithRDS.SpringRDS.repository.ProductRepository;

@RestController
public class ProductController {

    @Autowired
    private ProductRepository repo;

    @PostMapping("/product")
    public Product save(@RequestBody Product product) {
        return repo.save(product);
    }

    @GetMapping("/products")
    public List<Product> getAll() {
        return repo.findAll();
    }
}
```

application.properties

```
spring.application.name=SpringRDS

# JDBC URL for local MySQL (default port is 3306)
spring.datasource.url=jdbc:mysql://localhost:3306/localrds
spring.datasource.url=jdbc:mysql://database-1.circqggmoswa.us-east-1.rds.amazonaws.com/rdsdb

# MySQL credentials
spring.datasource.username=root
spring.datasource.password=root

#Mysql In AWS Rds
spring.datasource.username=admin
spring.datasource.password=rootadmin

# JPA & Hibernate configuration
spring.jpa.hibernate.ddl-auto=update
spring.jpa.show-sql=true
spring.jpa.database-platform=org.hibernate.dialect.MySQLDialect
server.port=7671
```

Go to AWS->RDS and Aurora
and create a mysql db and name it
create your own admin and password and save them in a notepad
enable public access and terms
go to cmd shell choose the proper mysql file path to run the commands

```
mysql -u root -p -> to check the local db created and the tables
Show database;
show tables;
Use database;
Select * from the table;
```

And then copy the end point code and paste it in the application.properties file

```
jdbc:mysql://<link-from-aws>/<db-name>
```

Then after successful entry-> create your own database and use it-> the product table will automatically display in the db which you have created!!!!

and the run it

At the end you may see the Summary section with CPU and Current Activity already in use and to access it you need to open your CMD-> and then run the code

```
mysql -h mydb.abcddefghijk.ap-south-1.rds.amazonaws.com -P 3306 -u admin -p
```

the enter the password from where you have named while creating an rds db on aws.

the above code basically defines the connection with the AWS rds with the springboot application, and can be also seen and tells you to copy the code to use it

Use Postman to check the localhost://<id>:XXXX to trigger the actions like POST/GET

The screenshot shows the AWS Management Console interface for an Amazon RDS database instance named 'database-1'. The 'Summary' tab is selected, displaying various instance details. The 'CPU' usage is shown as 4.11% with a progress bar, and the 'Current activity' is shown as 11 Connections, both of which are circled in red. Other details include the DB identifier 'database-1', Status 'Available', Class 'db.t4g.micro', Engine 'MySQL Community', and Region & AZ 'ap-south-1a'. The left sidebar shows the 'Aurora and RDS' navigation menu with options like Dashboard, Databases, Query editor, Performance insights, Snapshots, Exports in Amazon S3, Automated backups, Reserved instances, Proxies, Subnet groups, and Parameter groups. The top of the console shows the AWS logo, a search bar, and account information for 'Asia Pacific (Mumbai)' with Account ID '1371-3062-3544'.

The screenshot shows the AWS Management Console interface for the same Amazon RDS database instance 'database-1', but with the 'Connectivity & security' tab selected. This tab displays three main sections: 'Endpoint & port', 'Networking', and 'Security'. The 'Endpoint' section shows the endpoint 'database-1.c96aw.kikufpe.ap-south-1.rds.amazonaws.com' and the port '3306', with the endpoint text circled in red. The 'Networking' section shows the Availability Zone 'ap-south-1a', VPC 'vpc-01c5a81cd41b73e02', Subnet group 'default-vpc-01c5a81cd41b73e02', and Subnets 'subnet-'. The 'Security' section shows VPC security groups 'dbfirewall (sg-09d1cf93aafc98aa9)' with status 'Active', 'Publicly accessible' set to 'Yes', and 'Certificate authority' 'rds-ca-rsa2048-g1'. The left sidebar and top navigation bar are consistent with the previous screenshot.

```
Command Prompt - mysql -h x + v
Microsoft Windows [Version 10.0.22631.6199]
(c) Microsoft Corporation. All rights reserved.

C:\Users\deepa>mysql -h database-1.circqgmoswa.us-east-1.rds.amazonaws.com -P 3306 -u admin -p
'mysql' is not recognized as an internal or external command,
operable program or batch file.

C:\Users\deepa>where mysql
INFO: Could not find files for the given pattern(s).

C:\Users\deepa>cd "C:\Program Files\MySQL\MySQL Server 8.0\bin"

C:\Program Files\MySQL\MySQL Server 8.0\bin>mysql -h database-1.circqgmoswa.us-east-1.rds.amazonaws.com -P 3306 -u admin -p
Enter password: *****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 32
Server version: 8.4.9 Source distribution

Copyright (c) 2000, 2024, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> show databases;
-> ^C
mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| sys |
+-----+
4 rows in set (0.36 sec)

mysql> create database rdsdb;
Query OK, 1 row affected (0.30 sec)
```

```
Command Prompt - mysql -h x + v

| information_schema |
| mysql |
| performance_schema |
| sys |
+-----+
4 rows in set (0.36 sec)

mysql> create database rdsdb;
Query OK, 1 row affected (0.30 sec)

mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| rdsdb |
| sys |
+-----+
5 rows in set (0.31 sec)

mysql> use rdsdb;
Database changed
mysql> show tables;
+-----+
| Tables_in_rdsdb |
+-----+
| product |
+-----+
1 row in set (0.46 sec)

mysql> select * from product;
+-----+
| id | name | price |
+-----+
| 1 | Wrist bands | 10000 |
+-----+
1 row in set (0.28 sec)

mysql>
```

```
Command Prompt
4 rows in set (0.36 sec)

mysql> create database rdsdb;
Query OK, 1 row affected (0.30 sec)

mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| rdsdb |
| sys |
+-----+
5 rows in set (0.31 sec)

mysql> use rdsdb;
Database changed
mysql> show tables;
+-----+
| Tables_in_rdsdb |
+-----+
| product |
+-----+
1 row in set (0.46 sec)

mysql> select * from product;
+----+-----+-----+
| id | name      | price |
+----+-----+-----+
| 1  | Wrist bands | 10000 |
+----+-----+-----+
1 row in set (0.28 sec)

mysql> clear
mysql> clear
mysql> quit
Bye

C:\Program Files\MySQL\MySQL Server 8.0\bin>
```

31°C
Light rain



Search



ENG
IN



13:14
29-07-2026