



EE 604

Digital Image Processing

Lecture outline

- **Morphological image processing**
- Color fundamentals


Morphological image processing

- Morphology means shape, form and structure
- Modify, change, extract shapes and structures
- Processing is based on simple set-theoretic operations
- Primarily useful for binary images
- Often used for preprocessing or post-processing


Basic set operations

- A, B are sets in \mathbb{Z}^2
- An element in A : $a = (a_1, a_2)$
- Union: $A \cup B = \{w : w \in A \text{ or } w \in B\}$
- Intersection: $A \cap B = \{w : w \in A \text{ and } w \in B\}$
- Complement: $A^c = \{w : w \notin A\}$
- Difference: $A \setminus B = \{w : w \in A, w \notin B\}$


Basic set operations




Basic set operations




A




B




$C = A \cup B$



$C = A \cap B$



$C = A^c$



$C = A \setminus B$


Basic set operations

- Reflection:

$$\hat{B} = \{w : w = -b, b \in B\}$$


- Translation:

$$(A)_z = \{c : c = a + z, a \in A\}$$



Morphological processing

- Operations are defined in terms an image (set A) and a structuring element (set B).
- B can designed to have any shape and size. Often, symmetric in practice.
- Think of B as small mask that is translated over the entire image set A .





Dilation

- Dilation of A by B

$$A \oplus B = \left\{ z \left| \left(\hat{B} \right)_z \cap A \neq \emptyset \right. \right\}$$

A




B

Dilation

- Dilation of A by B


$$A \oplus B = \left\{ z \left| \left(\hat{B} \right)_z \cap A \neq \emptyset \right. \right\}$$



Dilation

- Dilation of A by B


$$A \oplus B = \left\{ z \left| \left(\hat{B} \right)_z \cap A \neq \emptyset \right. \right\}$$



Dilation

- Dilation of A by B


$$A \oplus B = \left\{ z \left| \left(\hat{B} \right)_z \cap A \neq \emptyset \right. \right\}$$



Dilation

- Dilation of A by B

$$A \oplus B = \left\{ z \left| \left(\hat{B} \right)_z \cap A \neq \emptyset \right. \right\}$$



Dilation

- Dilation of A by B

$$A \oplus B = \left\{ z \left| \left(\hat{B} \right)_z \cap A \neq \emptyset \right. \right\}$$



Dilation

Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.



Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.




0	1	0
1	1	1
0	1	0

Erosion

- Erosion of A by B


$$A \ominus B = \{z | (B)_z \subseteq A\}$$



Erosion

- Erosion of A by B


$$A \ominus B = \{z | (B)_z \subseteq A\}$$



Erosion

- Erosion of A by B


$$A \ominus B = \{z | (B)_z \subseteq A\}$$



Erosion

- Erosion of A by B


$$A \ominus B = \{z | (B)_z \subseteq A\}$$



Erosion

- Erosion of A by B


$$A \ominus B = \{z | (B)_z \subseteq A\}$$



Erosion



- Erosion of A by B

$$A \ominus B = \{z | (B)_z \subseteq A\}$$



Erosion





- Results can vary significantly depending on the shape of the structuring element



Opening

- Opening of A by B






$$A \circ B = (A \ominus B) \oplus B$$



Closing

- Closing of A by B

$$A \cdot B = (A \oplus B) \ominus B$$



Opening and Closing

- Opening:
 - smoothes contours, breaks narrow segments in between shapes, removes sharp peaks
- Closing:
 - smoothes contours, fuses narrow breaks, closes holes

Duality relation


- Dilation and Erosion are dual operations

$$(A \ominus B)^c = A^c \oplus \hat{B}$$

- Opening and Closing are dual operations


$$(A \bullet B)^c = A^c \circ \hat{B}$$

Processing pipeline




Boundary extraction


$$\beta(A) = A - (A \ominus B)$$




A



B




$A \ominus B$



$\beta(A)$

Region filling

$$X_k = (X_{k-1} \oplus B) \cap A^c$$




Skeletonization

$$S(A) = \bigcup_{k=0}^K S_k(A)$$

$$S_k(A) = (A \ominus kB) - (A \ominus kB) \circ B$$

$$K = \max\{k | (A \ominus kB) \neq \emptyset\}$$



$k \backslash$	$A \ominus kB$	$(A \ominus kB) \circ B$	$S_k(A)$	$\bigcup_{k=0}^K S_k(A)$
0				
1				
2				



Lecture outline

- Wiener filter
- Morphological image processing
- **Color fundamentals**

Why consider color?

- Color is a powerful descriptor for various tasks
 - tracking, segmentation, object detection and recognition
- Humans can distinguish **thousands** of color shades
 - as compared to only two dozens shades of gray

Color spectrum




Color characterization

- **Achromatic light**
 - colorless light (intensity)
- **Chromatic light**
 - **Radiance:** amount of energy that flow from the light source (watts)
 - **Luminance:** amount of energy an observer perceives from a light source, (lumens) e.g. Far infrared light: high radiance, but 0 luminance



Color perception

- The color of an object depends on the wavelength of the light reflected by it
- 6 - 7M cones => color sensors in our eyes



Primary and secondary colors

- Following the absorption trend in human eyes, colors are seen as a combination of the primary colors
 - Primary colors: Red (R), Green (G), Blue (B)
 - Secondary colors: Cyan (G+B), Yellow (R+G), Magenta (R+B)




Distinguishability of colors

- **Brightness:** Intensity
- **Hue:** Indicates the dominant wavelength in a mixture of light
- **Saturation:** Purity of the dominant wavelength

Color models/spaces

- Why do we need color models?
- **RGB** color space
- 24-bit color image




Color models/spaces

- CMY color space
- 1 = white
- Sometimes Black is added => CMYK
- Used in printing

$$\begin{bmatrix} C \\ M \\ Y \end{bmatrix} = \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix} - \begin{bmatrix} R \\ G \\ B \end{bmatrix}$$

Color models/spaces

- HSI color space
- Matches human description



RGB to HSI

$$H = \begin{cases} \theta & \text{if } B \leq G \\ 360 - \theta & \text{if } B > G \end{cases}$$

$$\theta = \cos^{-1} \left\{ \frac{\frac{1}{2}[(R-G) + (R-B)]}{\left[(R-G)^2 + (R-B)(G-B) \right]^{1/2}} \right\}$$

$$S = 1 - \frac{3}{(R+G+B)} [\min(R, G, B)]$$

$$I = \frac{1}{3}(R+G+B)$$

It is assumed that the RGB values have been normalized to the range [0,1]

Color image processing

- Most grayscale methods we studied extend to color images in a straight-forward manner
- Two main approaches of color image processing
 - treat pixel value as a vector [R G B]
 - process each channel as a grayscale image