

Lab Session 5

1. Write a MATLAB function program $[Q, R] = \text{cgs}(V)$ to orthonormalize the columns of an $n \times m$ matrix V , ($n \geq m$) by the Classical Gram Schmidt procedure so that Q is the isometry satisfying

$$\begin{aligned} \text{span}\{Q(:, 1)\} &= \text{span}\{V(:, 1)\} \\ \text{span}\{Q(:, 1), Q(:, 2)\} &= \text{span}\{V(:, 1), V(:, 2)\}, \\ &\vdots \\ \text{span}\{Q(:, 1), Q(:, 2), \dots, Q(:, m)\} &= \text{span}\{V(:, 1), V(:, 2), \dots, V(:, m)\} \end{aligned}$$

and R is an upper triangular matrix such that $R(i, j) = \langle V(:, j), Q(:, i) \rangle$.

2. A slight modification of the above program leads to the Modified Gram Schmidt procedure for orthonormalizing the columns of V . Perform this modification to obtain another function program $[Q, R] = \text{mgs}(V)$.
3. Write a function program $[Q, R] = \text{cgsrep}(V)$ that performs Classified Gram Schmidt with reorthogonalization by making appropriate changes to your function program cgs .
Take care to replace *for loops* by matrix-vector multiplications as far as possible in each of the above programs.
4. The purpose of this exercise is to solve the Least-Squares Problem (in short, LSP) $Ax = b$ by different methods and compare the solutions. Here $A \in \mathbb{R}^{n \times m}$ and $b \in \mathbb{R}^n$, and usually n is much bigger than m .

Origin: Suppose that we have a data set (t_i, b_i) , for $i = 1 : m$, that have been obtained from some experiment. These data are governed by some unknown laws. So, the task is to come up with a model that best fits these data. A model is generated by a few functions, called model functions, ϕ_1, \dots, ϕ_n . Therefore once a model is chosen, the task is to find a function p from the span of the model functions that best fits the data.

Suppose that the model functions ϕ_1, \dots, ϕ_n are given. For $p \in \text{span}(\phi_1, \dots, \phi_n)$, we have $p = x_1\phi_1 + \dots + x_n\phi_n$ for some $x_j \in \mathbb{R}$. Now, forcing p to pass through the data (t_i, b_i) for $i = 1 : m$, we have $p(t_i) = b_i + r_i$, where r_i is the error. We want to choose that p for which the sum of the squares of the errors r_i is the smallest, that is, $\sum_{i=1}^m |r_i|^2$ is minimized.

Now $p(t_i) = b_i + r_i$ gives $x_1\phi_1(t_i) + \dots + x_n\phi_n(t_i) = b_i + r_i$. Thus in matrix notation,

$$\begin{bmatrix} \phi_1(t_1) & \cdots & \phi_n(t_1) \\ \phi_1(t_2) & \cdots & \phi_n(t_2) \\ \vdots & \cdots & \vdots \\ \phi_1(t_m) & \cdots & \phi_n(t_m) \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} = \begin{bmatrix} b_1 \\ b_2 \\ \vdots \\ b_m \end{bmatrix} + \begin{bmatrix} r_1 \\ r_2 \\ \vdots \\ r_m \end{bmatrix}.$$

This is of the form $Ax = b + r$ and we have to choose $x \in \mathbb{R}^n$ for which the 2-norm of the residual vector $\|r\|_2$, is minimized. We write this as LSP $Ax = b$.

Your task is to find the polynomial of degree 19 that best fits the function $f(t) = \sin(\frac{\pi}{5}t) + \frac{t}{5}$ for $t_1 = -5, t_2 = -4.5, \dots, t_{23} = 6$. Set up the LSP $Ax = b$ and determine the polynomial p whose coefficients are determined by x in three different ways:

- (a) By using the Matlab command

```
>> A \ b
```

This uses QR factorization to solve the LSP $Ax = b$. Call this polynomial p_1 .

- (b) By setting up the normal equation $A^T Ax = A^T b$ and solving them for x . You will need to use the Cholesky method for this. Call this polynomial p_2 .

- (c) By solving the augmented system $\begin{bmatrix} I_n & A \\ A^T & 0 \end{bmatrix} \begin{bmatrix} -r \\ x \end{bmatrix} = \begin{bmatrix} b \\ 0 \end{bmatrix}$. Call this polynomial p_3 .

Set the formatting to **format long e** and compute the condition number of the coefficient matrix associated with each of the systems that you are solving. Which one is the most ill conditioned?

Compute the $\|r\|_2$ which gives the value of $\sqrt{\sum_{i=1}^{23} |p_j(t_i) - f(t_i)|^2}$ $j = 1, 2, 3$ for each of these methods (again in **format long e**). This is a measure of the goodness of the fit in each case. Which of the methods provide the best fit?