

How to create thread

There are two ways to create a thread:

1. By extending Thread class
 2. By implementing Runnable interface.
-

Thread class:

Thread class provide constructors and methods to create and perform operations on a thread. Thread class extends Object class and implements Runnable interface.

Commonly used Constructors of Thread class:

- Thread()
- Thread(String name)
- Thread(Runnable r)
- Thread(Runnable r,String name)

Commonly used methods of Thread class:

1. **public void run():** is used to perform action for a thread.
2. **public void start():** starts the execution of the thread. JVM calls the run() method on the thread.
3. **public void sleep(long milliseconds):** Causes the currently executing thread to sleep (temporarily cease execution) for the specified number of milliseconds.
4. **public void join():** waits for a thread to die.
5. **public void join(long milliseconds):** waits for a thread to die for the specified milliseconds.
6. **public int getPriority():** returns the priority of the thread.
7. **public int setPriority(int priority):** changes the priority of the thread.
8. **public String getName():** returns the name of the thread.
9. **public void setName(String name):** changes the name of the thread.
10. **public Thread currentThread():** returns the reference of currently executing thread.
11. **public int getId():** returns the id of the thread.
12. **public Thread.State getState():** returns the state of the thread.
13. **public boolean isAlive():** tests if the thread is alive.

14. **public void yield():** causes the currently executing thread object to temporarily pause and allow threads to execute.
15. **public void suspend():** is used to suspend the thread(deprecated).
16. **public void resume():** is used to resume the suspended thread(deprecated).
17. **public void stop():** is used to stop the thread(deprecated).
18. **public boolean isDaemon():** tests if the thread is a daemon thread.
19. **public void setDaemon(boolean b):** marks the thread as daemon or user thread.
20. **public void interrupt():** interrupts the thread.
21. **public boolean isInterrupted():** tests if the thread has been interrupted.
22. **public static boolean interrupted():** tests if the current thread has been interrupted.

Runnable interface:

The Runnable interface should be implemented by any class whose instances are intended to be executed by a thread. Runnable interface has only one method named run().

1. **public void run():** is used to perform action for a thread.

Starting a thread:

start() method of Thread class is used to start a newly created thread. It performs following tasks.

- A new thread starts(with new callstack).
- The thread moves from New state to the Runnable state.
- When the thread gets a chance to execute, its target run() method will run.

1) Java Thread Example by extending Thread class

```
class Multi extends Thread {  
    public void run() {  
        System.out.println("thread is running...");  
    }  
    public static void main(String args[]){  
  
        Multi t1 = new Multi();  
        t1.start();  
    }  
}
```

```
}
```

```
Output:thread is running...
```

2) Java Thread Example by implementing Runnable interface

```
class Multi3 implements Runnable {  
    public void run() {  
        System.out.println("thread is running...");  
    }  
  
    public static void main(String args[]) {  
  
        Multi3 m1=new Multi3();  
        Thread t1 =new Thread(m1);  
        t1.start();  
    }  
}
```

```
Output:thread is running...
```

If you are not extending the Thread class, your class object would not be treated as a thread object. So you need to explicitly create Thread class object. We are passing the object of your class that implements Runnable so that your class run() method may execute.