SERVICENOW SYSTEM ADMINISTRATOR · NAAN MUDHALVAN (SMARTBRIDGE)

Performance Testing

Phase 6 · Project Testing

Deepak P (Team Lead) · Hemanthan B N · Ganesh A K · Irfan Rifayil Z

This document is the Project Testing evidence for the Script-Controlled ACL project on ServiceNow instance dev443713.service-now.com. Because the deliverable is a native platform security configuration rather than a coded application, performance is measured as functional and security correctness: does record-level, field-value-driven access control behave exactly as designed for each user and each operation. Testing was carried out on 2026-09-28 using ServiceNow impersonation, so every result reflects what the target user actually sees on the platform.

Test Environment

Instance	dev443713.service-now.com (Personal Developer Instance)
Release family	Australia / Zurich
Table under test	u_institution_details (Institution Details)
Access model	4 record-level ACLs (read, create, write, delete)
Roles	bb1 read, bb2 create, bb3 write, bb4 delete
Sample records	ECE001 (ECE), EEE001 (EEE), EEE002 (EEE), CSE001 (CSE)
Test method	Impersonation of each target user
Test date	2026-09-28

Functional and Security Test Cases

Test ID	Scenario	User / Role	Expected Result	Actual Result	Status
TC-01	Branch user sees only own-branch records	EEE User (bb1-bb4)	Institution Details list shows only EEE001 and EEE002 (2 of 2)	List displayed exactly EEE001 and EEE002	Pass
TC-02	Non-EEE records are hidden from branch user	EEE User (bb1-bb4)	ECE001 and CSE001 must not appear in the list	Neither ECE001 nor CSE001 was visible	Pass
TC-03	Branch user can create a record	EEE User (bb2)	New button is available and a record can be saved	New button present, record created successfully	Pass

Test ID	Scenario	User / Role	Expected Result	Actual Result	Status
TC-04	Branch user can update a record	EEE User (bb3)	EEE001 opens as an editable form with a working Update	Form editable, Update saved without error	Pass
TC-05	Branch user can delete a record	EEE User (bb4)	Delete control is available and removes the record	Delete control present on EEE001, record deletable	Pass
TC-06	User with no branch roles is blocked	Abel Tuter (no bb roles)	Access to the list must be denied	Page replaced by 'Security constraints prevent access to requested page'	Pass
TC-07	Administrator retains full visibility	System Administrator (admin)	All 4 records are visible regardless of branch	List showed ECE001, EEE001, EEE002 and CSE001	Pass


Result Summary

- 7 of 7 test cases passed. No defects were raised.
- Read access is correctly scoped by field value: the READ ACL (Advanced, role bb1, condition u_branch=EEE) combined with the gs.hasRole script returns records only to admin and bb1 holders, which is why the branch user sees 2 of the 4 records and the no-role user is blocked.
- Create, write and delete are correctly gated by roles bb2, bb3 and bb4 respectively, confirmed by EEE User being able to create, update and delete while a no-role user cannot reach the table at all.
- The removal of the auto-generated u_institution_details_user role was validated indirectly: each operation now succeeds using only its intended bb role, with no extra role required.


Platform Responsiveness Note

All operations were evaluated inside the ServiceNow Now Platform UI on a free Personal Developer Instance. List loads, form opens, save and delete actions, and impersonation switches all completed promptly with no timeouts or errors, and each ACL decision was applied on the same page render as the request. Because access control is enforced server-side by the ACL engine, correctness does not depend on client load, and the configuration behaved consistently across every user impersonated during testing.


Evidence (from the ServiceNow instance)




EEE User sees only the two EEE records



EEE User can update and delete



No-role user blocked



Admin sees all four records