RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:12 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:17 PM
Time taken	4 mins 21 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n, count = 0;
    if (scanf("%d", &n) != 1) return 0;

    int i = 1;
    count++; // count for initialization of i

    int s = 1;
    count++; // count for initialization of s

    while (count++, s <= n) { // count++ for while condition check
        i++;
        count++; // count for i++

        s += i;
        count++; // count for s += i
    }

    printf("%d", count);
    return 0;
}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:17 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:25 PM
Time taken	8 mins 19 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void func(int n)
{
    int count = 0;

    count++;                    // if(n==1)

    if(n == 1)
    {
        count++;                // printf("*")
    }
    else
    {
        for(int i = 1; i <= n; i++)
        {
            count++;            // i <= n

            for(int j = 1; j <= n; j++)
            {
                count++;        // j <= n
                count++;        // printf("*")
                count++;        // printf("*")
                break;
            }

            count++;            // i++
        }

        count++;                // final i <= n
    }

    printf("%d", count);
}
```

```
int main()
{
    int n;
    scanf("%d", &n);
    func(n);
    return 0;
}
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:26 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:27 PM
Time taken	1 min 33 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int num, count = 0;
    scanf("%d", &num);

    int i = 1;
    count++;                    // i = 1

    while(i <= num)
    {
        count++;                // while condition

        count++;                // num % i == 0

        if(num % i == 0)
        {
            count++;            // printf
        }

        i++;
    }

    printf("%d", count);
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:27 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:28 PM
Time taken	1 min 15 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, count = 0;
    scanf("%d", &n);

    int c = 0;
    count++;                    // c = 0

    int i = n / 2;
    count++;                    // i = n / 2

    while(i < n)
    {
        int j = 1;
        count++;                // j = 1

        while(j < n)
        {
            int k = 1;
            count++;            // k = 1

            while(k < n)
            {
                c++;
                count++;        // c++

                k = k * 2;
                count++;        // k = k * 2
            }

            j = 2 * j;
            count++;            // j = 2 * j
        }

        i++;
        count++;                // i++
    }

    printf("%d", count);
    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:28 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:30 PM
Time taken	1 min 45 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, count = 0;
    scanf("%d", &n);

    int rev = 0, remainder;
    count++;                    // rev = 0

    while(n != 0)
    {
        count++;                // n != 0

        remainder = n % 10;
        count++;                // n % 10

        rev = rev * 10 + remainder;
        count++;                // rev = rev * 10 + remainder

        n /= 10;
        count++;                // n /= 10
    }

    count++;                    // final n != 0 check
    count++;                    // printf("%d", rev)

    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 25 September 2026, 3:35 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 11:55 AM
Time taken	4 days 20 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int V;
    scanf("%d", &V);

    int coins[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
    int n = sizeof(coins) / sizeof(coins[0]);

    int count = 0;

    for (int i = 0; i < n; i++) {
        while (V >= coins[i]) {
            V -= coins[i];
            count++;
        }
    }

    printf("%d\n", count);
    return 0;
}

```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE

S2

Started on	Friday, 25 September 2026, 3:32 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 11:56 AM
Time taken	4 days 20 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparison function for qsort
int cmp(const void *a, const void *b) {
    return (*(int*)a - *(int*)b);
}

int findContentChildren(int g[], int n, int s[], int m) {
    qsort(g, n, sizeof(int), cmp);
    qsort(s, m, sizeof(int), cmp);

    int i = 0, j = 0, count = 0;

    while (i < n && j < m) {
        if (s[j] >= g[i]) {  // cookie satisfies child
            count++;
            i++;
            j++;
        } else {
            j++;  // try next bigger cookie
        }
    }
    return count;
}

int main() {
    int n, m;
    scanf("%d", &n);
    int g[n];
    for (int i = 0; i < n; i++) scanf("%d", &g[i]);

    scanf("%d", &m);
    int s[m];
    for (int i = 0; i < m; i++) scanf("%d", &s[i]);

    printf("%d\n", findContentChildren(g, n, s, m));
    return 0;
```

```
39 }
40
```

	Input	Expected	Got	
✔	2 1 2 3 1 2 3	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 9 October 2026, 3:13 PM
State	Finished
Completed on	Friday, 9 October 2026, 3:20 PM
Time taken	6 mins 45 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3 burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include<math.h>
int main(){
    int n;
    scanf("%d",&n);
    int arr[n];
    int sum=0;

    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    for(int i=0;i<n;i++){
        for(int j=0;j<n-i-1;j++){
            if(arr[j]<arr[j+1]){
                int temp=arr[j];
                arr[j]=arr[j+1];
                arr[j+1]=temp;
            }
        }
    }
    for(int i=0;i<n;i++){
        int s=pow(n,i);
        sum+=(arr[i]*s);
    }
    printf("%d",sum);

}
```

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 2	4 7 4 9 6	389	389	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE

S2

Started on	Friday, 25 September 2026, 4:00 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 11:57 AM
Time taken	4 days 19 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparison function for qsort (ascending order)
int compare(const void *a, const void *b) {
    return (*(int*)a - *(int*)b);
}

int main() {
    int n;
    scanf("%d", &n);

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // Sort the array in ascending order
    qsort(arr, n, sizeof(int), compare);

    long long maxSum = 0;
    // Compute sum of arr[i] * i
    for (int i = 0; i < n; i++) {
        maxSum += (long long)arr[i] * i;
    }

    // Print result
    printf("%lld\n", maxSum);

    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 25 September 2026, 4:01 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 11:57 AM
Time taken	4 days 19 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Comparison functions for qsort
int asc(const void *a, const void *b) {
    return (*(int*)a - *(int*)b);
}
int desc(const void *a, const void *b) {
    return (*(int*)b - *(int*)a);
}

int main() {
    int n;
    scanf("%d", &n);

    int arr1[n], arr2[n];
    for (int i = 0; i < n; i++) scanf("%d", &arr1[i]);
    for (int i = 0; i < n; i++) scanf("%d", &arr2[i]);

    // Sort arr1 ascending, arr2 descending
    qsort(arr1, n, sizeof(int), asc);
    qsort(arr2, n, sizeof(int), desc);

    long long sum = 0;
    for (int i = 0; i < n; i++) {
        sum += (long long)arr1[i] * arr2[i];
    }

    printf("%lld\n", sum);
    return 0;
}

```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

	Input	Expected	Got	
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:31 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:31 PM
Time taken	32 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

// Function to find the index of the first occurrence of 0 using Divide and Conquer
int findFirstZero(int arr[], int low, int high) {
    if (high >= low) {
        int mid = low + (high - low) / 2;

        // Check if mid is the first occurrence of 0
        if ((mid == 0 || arr[mid - 1] == 1) && arr[mid] == 0) {
            return mid;
        }

        // If element at mid is 1, the first 0 must be in the right half
        if (arr[mid] == 1) {
            return findFirstZero(arr, mid + 1, high);
        }

        // If element at mid is 0 but not the first 0, search in the left half
        return findFirstZero(arr, low, mid - 1);
    }

    return -1; // Return -1 if 0 is not present in the array
}

// Main function to calculate total zeros
int countZeroes(int arr[], int size) {
    int first_zero = findFirstZero(arr, 0, size - 1);

    if (first_zero == -1) {
        return 0;
    }

    return size - first_zero;
}

int main() {
    int m;
    if (scanf("%d", &m) != 1 || m <= 0) {
        return 0;
    }

    int arr[m];
    for (int i = 0; i < m; i++) {
        scanf("%d", &arr[i]);
    }

    int zeroesCount = countZeroes(arr, m);
    printf("%d\n", zeroesCount);

    return 0;
}
```

	Input	Expected	Got	
✔	5 1 1 1 0 0	2	2	✔
✔	10 1 1 1 1 1 1 1 1 1 1	0	0	✔
✔	8 0 0 0 0 0 0 0 0	8	8	✔
✔	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE

S2

Started on	Friday, 21 August 2026, 4:31 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:32 PM
Time taken	42 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findMajorityElement(int nums[], int n) {
    int candidate = 0;
    int count = 0;

    for (int i = 0; i < n; i++) {
        if (count == 0) {
            candidate = nums[i];
            count = 1;
        } else if (nums[i] == candidate) {
            count++;
        } else {
            count--;
        }
    }

    return candidate;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int nums[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &nums[i]);
    }

    printf("%d\n", findMajorityElement(nums, n));
    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:32 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:33 PM
Time taken	28 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

// Divide and Conquer function to find the floor of x
int findFloor(int arr[], int low, int high, int x) {
    // If element is smaller than the first element, floor doesn't exist
    if (low > high) {
        return -1;
    }

    // If last element is smaller than or equal to x, it is the floor
    if (x >= arr[high]) {
        return arr[high];
    }

    int mid = low + (high - low) / 2;

    // If mid element is equal to x, it is the floor
    if (arr[mid] == x) {
        return arr[mid];
    }

    // If x lies between mid-1 and mid, arr[mid-1] is the floor
    if (mid > 0 && arr[mid - 1] <= x && x < arr[mid]) {
        return arr[mid - 1];
    }

    // If x is smaller than mid, floor lies in left half
    if (x < arr[mid]) {
        return findFloor(arr, low, mid - 1, x);
    }

    // If x is greater than mid, floor lies in right half
    return findFloor(arr, mid + 1, high, x);
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int x;
    scanf("%d", &x);

    int floorValue = findFloor(arr, 0, n - 1, x);
    printf("%d\n", floorValue);

    return 0;
}
```

	Input	Expected	Got	
✔	6 1 2 8 10 12 19 5	2	2	✔
✔	5 10 22 85 108 129 100	85	85	✔
✔	7 3 5 7 9 11 13 15 10	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 21 August 2026, 4:33 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:33 PM
Time taken	26 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

// Recursive Divide and Conquer function to find two elements that sum to x
int findPairSum(int arr[], int low, int high, int x) {
    // Base Case: No pair found
    if (low >= high) {
        return 0;
    }

    int sum = arr[low] + arr[high];

    // If pair found, print the elements
    if (sum == x) {
        printf("%d\n%d\n", arr[low], arr[high]);
        return 1;
    }

    // If current sum is less than target, move left pointer rightward
    if (sum < x) {
        return findPairSum(arr, low + 1, high, x);
    }

    // If current sum is greater than target, move right pointer leftward
    return findPairSum(arr, low, high - 1, x);
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n < 2) {
        printf("No\n");
        return 0;
    }

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int x;
    scanf("%d", &x);

    if (!findPairSum(arr, 0, n - 1, x)) {
        printf("No\n");
    }

    return 0;
}
```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE

S2

Started on	Friday, 21 August 2026, 4:33 PM
State	Finished
Completed on	Friday, 21 August 2026, 4:34 PM
Time taken	32 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:
Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

Answer:

```c
#include <stdio.h>

void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

int partition(int arr[], int low, int high) {
    int pivot = arr[high];
    int i = (low - 1);

    for (int j = low; j < high; j++) {
        if (arr[j] < pivot) {
            i++;
            swap(&arr[i], &arr[j]);
        }
    }
    swap(&arr[i + 1], &arr[high]);
    return (i + 1);
}

void quickSort(int arr[], int low, int high) {
    if (low < high) {
        int pi = partition(arr, low, high);

        quickSort(arr, low, pi - 1);
        quickSort(arr, pi + 1, high);
    }
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) return 0;

    int arr[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    quickSort(arr, 0, n - 1);

    for (int i = 0; i < n; i++) {
        printf("%d", arr[i]);
        if (i < n - 1) {
            printf(" ");
        }
    }
    printf("\n");

    return 0;
}
```

	Input	Expected	Got	
✔	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✔
✔	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✔
✔	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 25 September 2026, 3:24 PM
State	Finished
Completed on	Friday, 25 September 2026, 4:09 PM
Time taken	45 mins
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: *6*
Output:*6*
Explanation: *There are 6 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1
3+3
1+1+1+3
1+1+3+1
1+3+1+1
3+1+1+1

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <string.h>

#define MAX_DIGITS 1000  // enough to hold very large results

// Big integer addition: res = a + b
void addBigInt(char *a, char *b, char *res) {
    int lenA = strlen(a);
    int lenB = strlen(b);
    int carry = 0, i, j, k = 0;
    char temp[MAX_DIGITS];

    i = lenA - 1;
    j = lenB - 1;

    while (i >= 0 || j >= 0 || carry) {
        int digitA = (i >= 0) ? a[i] - '0' : 0;
        int digitB = (j >= 0) ? b[j] - '0' : 0;
        int sum = digitA + digitB + carry;
        temp[k++] = (sum % 10) + '0';
        carry = sum / 10;
        i--; j--;
    }

    // reverse temp into res
    for (int p = 0; p < k; p++) {
        res[p] = temp[k - 1 - p];
    }
    res[k] = '\0';
}

// Copy string
void copyStr(char *dest, const char *src) {
    strcpy(dest, src);
}

int main() {
    int n;
    scanf("%d", &n);

```

```
41      char dp[n+1][MAX_DIGITS];
42      // initialize
43      copyStr(dp[0], "1");
44
45      for (int i = 1; i <= n; i++) {
46          char sum[MAX_DIGITS] = "0";
47          addBigInt(dp[i-1], sum, sum);  // sum = dp[i-1]
48
49          if (i >= 3) {
50              char temp[MAX_DIGITS];
51              addBigInt(sum, dp[i-3], temp);
52              copyStr(dp[i], temp);
```

	Input	Expected	Got	
✔	6	6	6	✔
✔	25	8641	8641	✔
✔	100	24382819596721629	24382819596721629	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE

S2

Started on	Friday, 25 September 2026, 3:30 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:31 PM
Time taken	10 days
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

#define MAX 100  // maximum board size

int main() {
    int n;
    scanf("%d", &n);

    int board[MAX][MAX];
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &board[i][j]);
        }
    }

    long long dp[MAX][MAX];

    // Initialize starting cell
    dp[0][0] = board[0][0];

    // Fill first row
    for (int j = 1; j < n; j++) {
        dp[0][j] = dp[0][j-1] + board[0][j];
    }

    // Fill first column
    for (int i = 1; i < n; i++) {
        dp[i][0] = dp[i-1][0] + board[i][0];
    }

    // Fill rest of the dp table
    for (int i = 1; i < n; i++) {
        for (int j = 1; j < n; j++) {
            long long fromTop = dp[i-1][j];
            long long fromLeft = dp[i][j-1];
            dp[i][j] = board[i][j] + (fromTop > fromLeft ? fromTop : fromLeft);
```

```
        }
    }

    printf("%lld\n", dp[n-1][n-1]);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 4 2 3 4 8 7 1	19	19	✔
✔	3 1 3 1 1 5 1 4 2 1	12	12	✔
✔	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE

S2

Started on	Friday, 25 September 2026, 3:31 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:31 PM
Time taken	10 days
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1		a	g	**g**	**t**	**a**	**b**
s2	**g**	x	**t**	x	**a**	y	**b**

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <string.h>

#define MAX 1000  // maximum string length

int LCS(char *s1, char *s2) {
    int n = strlen(s1);
    int m = strlen(s2);

    int dp[MAX+1][MAX+1];

    // initialize
    for (int i = 0; i <= n; i++) {
        for (int j = 0; j <= m; j++) {
            if (i == 0 || j == 0)
                dp[i][j] = 0;
            else if (s1[i-1] == s2[j-1])
                dp[i][j] = 1 + dp[i-1][j-1];
            else
                dp[i][j] = (dp[i-1][j] > dp[i][j-1]) ? dp[i-1][j] : dp[i][j-1];
        }
    }

    return dp[n][m];
}

int main() {
    char s1[MAX], s2[MAX];
    scanf("%s", s1);
    scanf("%s", s2);

    printf("%d\n", LCS(s1, s2));
    return 0;
}

```

	Input	Expected	Got	
✔	aab azb	2	2	✔
✔	ABCD ABCD	4	4	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Friday, 25 September 2026, 3:32 PM
State	Finished
Completed on	Friday, 25 September 2026, 4:32 PM
Time taken	1 hour
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

#define MAX 1000

int LNDS(int arr[], int n) {
    int dp[MAX];
    int maxLen = 1;

    for (int i = 0; i < n; i++) {
        dp[i] = 1; // base case
        for (int j = 0; j < i; j++) {
            if (arr[j] <= arr[i] && dp[j] + 1 > dp[i]) {
                dp[i] = dp[j] + 1;
            }
        }
        if (dp[i] > maxLen) {
            maxLen = dp[i];
        }
    }
    return maxLen;
}

int main() {
    int n;
    scanf("%d", &n);
    int arr[MAX];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    printf("%d\n", LNDS(arr, n));
    return 0;
}

```

	Input	Expected	Got	
✔	9 -1 3 4 5 2 2 2 2 3	6	6	✔
✔	7 1 2 2 4 5 7 6	6	6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Monday, 5 October 2026, 3:17 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:22 PM
Time taken	4 mins 30 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int findDuplicate(const int* arr, int n) {
    // Phase 1: Move tortoise and hare to find a meeting point inside the cycle
    int tortoise = arr[0];
    int hare = arr[0];

    do {
        tortoise = arr[tortoise];
        hare = arr[arr[hare]];
    } while (tortoise != hare);

    // Phase 2: Find the entrance to the cycle (the duplicate number)
    tortoise = arr[0];
    while (tortoise != hare) {
        tortoise = arr[tortoise];
        hare = arr[hare];
    }

    return tortoise;
}

int main() {
    int n;

    // Read the total number of elements
    if (scanf("%d", &n) != 1 || n <= 0) {
        return 1;
    }

    // Allocate memory for the read-only array
    int* arr = (int*)malloc(n * sizeof(int));
    if (arr == NULL) {
        return 1;
    }

    // Read the n elements
    for (int i = 0; i < n; i++) {
        if (scanf("%d", &arr[i]) != 1) {
            free(arr);
            return 1;
        }
    }

    // Find and print the duplicate element
    int duplicate = findDuplicate(arr, n);
    printf("%d\n", duplicate);

    // Clean up allocated memory
    free(arr);
    return 0;
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Monday, 5 October 2026, 3:19 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:22 PM
Time taken	2 mins 40 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int findDuplicate(const int* arr, int n) {
    // Phase 1: Move tortoise and hare to find a meeting point inside the cycle
    int tortoise = arr[0];
    int hare = arr[0];

    do {
        tortoise = arr[tortoise];
        hare = arr[arr[hare]];
    } while (tortoise != hare);

    // Phase 2: Find the entrance to the cycle (the duplicate number)
    tortoise = arr[0];
    while (tortoise != hare) {
        tortoise = arr[tortoise];
        hare = arr[hare];
    }

    return tortoise;
}

int main() {
    int n;

    // Read the total number of elements
    if (scanf("%d", &n) != 1 || n <= 0) {
        return 1;
    }

    // Allocate memory for the read-only array
    int* arr = (int*)malloc(n * sizeof(int));
    if (arr == NULL) {
        return 1;
    }

    // Read all n space-separated elements from the line
    for (int i = 0; i < n; i++) {
        if (scanf("%d", &arr[i]) != 1) {
            free(arr);
            return 1;
        }
    }

    // Find and print the duplicate element
    int duplicate = findDuplicate(arr, n);
    printf("%d\n", duplicate);

    // Clean up allocated memory
    free(arr);
    return 0;
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE

S2

Started on	Monday, 5 October 2026, 3:22 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:26 PM
Time taken	4 mins 15 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <stdlib.h>

void solve() {
    int n1, n2;

    // Read the size of the first array
    if (scanf("%d", &n1) != 1) return;
    int* arr1 = (int*)malloc(n1 * sizeof(int));
    for (int i = 0; i < n1; i++) {
        scanf("%d", &arr1[i]);
    }

    // Read the size of the second array
    if (scanf("%d", &n2) != 1) {
        free(arr1);
        return;
    }
    int* arr2 = (int*)malloc(n2 * sizeof(int));
    for (int i = 0; i < n2; i++) {
        scanf("%d", &arr2[i]);
    }

    // Two-pointer logic to find intersection
    int i = 0, j = 0;
    int first = 1; // Flag to manage trailing spaces in output

    while (i < n1 && j < n2) {
        if (arr1[i] < arr2[j]) {
```

```
            i++;
        } else if (arr1[i] > arr2[j]) {
            j++;
        } else {
            // Found a common element
            if (!first) {
                printf(" ");
            }
            printf("%d", arr1[i]);
            first = 0;

            i++;
            j++;
        }
    }
    printf("\n");

    // Clean up memory
    free(arr1);
    free(arr2);
}

int main() {
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Monday, 5 October 2026, 3:27 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:28 PM
Time taken	1 min 49 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

void solve() {
    int n1, n2;

    // Read size of the first array
    if (scanf("%d", &n1) != 1) return;
    int* arr1 = (int*)malloc(n1 * sizeof(int));
    for (int i = 0; i < n1; i++) {
        scanf("%d", &arr1[i]);
    }

    // Read size of the second array
    if (scanf("%d", &n2) != 1) {
        free(arr1);
        return;
    }
    int* arr2 = (int*)malloc(n2 * sizeof(int));
    for (int i = 0; i < n2; i++) {
        scanf("%d", &arr2[i]);
    }

    // Two-pointer intersection logic
    int i = 0, j = 0;
    int first = 1; // Tracks formatting to avoid leading/trailing spaces

    while (i < n1 && j < n2) {
        if (arr1[i] < arr2[i]) {
```

```
            i++;
        } else if (arr1[i] > arr2[j]) {
            j++;
        } else {
            // Match found
            if (!first) {
                printf(" ");
            }
            printf("%d", arr1[i]);
            first = 0;

            i++;
            j++;
        }
    }
    printf("\n");

    // Clean up memory
    free(arr1);
    free(arr2);
}

int main() {
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Monday, 5 October 2026, 3:28 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:29 PM
Time taken	38 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int hasPairWithDifference(const int* arr, int n, int k) {
    int i = 0;
    int j = 1;

    // Slide pointers across the array
    while (i < n && j < n) {
        // Ensure i and j are distinct indices
        if (i == j) {
            j++;
            continue;
        }

        int diff = arr[j] - arr[i];

        if (diff == k) {
            return 1; // Pair found
        } else if (diff < k) {
            j++; // Increase the difference by moving the right pointer
        } else {
            i++; // Decrease the difference by moving the left pointer
        }
    }

    return 0; // No pair found
}

int main() {
    int n;

    // Read number of elements
    if (scanf("%d", &n) != 1 || n <= 0) {
        printf("0\n");
        return 0;
    }

    // Allocate memory for the array
    int* arr = (int*)malloc(n * sizeof(int));
    if (arr == NULL) {
        return 1;
    }

    // Read the array elements (handles single line or multiple lines)
    for (int i = 0; i < n; i++) {
        if (scanf("%d", &arr[i]) != 1) {
            free(arr);
```

```
            return 1;
        }
    }

```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

S Deepak Sathya 250701130-2025-CSE S2

Started on	Monday, 5 October 2026, 3:29 PM
State	Finished
Completed on	Monday, 5 October 2026, 3:31 PM
Time taken	1 min 25 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int findPairWithDifference(const int* arr, int n, int k) {
    int i = 0;
    int j = 1;

    // Two-pointer traversal
    while (i < n && j < n) {
        // Enforce the constraint i != j
        if (i == j) {
            j++;
            continue;
        }

        int diff = arr[j] - arr[i];

        if (diff == k) {
            return 1; // Pair found
        } else if (diff < k) {
            j++; // Move the right pointer to increase the difference
        } else {
            i++; // Move the left pointer to decrease the difference
        }
    }

    return 0; // No valid pair exists
}

int main() {
    int n;

    // Read the total number of elements
    if (scanf("%d", &n) != 1 || n <= 0) {
        printf("0\n");
        return 0;
    }

    // Allocate memory for the array
    int* arr = (int*)malloc(n * sizeof(int));
    if (arr == NULL) {
        return 1;
    }

    // Read the n elements
    for (int i = 0; i < n; i++) {
        if (scanf("%d", &arr[i]) != 1) {
            free(arr);
```

```
            return 1;
        }
    }

```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course