




deeplearning.ai

Recurrent Neural Networks

Recurrent Neural Network Model


Why not a standard network?



Problems:

- - Inputs, outputs can be different lengths in different examples.
- - Doesn't share features learned across different positions of text.


Recurrent Neural Networks



He said, "Teddy Roosevelt was a great President."

He said, "Teddy bears are on sale!"

Forward Propagation



$$a^{<0>} = \vec{0}.$$

$$\underline{a}^{<1>} = g_1(W_{aa} a^{<0>} + \underline{W_{ax}} x^{<1>} + b_a) \leftarrow \underline{\tanh / \text{Relu}}$$

$$\underline{\hat{y}}^{<1>} = g_2(\underline{W_{ya}} \underline{a}^{<1>} + b_y) \leftarrow \text{Sigmoid}$$

$$\boxed{\begin{aligned} a^{<t>} &= g(W_{aa} a^{<t-1>} + W_{ax} x^{<t>} + b_a) \\ \hat{y}^{<t>} &= g(W_{ya} a^{<t>} + b_y) \end{aligned}}$$

Simplified RNN notation

$$a^{<t>} = g(\underbrace{W_{aa} a^{<t-1>}}_{\substack{\uparrow \\ (100, 100)}} + \underbrace{W_{ax} x^{<t>}}_{\substack{\uparrow \\ (100, 10,000)}} + b_a)$$

$$\hat{y}^{<t>} = g(W_{ya} a^{<t>} + b_y)$$

$$\hat{y}^{<t>} = g(W_y a^{<t>} + b_y)$$

$$a^{<t>} = g(\underbrace{W_a}_{\text{green circle}} \underbrace{[a^{<t-1>}, x^{<t>}]}_{\text{purple box}} + b_a)$$

$$\begin{matrix} \uparrow 100 \\ \left[\begin{array}{c|c} W_{aa} & W_{ax} \end{array} \right] \\ \leftarrow 100 \quad \leftarrow 10,000 \end{matrix} = W_a \quad (100, 10,000)$$

$$[a^{<t-1>}, x^{<t>}] = \begin{bmatrix} a^{<t-1>} \\ x^{<t>} \end{bmatrix} \quad \begin{matrix} \updownarrow 100 \\ \updownarrow 10,000 \\ \updownarrow 10,100 \end{matrix}$$

$$\begin{bmatrix} W_{aa} & W_{ax} \end{bmatrix} \begin{bmatrix} a^{<t-1>} \\ x^{<t>} \end{bmatrix} = \underline{W_{aa} a^{<t-1>} + W_{ax} x^{<t>}}$$