



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Experiment 3

**Student Name:** Deepanshu Mandhyan

**Branch:** CSE

**Semester:** 5th

**Subject Name:** ADBMS

**UID:** 23BCS12327

**Section/Group:** KRG 3-A

**Date of Performance:** 14/08/2025

**Subject Code:** 23CSP-333

### 1. Aim:

1. Create an Employee relation with a single attribute EMP\_ID. From this relation, find the maximum EMP\_ID value after removing duplicates.

2. Define two tables:

a. Department(ID, Name)

b. Employees(ID, Name, Salary, DeptID)

Then, retrieve the employee(s) with the highest salary in each department.

3. Create two tables A(EmpID, EmpName, Salary) and B(EmpID, EmpName, Salary). From both tables, determine the lowest salary of each employee across the two tables..

### 2. Objective:

- Create employee relation and find max EMP\_ID without duplicates.
- Identify highest earners in each department.
- Find lowest salary per employee across two tables.
- Practice SQL queries on creation, grouping, and aggregation.

### 3. DBMS script and output:

#### Solution-(1)

```
CREATE TABLE EMPLOYEE1 (  
    EMP_ID INT  
);
```

-- Insert given data

```
INSERT INTO EMPLOYEE1(EMP_ID) VALUES
```

```
(2), (4), (4), (6), (6), (7), (8), (8), (8);
```

```
SELECT MAX(EMP_ID) AS MAXID FROM EMPLOYEE1 WHERE EMP_ID  
NOT IN
```

```
(SELECT EMP_ID
```

```
FROM
```

```
EMPLOYEE1
```

```
GROUP BY EMP_ID
```

```
HAVING COUNT(EMP_ID)>1 )
```

	MAXID
1	7

**Figure(a): JOIN Operation**

### **Solution-(b)**

-- Create Department Table

```
CREATE TABLE department (  
  id INT PRIMARY KEY,  
  dept_name VARCHAR(50)  
);
```

-- CREATE Employee Table

```
CREATE TABLE employee (  
  id INT,  
  name VARCHAR(50),  
  salary INT,  
  department_id INT,  
  FOREIGN KEY (department_id) REFERENCES department(id)  
);
```

```
-- Insert into Department Table
INSERT INTO department (id, dept_name) VALUES
(1, 'IT'),
(2, 'SALES');

-- Insert into Employee Table
INSERT INTO employee (id, name, salary, department_id) VALUES
(1, 'JOE', 70000, 1),
(2, 'JIM', 90000, 1),
(3, 'HENRY', 80000, 2),
(4, 'SAM', 60000, 2),
(5, 'MAX', 90000, 1);

-- APPROACH 01
SELECT d.dept_name, e.name
FROM department d
INNER JOIN employee e
ON d.id = e.department_id
WHERE e.salary IN
( SELECT MAX(salary)
  FROM employee
  WHERE department_id = e.department_id
)
ORDER BY d.dept_name
```

	dept_name	name
1	IT	MAX
2	IT	JIM
3	SALES	HENRY

**Figure (b): SQL Operation**

**Solution (c):**

```
CREATE TABLE A
( EmpID INT PRIMARY KEY,
  Ename VARCHAR(50),
  Salary INT);
```

```
CREATE TABLE B  
( EmpID INT PRIMARY KEY,  
  Ename VARCHAR(50),  
  Salary INT);
```

```
INSERT INTO A (EmpID, Ename, Salary) VALUES  
(1, 'AA', 1000),  
(2, 'BB', 300);
```

```
INSERT INTO B (EmpID, Ename, Salary) VALUES  
(2, 'BB', 400),  
(3, 'CC', 100);
```

```
SELECT EmpID, MIN(Ename), MIN(Salary) AS Salary  
FROM  
(  
  SELECT * FROM A  
  UNION ALL  
  SELECT * FROM B  
) AS Intermediate_result  
GROUP BY EmpID
```

	EmpID	(No column name)	Salary
1	1	AA	1000
2	2	BB	300
3	3	CC	100

#### 4. Learning Outcomes:

- Learn to model hierarchies using self-joins
- Use LEFT JOINS to include unmatched rows
- Apply multi-column join conditions (e.g., ID & YEAR)
- Handle NULLs using IFNULL (or ISNULL in SQL Server)
- Build SQL skills for real-world data queries