Status	Finished
Started	Thursday, 1 October 2026, 3:47 PM
Completed	Thursday, 1 October 2026, 3:56 PM
Duration	9 mins 1 sec
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. True ✓
True

c. True
False

d. False
True

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a.
{'rec', True, ('cse', 'ece')}

b. Error

c. {'rec', 1, ('cse', 'ece')} ✓

d. {'rec', 1, ('cse', 'ece'),True}

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. iii

b. ii

c. i,ii ✓

d. All of the above

Question **4**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain only strings as its elements.

b. In Python, a tuple can contain only integers as its elements.

c. In Python, a tuple can contain either string or integer but not both at a time.

d. In Python, a tuple can contain both integers and strings as its elements. ✓

Question **5**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. Yes, Yes

b. "==" is not supported for set in Python

c. Yes, No ✓

d. No, No

Question **6**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

```
t = (15,83,83,52,60,45,52,85,100)
print(min(t)+max(t)+t.count(52))
```

a. 100

b. Error

c. 2

d. 117 ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {0,0,9}

b. It will throw an error as there are two 0 while creating the set.

c. {9}

d. {0,9} ✓

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

b. TypeError: update() doesn't allow list as a argument.

c. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

d. Name Error

Question **9**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

- a. Error ✓
- b. 12
- c. (55,78,64,25)
- d. (12)

Question **10**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

- a. (11,3,11,11,3,11,11,11,3)
- b. [11,11,11,3,3,3]
- c. (11,3)(11,3)(11,3)
- d. (11, 3, 11, 3, 11, 3) ✓

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

- a. (36, 25, 14) ✓
- b. (3,14,25)
- c. (58,47,36,25)
- d. Error

Question **12**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50)(40, 50, 60, 70, 80)

b. (10, 20, 30, 40) (40, 50, 60, 70, 80)

c. (30, 40, 50) (10, 20, 30, 40)

d. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

Question **13**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓

Question **14**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [1, 2, 4, 3, 8, 9]

b. (1, 4, 8)

c. [1, 4, 8] ✓

d. [2, 3, 9]

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
my_t1 = (1, 2, 3, 4)
my_t1.append( (5, 6, 7) )
print(len(my_t1))
```

a. 2

b. 5

c. Error ✓

d. 1