

# Model Accuracy and Evaluation

Spring 2023

May 17 2023


## Recap: KNN (K- Nearest Neighbor)

- *Supervised machine learning algorithm i.e., it requires labeled data for training*
- *Need to tell the algorithm the exact number of neighbors ( $K$ ) we want to consider*

## Training and Testing

**Training:** *Fitting a model with certain hyper-parameters on a particular subset of the dataset*

**Testing:** *Test the model on a different subset of the dataset to get an estimate of a final, unbiased assessment of the model's performance*



rstudio.com

## Workflows

A machine learning workflow (the “black box”) containing model specification and preprocessing recipe/formula

# Forest Fire : Data Description (Recall!)

Variable	Description
Date	(DD-MM-YYYY) Day, month, year
Temp	Noon temperature in Celsius degrees: 22 to 42
RH	Relative Humidity in percentage: 21 to 90
Ws	Wind speed in km/h: 6 to 29
Rain	Daily total rain in mm: 0 to 16.8
Fine Fuel Moisture Code (FFMC) index	28.6 to 92.5
Duff Moisture Code (DMC) index	1.1 to 65.9
Drought Code (DC) index	7 to 220.4
Initial Spread Index (ISI) index	0 to 18.5
Buildup Index (BUI) index	1.1 to 68
Fire Weather Index (FWI) index	0 to 31.1
Classes	Two classes, namely <b>fire</b> and <b>not fire</b>

# 1. Create a workflow: Split the raw data

```
set.seed(123) # set seed for reproducibility

# Prepare the raw dataset
fire_raw <- fire %>% select(temperature, isi, classes)

fire_split <- initial_split(fire_raw, prop = 0.75)
```

```
# Create training data
(fire_train <- fire_split %>% training())
# A tibble: 182 × 3
  temperature    isi classes
    <dbl>    <dbl> <chr>
1       38     4.1  fire
2       34    14.3  fire
3       33     6.7  fire
4       30     1   not fire
5       35     7.5  fire
6       34     7.3  fire
7       33     2.8  fire
8       31     2.5  not fire
9       34     3    not fire
10      33    14.2  fire
# ... with 172 more rows
```

```
# Create testing data
(fire_test <- fire_split %>% testing())
# A tibble: 61 × 3
  temperature    isi classes
    <dbl>    <dbl> <chr>
1       29     1   not fire
2       26     0.3 not fire
3       26     4.8  fire
4       28     0.4 not fire
5       31     0.7 not fire
6       31     2.5 not fire
7       34     9.2  fire
8       32     7.6  fire
9       32     2.2 not fire
10      29     1.1 not fire
# ... with 51 more rows
```

## 2. Make a recipe

```
fire_recipe <- recipe(classes ~ ., data = fire_raw) %>%  
  step_scale(all_predictors()) %>% # scale the predictors  
  step_center(all_predictors()) %>% # center the predictors  
  prep      # pre-process
```

### 3. Specify the model

```
fire_knn_spec <- nearest_neighbor(mode = "classification",  
                                  engine = "kknn",  
                                  weight_func = "rectangular",  
                                  neighbors = 5)
```



## 4. Define the workflow object

```
fire_workflow <- workflow() %>% # initialize a workflow  
  add_recipe(fire_recipe) %>% # add recipe  
  add_model(fire_knn_spec) # add model specification
```

## 5. Fit the model

```
fire_fit <- fit(fire_workflow, data = fire_train)
```

## Fitted workflow

```
fire_fit
== Workflow [trained] ==
Preprocessor: Recipe
Model: nearest_neighbor()

— Preprocessor —
2 Recipe Steps

• step_scale()
• step_center()

— Model —

Call:
kkn::train.kknn(formula = ..y ~ ., data = data, ks = min_rows(5,      data, 5), kernel = ~"rectangular")

Type of response variable: nominal
Minimal misclassification: 0.03296703
Best kernel: rectangular
Best k: 5
```

## 6. Evaluate the model on test dataset

```
test_features <- fire_test %>% select(temperature, isi)
fire_pred <- predict(fire_fit, test_features)
fire_results <- fire_test %>%
  select(classes) %>%
  bind_cols(predicted = fire_pred)
```


## 7. Compare the known labels and predicted labels

```
knitr::kable(fire_results)
```

classes	.pred_class
not fire	not fire
not fire	not fire
fire	fire
not fire	not fire
not fire	not fire
not fire	not fire
not fire	not fire


# ✍ GROUP ACTIVITY 1

05:00



- Get the class activity 22.Rmd file from [moodle](#)
- Let's work on group activity 1 together

**How do we choose the number of neighbors in a principled way?**







## Evaluating accuracy


We want to evaluate classifiers based on some accuracy metrics.

- Randomly split data set into two pieces: **training set** and **test set**
- Train (i.e. fit) KNN on the training set
- Make predictions on the test set
- See how good those predictions are


# Train (left) and test (right) dataset (50-50)



## Training 1-NN



## Evaluating performance



		Expected	
		+ve	-ve
Predicted	+ve	45	8
	-ve	15	32

TP (True Positive) points to the cell with 45.

FP (False Positive) points to the cell with 8.

FN (False Negative) points to the cell with 15.

TN (True Negative) points to the cell with 32.

A confusion matrix diagram showing the relationship between predicted and expected class labels. The matrix is a 2x2 grid with 'Expected' labels as columns (+ve, -ve) and 'Predicted' labels as rows (+ve, -ve). The cells contain counts: 45 (TP, green), 8 (FP, red), 15 (FN, red), and 32 (TN, green). Arrows point from labels to their respective cells: TP to 45, FP to 8, FN to 15, and TN to 32.

		Expected	
		+ve	-ve
Predicted	+ve	45	8
	-ve	15	32

Confusion matrix: tabulation of true (i.e. expected) and predicted class labels

Common metrics include:

- accuracy
- sensitivity
- specificity
- positive predictive value (PPV)

```
conf_mat(fire_results, truth = classes, estimate = predicted)
```

	Truth	
Prediction	fire	not fire
fire	61	2
not fire	6	53

## Proportion of correctly classified cases

$$\text{Accuracy} = \frac{\text{true positives} + \text{true negatives}}{n}$$

	Truth	
Prediction	fire	not fire
fire	61	2
not fire	6	53

```
accuracy(fire_results, truth = classes,  
         estimate = predicted)  
# A tibble: 1 × 3  
  .metric .estimator .estimate  
  <chr>   <chr>      <dbl>  
1 accuracy binary      0.934
```



Proportion of positive cases that are predicted to be positive

$$\text{Sensitivity} = \frac{\text{true positives}}{\text{true positives} + \text{false negatives}}$$

Also called... true positive rate or recall

	Truth	
Prediction	fire	not fire
fire	61	2
not fire	6	53

```
sens(fire_results, truth = classes,  
      estimate = predicted)  
# A tibble: 1 × 3  
  .metric .estimator .estimate  
  <chr>   <chr>       <dbl>  
1 sens    binary         0.910
```

Proportion of negative cases that are predicted to be negative

$$\text{Specificity} = \frac{\text{true negatives}}{\text{false positives} + \text{true negatives}}$$

Also called... true negative rate

	Truth	
Prediction	fire	not fire
fire	61	2
not fire	6	53

```
spec(fire_results, truth = classes,  
      estimate = predicted)  
# A tibble: 1 × 3  
  .metric .estimator .estimate  
  <chr>   <chr>       <dbl>  
1 spec    binary       0.964
```

## Positive predictive value (PPV)

Proportion of cases that are predicted to be positives that are truly positives

$$\text{PPV} = \frac{\text{true positives}}{\text{true positives} + \text{false positives}}$$


Also called... precision

	Truth	
Prediction	fire	not fire
fire	61	2
not fire	6	53

```
ppv(fire_results, truth = classes,  
    estimate = predicted)  
# A tibble: 1 × 3  
  .metric .estimator .estimate  
  <chr>   <chr>       <dbl>  
1 ppv     binary         0.968
```

# GROUP ACTIVITY 2

15:00



- Please continue working on group activity 2
- Consider calculating the accuracy metrics by hand
- Verify your calculations with R-code

## Tabulate the metrics !!

```
custom_metrics <- metric_set(accuracy, sens, spec, ppv) # select custom metrics
metrics <- custom_metrics(fire_results, truth = classes, estimate = predicted)
metrics
```

**# A tibble: 4 × 3**

	.metric	.estimator	.estimate
	<chr>	<chr>	<dbl>
1	accuracy	binary	0.934
2	sens	binary	0.910
3	spec	binary	0.964
4	ppv	binary	0.968

# Choose the optimal K based on majority of the metrics!

