



J S P

Authored by : Sangeeta Joshi

Presented by: Sangeeta Joshi

This presentation is the intellectual property of Cybage Software Pvt. Ltd. and is meant for the usage of the intended Cybage employee/s for training purpose only. This should not be used for any other purpose or reproduced in any other form without written permission and consent of the concerned authorities.

Agenda

- Introduction to JSP Technology
- JSP Directives
- JSP Implicit Objects
- JSP Standard Actions

JSP

- Embedding java code into tags
- Separation of Presentation from Business logic
- Template based content generation

Three types of predefined tags:

- Directives
- Scripting elements
- Actions

JSP Elements

Element

- Syntax

Declaration

- `<% ! JSP declaration %>`

Expression

- `<%= java expression %>`

JSP Scriptlet

- `<% java statements %>`

JSP Directive

- `<% @%>`

JSP Comment

- `<%- - JSP Comment - -%>`

JSP Directives

The general syntax for JSP Directives

<%@ directive [---] %>

- **@Page** : Controls JSP Page properties
- **@include** : Includes content of a file into JSP page at translation time
- **@taglib** : Makes a custom tag library available within JSP

Page Directive Attributes

- import
- language
- extends
- session
- buffer
- autoflush
- isThradSafe
- Info
- errorPage
- isErrorPage
- contentType

Include directive

Syntax:

```
<%@ include file= "file name" %>
```


Implicit Objects

Object	Class
application	<code>javax.servlet.ServletContext</code>
config	<code>javax.servlet.ServletConfig</code>
exception	<code>java.lang.Throwable</code>
out	<code>javax.servlet.jsp.JspWriter</code>
page	<code>java.lang.Object</code>
PageContext	<code>javax.servlet.jsp.PageContext</code>
request	<code>javax.servlet.ServletRequest</code>
response	<code>javax.servlet.ServletResponse</code>
session	<code>javax.servlet.http.HttpSession</code>

JSP Standard Actions

Action element	Description
<code><jsp:useBean></code>	Makes a JavaBeans component available in a page
<code><jsp:getProperty></code>	Gets a property value from a JavaBeans component and adds it to the response
<code><jsp:setProperty></code>	Sets a JavaBeans component property value

JSP Standard Actions

Action element	Description
<code><jsp:include></code>	Includes the response from a servlet or JSP page during the request processing phase
<code><jsp:forward></code>	Forwards the processing of a request to servlet or JSP page
<code><jsp:param></code>	Adds a parameter value to a request handed off to another servlet or JSP page using <code><jsp:include></code> or <code><jsp:forward></code>
<code><jsp:plugin></code>	Generates HTML that contains the appropriate browser-dependent elements (OBJECT or EMBED) needed to execute an applet with the Java Plug-in software

Any Questions?

