

ubuntu@ip-172-31-5-35: ~/ITEND\$ mkdir kb3

ubuntu@ip-172-31-5-35: ~/Tiredness\$ cd kb\$



ubuntu@ip-172-31-5-35:~/\$ cd /tmp/ && ls -la /tmp/dep10ymemt.yml

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: trend-app
spec:
  replicas: 2
  selector:
    matchLabels:
      app: trend
  template:
    metadata:
      labels:
        app: trend
    spec:
      containers:
        - name: trend-container
          image: dockerhubuser/trend-nginx-app:latest
          ports:
            - containerPort: 3000
```

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: trend-app
spec:
  replicas: 2
  selector:
    matchLabels:
      app: trend
  template:
    metadata:
      labels:
        app: trend
    spec:
      containers:
        - name: trend-container
          image: dockerhubuser/trend-app:latest
```

11b11111@ip-172-31-5-35 ~ / T r e n d / k 0 5 \$ n a n o s e r v i c e . y m l

```
apiVersion: v1
kind: Service
metadata:
  name: trend-service
spec:
  type: LoadBalancer
  selector:
    app: trend
  ports:
    - port: 80
      targetPort: 3000
```



```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ kubectl apply -f k8s/  
Command 'kubectl' not found, did you mean:  
  command 'kubectx' from deb kubectx (0.9.5-1ubuntu0.4)  
Try: sudo apt install <deb name>  
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```



```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ curl -LO https://dl.k8s.io/release/$(curl -L -s https://dl.k8s.io/release/stable.txt)/bin/linux/amd64/kubect1
```

```
1
ubuntu@ip-172-31-5-35:~/Trend/k8s$ curl -LO https://dl.k8s.io/release/$(curl -L -s https://dl.k8s.io/release/stable.txt)/bin/linux/amd64/kub
ectl

  % Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
                                 Dload  Upload  Total  Spent    Left    Speed

100  138    100    138     0     0   456      0  --:--:--  --:--:--  --:--:--   456
100 55.8M    100 55.8M     0     0 112M      0  --:--:--  --:--:--  --:--:-- 112M
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

◆ Step 1.2: Permission do

```
bash
```

 Copy code

```
chmod +x kubect1
```

```
ubuntu@ip-172-31-5-35: ~/Trend/k8s$ chmod +x kubectl
```

```
ubuntu@ip-172-31-5-35: ~/Trend/k8s$
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ sudo mv kubectl /usr/local/bin/
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ kubectl version --client
Client Version: v1.35.0
Kustomize Version: v5.7.1
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ aws --version
aws-cli/2.32.21 Python/3.13.11 Linux/6.14.0-1015-aws exe/x86_64.ubuntu.24
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

	Name 		Instance ID	Instance state 	Instance type 	Status check	Alarm status
---	--	---	-------------	--	---	--------------	--------------

	Trend-App		i-005d90f4edade8730	 Running  	t3.small	 3/3 checks passed	View alarms 
---	-----------	--	---------------------	---	----------	---	---

Instances (1/2) [Info](#)

[Connect](#)[Instance state ▼](#)[Actions ▲](#)[Launch instances](#)

Find Instance by attribute or tag (case-sensitive)

Instance state = running

[Clear filters](#)

Name



Instance ID

Instance state



Trend-App

i-005d90f4edade8730

Running



jenkins-server

i-0487941227a86f4db

Running

Change security groups

Get Windows password

Modify IAM role

Instance diagnostics

Instance settings ▶

Networking ▶

Security ▶

Image and templates ▶

Storage ▶

Monitor and troubleshoot ▶

i-005d90f4edade8730 (Trend-App)

Roles (52) [Info](#)

[Delete](#)[Create role](#)

An IAM role is an identity you can create that has specific permissions with credentials that are valid for short durations. Roles can be assumed by entities that you trust.



1 match



1



Role name



Trusted entities

Last activity



[terraform-ec2-role](#)

AWS Service: ec2

24 minutes



Roles Anywhere [Info](#)

[Manage](#)

Filter by Type

All types ▼



1



☐	Policy name ↗	Type	Attached entities
☐	  AmazonEC2ContainerRegi...	AWS managed	4
☐	  AmazonEC2FullAccess	AWS managed	2
☐	  AmazonEKSClusterPolicy	AWS managed	6
☐	  AmazonEKSServicePolicy	AWS managed	3
☐	  AmazonEKSWorkerNodeP...	AWS managed	6
☐	  AmazonVPCFullAccess	AWS managed	1

Install eksctl:

bash

 Copy code

```
curl -s --location "https://github.com/weaveworks/eksctl/releases/latest/download/eksctl_$(uname -s).amd64.tar.gz" | tar xz
sudo mv /tmp/eksctl /usr/local/bin
```

Verify:

bash

 Copy code

```
eksctl version
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ curl -s --location "https://github.com/weaveworks/eksctl/releases/latest/download/eksctl_$(uname -s)_amd64.tar.gz" | tar xz -C /tmp  
sudo mv /tmp/eksctl /usr/local/bin
```

```
ubuntu@ip-172-31-5-35: ~/Trend/k8s$ eksctl version  
0.221.0  
ubuntu@ip-172-31-5-35: ~/Trend/k8s$
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ eksctl create cluster \
--name trend-cluster \
--region ap-south-1 \
--nodegroup-name trend-nodes \
--node-type t3.medium \
--nodes 2 \
--nodes-min 1 \
--nodes-max 3
Error: describing cluster versions: operation error EKS: DescribeClusterVersions, https response error StatusCode: 403, RequestID: 7855bb6c-22c1-4fe0-9a60-ce88521d932d, api error AccessDeniedException: User: arn:aws:sts::284419413658:assumed-role/terraform-ec2-role/i-005d90f4edad-e8730 is not authorized to perform: eks:DescribeClusterVersions on resource: arn:aws:eks:ap-south-1:284419413658:* because no identity-based policy allows the eks:DescribeClusterVersions action
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

	Policy name	Type	Attached entities
☐	  AmazonEC2ContainerRegi...	AWS managed	4
☐	  AmazonEC2FullAccess	AWS managed	2
☐	  AmazonEKSClusterPolicy	AWS managed	6
☐	  AmazonEKSNetworkingPo...	AWS managed	2
☐	  AmazonEKSServicePolicy	AWS managed	3
☐	  AmazonEKSWorkerNodeP...	AWS managed	6
☐	  AmazonVPCFullAccess	AWS managed	1
☐	  AWSCloudFormationFullA...	AWS managed	1
☐	  IAMFullAccess	AWS managed	1

Filter by Type

All types ▼

24 matches

< 1 2 >

☐	Policy name	Type	Description
☒	+  AdministratorAccess	AWS managed - job function	Provides full access to AWS services an...

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ eksctl create cluster \
--name trend-cluster \
--region ap-south-1 \
--nodegroup-name trend-cluster \
--node-type t3.micro
--nodes 2 \
--nodes-min 1 \
--nodes-max 3
2025-12-25 08:12:25 [i] eksctl version 0.221.0
2025-12-25 08:12:25 [i] using region ap-south-1
2025-12-25 08:12:25 [i] setting availability zones to [ap-south-1b ap-south-1c ap-south-1a]
2025-12-25 08:12:25 [i] subnets for ap-south-1b - public:192.168.0.0/19 private:192.168.96.0/19
2025-12-25 08:12:25 [i] subnets for ap-south-1c - public:192.168.32.0/19 private:192.168.128.0/19
2025-12-25 08:12:25 [i] subnets for ap-south-1a - public:192.168.64.0/19 private:192.168.160.0/19
2025-12-25 08:12:25 [i] nodegroup "trend-cluster" will use "" [AmazonLinux2023/1.32]
```

```
}
2025-12-25 08:12:25 [i] building cluster stack "eksctl-trend-cluster-cluster"
2025-12-25 08:12:26 [i] deploying stack "eksctl-trend-cluster-cluster"
2025-12-25 08:12:56 [i] waiting for CloudFormation stack "eksctl-trend-cluster-cluster"
2025-12-25 08:12:56 [X] unexpected status "ROLLBACK_IN_PROGRESS" while waiting for CloudFormation stack "eksctl-trend-cluster-cluster"
2025-12-25 08:12:56 [X] unexpected status "ROLLBACK_IN_PROGRESS" while waiting for CloudFormation stack "eksctl-trend-cluster-cluster"
2025-12-25 08:12:56 [i] fetching stack events in attempt to troubleshoot the root cause of the failure
2025-12-25 08:12:56 [!] AWS::EC2::EIP/NATIP: DELETE_IN_PROGRESS
2025-12-25 08:12:56 [!] AWS::IAM::Role/ServiceRole: DELETE_IN_PROGRESS
2025-12-25 08:12:56 [!] AWS::EC2::VPC/VPC: DELETE_IN_PROGRESS
2025-12-25 08:12:56 [X] AWS::IAM::Role/ServiceRole: CREATE_FAILED - "Resource creation cancelled"
2025-12-25 08:12:56 [X] AWS::EC2::VPC/VPC: CREATE_FAILED - "Resource creation cancelled"
2025-12-25 08:12:56 [X] AWS::EC2::EIP/NATIP: CREATE_FAILED - "Resource creation cancelled"
2025-12-25 08:12:56 [X] AWS::EC2::InternetGateway/InternetGateway: CREATE_FAILED - "Resource handler returned message: \"The maximum number of internet gateways has been reached. (Service: Ec2, Status Code: 400, Request ID: d007aaa4-b95b-424b-b488-9d98592002a9) (SDK Attempt Count: 1)\" (RequestToken: a485800b-c6cc-d7ab-591a-4965498c2a41, HandlerErrorCode: ServiceLimitExceeded) "
2025-12-25 08:12:56 [!] 1 error(s) occurred and cluster hasn't been created properly, you may wish to check CloudFormation console
2025-12-25 08:12:56 [i] to cleanup resources, run 'eksctl delete cluster --region=ap-south-1 --name=trend-cluster'
2025-12-25 08:12:56 [X] ResourceNotReady: failed waiting for successful resource state
Error: failed to create cluster "trend-cluster"
--nodes: command not found
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

Internet gateways (3/5) Info

Q

Find internet gateways by attribute or tag

	Name	Internet gateway ID	Status	
☐	-	igw-08e0484917b582f59	Available	vpc-078b922c8f
☒	my-igw-2	igw-0ac4ee94fb0da8dbb	Detached	
☐	trend-internet-gateway	igw-0c0ffa5b64714ef89	Available	vpc-0adebe035c trend-internet-gateway
☒	eksctl-brain-eks-cluster/InternetGateway	igw-0f799ab7d7c600fa3	Attached	vpc-0c126d34a5277fb3c eksctl-brain-eks-cluster

Actions

Create internet gateway

- View details

Attach to VPC

Detach from VPC

Manage tags

Delete internet gateway

Internet gateways: igw-0264e70d5705a7972, igw-0f799ab7d7c600fa3, igw-0ac4ee94fb0da8dbb

Delete internet gateway



Are you sure that you want to delete this internet gateway?

- igw-0ac4ee94fb0da8dbb - my-igw-2

The following internet gateways are each attached to a VPC and cannot be deleted:

- igw-0264e70d5705a7972
- igw-0f799ab7d7c600fa3 - eksctl-brain-eks-cluster/InternetGateway

To confirm deletion, type *delete* in the field:

Cancel

Delete internet gateway

```
2025-12-25 08:25:14 [i] building cluster stack "eksctl-trend-cluster-cluster"
2025-12-25 08:25:14 [!] 1 error(s) occurred and cluster hasn't been created properly, you may wish to check CloudFormation console
2025-12-25 08:25:14 [i] to cleanup resources, run 'eksctl delete cluster --region=ap-south-1 --name=trend-cluster'
2025-12-25 08:25:14 [X] creating CloudFormation stack "eksctl-trend-cluster-cluster": operation error CloudFormation: CreateStack, https
response error StatusCode: 400, RequestID: 4ee2bed0-ae96-4ae3-af2e-c74e79adc10b, AlreadyExistsException: Stack [eksctl-trend-cluster-clust
er] already exists
Error: failed to create cluster "trend-cluster"
--nodes: command not found
```

Stacks (5)



Delete

Update stack ▼

Stack actions ▼

Create stack ▼

Filter status

Search by stack name

Active ▼

☒ View nested

Stack name	Status	Created time	Description
 eksctl-trend-cluster-cluster	 ROLLBACK_COMPLETE	2025-12-25 13:42:26 UTC+0530	EKS cluster (dedicated VPC: true, dedicated IAM: true) [created and managed by eksctl]

nodes: Command not found

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ eksctl create cluster \
```

```
--name trend-cluster \
```

```
--region ap-south-1 \
```

```
--nodegroup-name trend-nodes \
```

```
--node-type t3.micro
```

```
--nodes 2 \
```

```
--nodes-min 1 \
```

```
--nodes-max 3
```

```
2025-12-25 08:39:49 [i] eksctl version 0.221.0
```

```
2025-12-25 08:39:49 [i] using region ap-south-1
```

```
2025-12-25 08:39:49 [i] setting availability zones to [ap-south-1b ap-south-1a ap-south-1c]
```

```
2025-12-25 08:39:49 [i] subnets for ap-south-1b - public:192.168.0.0/19 private:192.168.96.0/19
```

```
2025-12-25 08:39:49 [i] subnets for ap-south-1a - public:192.168.32.0/19 private:192.168.128.0/19
```

```
2025-12-25 08:39:49 [i] subnets for ap-south-1c - public:192.168.64.0/19 private:192.168.160.0/19
```

```
2025-12-25 08:39:49 [i] nodegroup "trend-nodes" will use "" [AmazonLinux2023/1.32]
```



```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ kubectl get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
ip-192-168-23-90.ap-south-1.compute.internal	Ready	<none>	15m	v1.32.9-eks-ecaa3a6
ip-192-168-78-181.ap-south-1.compute.internal	Ready	<none>	15m	v1.32.9-eks-ecaa3a6

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ cd ..
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl apply -f k8s/
```

```
deployment.apps/trend-app created
```

```
service/trend-service created
```

```
ubuntu@ip-172-31-5-35:~/Trend$
```

ubuntu@ip-192-168-23-90:~\$

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
ip-192-168-23-90.ap-south-1.compute.internal	Ready	<none>	18m	v1.32.9-eks-ecaa3a6
ip-192-168-78-181.ap-south-1.compute.internal	Ready	<none>	18m	v1.32.9-eks-ecaa3a6

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get svc
NAME                                TYPE                CLUSTER-IP      EXTERNAL-IP      PORT(S)          AGE
kubernetes                         ClusterIP           10.100.0.1      <none>           443/TCP          24m
trend-service                      LoadBalancer       10.100.52.20    af0a09939a1464300abce5f383a15be1-1271015444.ap-south-1.elb.amazonaws.com 80:31309/TCP     48s
ubuntu@ip-172-31-5-35:~/Trend$
```



This site can't be reached

af0a09939a1464300abce5f383a15be1-1271015444.ap-south-1.elb.amazonaws.com
took too long to respond.

Try:

- Checking the connection
- [Checking the proxy and the firewall](#)
- [Running Windows Network Diagnostics](#)

ERR_CONNECTION_TIMED_OUT

Reload

Details

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
trend-app-6775696f64-2np9m	0/1	Pending	0	11m
trend-app-6775696f64-6kwxm	0/1	Pending	0	11m

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get svc
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT (S)	AG
kubernetes	ClusterIP	10.100.0.1	<none>	443/TCP	24
trend-service	LoadBalancer	10.100.52.20	af0a09939a1464300abce5f383a15be1-1271015444.ap-south-1.elb.amazonaws.com	80:31309/TCP	48

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get svc trend-service
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT (S)	AG
trend-service	LoadBalancer	10.100.52.20	af0a09939a1464300abce5f383a15be1-1271015444.ap-south-1.elb.amazonaws.com	80:31309/TCP	2m14s

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
ip-192-168-23-90.ap-south-1.compute.internal	Ready	<none>	37m	v1.32.9-eks-ecaa3a6
ip-192-168-78-181.ap-south-1.compute.internal	Ready	<none>	38m	v1.32.9-eks-ecaa3a6

```
ubuntu@ip-172-31-5-35:~/Trend$
```



```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl describe pod trend-app-6775696f64-2np9m
Name: trend-app-6775696f64-2np9m
Namespace: default
Priority: 0
Service Account: default
Node: <none>
Labels: app=trend
        pod-template-hash=6775696f64
Annotations: <none>
Status: Pending
IP: <none>
IPs: <none>
Controlled By: ReplicaSet/trend-app-6775696f64
Containers:
  trend-container:
    Image: dockerhubuser/trend-app:latest
    Port: 3000/TCP
    Host Port: 0/TCP
    Environment: <none>
    Mounts:
      /var/run/secrets/kubernetes.io/serviceaccount from kube-api-access-zcp7k (ro)
Conditions:
  Type           Status
  PodScheduled   False
Volumes:
  kube-api-access-zcp7k:
    Type: Projected (a volume that contains injected data from multiple sources)
    TokenExpirationSeconds: 3607
    ConfigMapName: kube-root-ca.crt
    Optional: false
    DownwardAPI: true
QoS Class: BestEffort
Node-Selectors: <none>
Tolerations: node.kubernetes.io/not-ready:NoExecute op=Exists for 300s
              node.kubernetes.io/unreachable:NoExecute op=Exists for 300s
Events:
  Type      Reason             Age          From          Message
  ----      -
  Warning   FailedScheduling   25m          default-scheduler  0/2 nodes are available: 2 Too many pods. preemption: 0/2 nodes are available: 2 No preemption victims found for incoming pod.
  Warning   FailedScheduling   15m (x2 over 20m)  default-scheduler  0/2 nodes are available: 2 Too many pods. preemption: 0/2 nodes are available: 2 No preemption victims found for incoming pod.
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl scale deployment trend-app --replicas=1
```

```
deployment.apps/trend-app scaled
```

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl scale deployment trend-app --replicas=3
```

```
deployment.apps/trend-app scaled
```

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl scale deployment trend-app --replicas=3
```

```
deployment.apps/trend-app scaled
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
trend-app-6775696f64-2np9m	0/1	Pending	0	33m
trend-app-6775696f64-2nrj4	0/1	Pending	0	11s
trend-app-6775696f64-wb64g	0/1	Pending	0	11s

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl scale deployment trend-app --replicas=1
```

```
deployment.apps/trend-app scaled
```

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
trend-app-6775696f64-2np9m	0/1	Pending	0	36m

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl scale deployment trend-app --replicas=1
deployment.apps/trend-app scaled
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
trend-app-6775696f64-2np9m          0/1     Pending   0           36m
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl delete pod -l app=trend
pod "trend-app-6775696f64-2np9m" deleted from default namespace
ubuntu@ip-172-31-5-35:~/Trend$ □
```



```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl scale deployment trend-app --replicas=1
```

```
deployment.apps/trend-app scaled
```

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl rollout restart deployment trend-app
```

```
deployment.apps/trend-app restarted
```

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
trend-app-557d8bd6b8-zpdsp	0/1	Pending	0	43s
trend-app-6775696f64-xlk86	0/1	Pending	0	2m28s

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ eksctl get nodegroup --cluster trend-cluster
Error: could not create cluster provider from options: AWS Region must be set, please set the AWS Region in AWS config file or as environment variable
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ eksctl create nodegroup \
```

```
--cluster trend-cluster \
```

```
--region ap-south-1 \
```

```
--name trend-nodes \
```

```
--node-type t3.nano \
```

```
--nodes 2 \
```

```
--nodes-min 1 \
```

```
--nodes-max 3 \
```

```
--managed
```

```
Error: could not create cluster provider from options: unable to describe cluster control plane: operation error EKS: DescribeCluster, https response error StatusCode: 404, RequestID: 06071238-c9fe-4a77-9933-395f9a34fd15, ResourceNotFoundException: No cluster found for name: trend-cluster.
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ eksctl create cluster \
--name trend-cluster \
--region ap-south-1 \
--nodegroup-name trend-nodes \
--node-type t3.nano \
--nodes 2 \
--nodes-min 1 \
--nodes-max 3
2025-12-25 12:42:32 [i] eksctl version 0.221.0
2025-12-25 12:42:32 [i] using region ap-south-1
2025-12-25 12:42:32 [i] setting availability zones to [ap-south-1b ap-south-1c ap-south-1a]
2025-12-25 12:42:32 [i] subnets for ap-south-1b - public:192.168.0.0/19 private:192.168.96.0/19
2025-12-25 12:42:32 [i] subnets for ap-south-1c - public:192.168.32.0/19 private:192.168.128.0/19
2025-12-25 12:42:32 [i] subnets for ap-south-1a - public:192.168.64.0/19 private:192.168.160.0/19
2025-12-25 12:42:32 [i] nodegroup "trend-nodes" will use "" [AmazonLinux2023/1.32]
2025-12-25 12:42:32 [!] Auto Mode will be enabled by default in an upcoming release of eksctl. This means managed node groups and managed n
etworking add-ons will no longer be created by default. To maintain current behavior, explicitly set 'autoModeConfig.enabled: false' in your
cluster configuration. Learn more: https://eksctl.io/usage/auto-mode/
2025-12-25 12:42:32 [i] using Kubernetes version 1.32
```

```
2025-12-25 16:00:55 [!] 1 error(s) occurred and cluster hasn't been created properly, you may wish to check CloudFormation console
2025-12-25 16:00:55 [i] to cleanup resources, run 'eksctl delete cluster --region=ap-south-1 --name=trend-cluster'
2025-12-25 16:00:55 [X] exceeded max wait time for StackCreateComplete waiter
Error: failed to create cluster "trend-cluster"
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```


resources found in actual namespace:

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ kubectl get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
ip-192-168-29-132.ap-south-1.compute.internal	Ready	<none>	6m25s	v1.32.9-eks-ecaa3a6
ip-192-168-62-244.ap-south-1.compute.internal	Ready	<none>	6m25s	v1.32.9-eks-ecaa3a6

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ cd ..
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl apply -f k8s/
```

```
deployment.apps/trend-app created
```

```
service/trend-service created
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
trend-app-6775696f64-mrdwz	0/1	ErrImagePull	0	6s
trend-app-6775696f64-v8xcw	0/1	ErrImagePull	0	6s

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
node.kubernetes.io/unreachable:NoExecute op=Exists for 300s

Events:
  Type            Reason            Age               From              Message
  ----            -
  Normal          Scheduled         2m21s            default-scheduler Successfully assigned default/trend-app-6775696f64-mrdwz to ip-192-168-62-24
4.ap-south-1.compute.internal
  Normal          Pulling           44s (x4 over 2m21s) kubelet            spec.containers{trend-container}: Pulling image "dockerhubuser/trend-app:lat
est"
  Warning         Failed            43s (x4 over 2m19s) kubelet            spec.containers{trend-container}: Failed to pull image "dockerhubuser/trend-
app:latest": failed to pull and unpack image "docker.io/dockerhubuser/trend-app:latest": failed to resolve reference "docker.io/dockerhubu
ser/trend-app:latest": pull access denied, repository does not exist or may require authorization: server message: insufficient_scope: aut
horization failed
  Warning         Failed            43s (x4 over 2m19s) kubelet            spec.containers{trend-container}: Error: ErrImagePull
  Normal          BackOff           5s (x8 over 2m18s) kubelet            spec.containers{trend-container}: Back-off pulling image "dockerhubuser/tren
d-app:latest"
  Warning         Failed            5s (x8 over 2m18s) kubelet            spec.containers{trend-container}: Error: ImagePullBackOff

ubuntu@ip-172-31-5-35:~/Trend$
```

```
  app: trend
template:
  metadata:
    labels:
      app: trend
  spec:
    containers:
      - name: trend-container
        image: dockerhubuser/trend-app
```

/var/run/secrets/kubernetes.io/serviceaccount/token kube-api-access-fthkj (10)

Conditions:

Type	Status
PodScheduled	False

Volumes:

kube-api-access-fthkj:

Type:	Projected (a volume that contains injected data from multiple sources)
TokenExpirationSeconds:	3607
ConfigMapName:	kube-root-ca.crt
Optional:	false
DownwardAPI:	true

QoS Class: BestEffort

Node-Selectors: <none>

Tolerations: node.kubernetes.io/not-ready:NoExecute op=Exists for 300s
node.kubernetes.io/unreachable:NoExecute op=Exists for 300s

Events:

Type	Reason	Age	From	Message
----	-----	----	----	-----
Warning	FailedScheduling	3m30s	default-scheduler	0/2 nodes are available: 2 Too many pods. preemption: 0/2 nodes are available: 2 No preemption victims found for incoming pod.

ubuntu@ip-172-31-5-35:~/Trend/k8s\$

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ kubectl get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
ip-192-168-31-108.ap-south-1.compute.internal	Ready	<none>	88s	v1.32.9-eks-ecaa3a6
ip-192-168-49-122.ap-south-1.compute.internal	Ready	<none>	10m	v1.32.9-eks-ecaa3a6
ip-192-168-67-20.ap-south-1.compute.internal	Ready	<none>	10m	v1.32.9-eks-ecaa3a6

```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
trend-app-6d6984c74c-f55b1	0/1	ErrImagePull	0	8m34s
trend-app-6d6984c74c-rsq76	0/1	ImagePullBackOff	0	8m34s

```
node.kubernetes.io/not-ready:NoExecute op=Exists for 300s
Events:
  Type      Reason              Age             From              Message
  ----      -
Warning    FailedScheduling    11m             default-scheduler 0/2 nodes are available: 2 Too many pods.
preemption: 0/2 nodes are available: 2 No
preemption victims found for incoming pod.
Warning    FailedScheduling    4m27s (x2 over 5m56s) default-scheduler 0/2 nodes are available: 2 Too many pods.
preemption: 0/2 nodes are available: 2 No
preemption victims found for incoming pod.
Warning    FailedScheduling    4m23s             default-scheduler 0/3 nodes are available: 1 node(s) had
untolerated taint {node.kubernetes.io/not-ready: }, 2 Too many pods.
preemption: 0/3 nodes are available: 1
Preemption is not helpful for scheduling, 2 No
preemption victims found for incoming pod.
Normal     Scheduled           4m14s             default-scheduler Successfully assigned default/trend-app-6d6984c74c-f55b1 to ip-192-168-31-108.ap-south-1.compute.internal
Warning    FailedCreatePodSandBox 4m13s             kubelet           Failed to create pod sandbox: rpc error: code = Unknown desc = failed to setup network for sandbox "4e672a47f82ebb81c3fca6ea3010b7be81eddb265cea8e965c621508be25d052": plugin type="aws-cni" name="aws-cni" failed (add): add cmd: failed to assign an IP address to container
Normal     Pulling             45s (x5 over 3m58s) kubelet           spec.containers{trend-container}: Pulling image "dockerhubuser/trend-app"
Warning    Failed              44s (x5 over 3m56s) kubelet           spec.containers{trend-container}: Failed to pull image "dockerhubuser/trend-app": failed to pull and unpack image "docker.io/dockerhubuser/trend-app:latest": failed to resolve reference "docker.io/dockerhubuser/trend-app:latest": pull access denied, repository does not exist or may require authorization: server message: insufficient_scope: authorization failed
Warning    Failed              44s (x5 over 3m56s) kubelet           spec.containers{trend-container}: Error: ErrImagePull
Normal     BackOff             3s (x14 over 3m56s) kubelet           spec.containers{trend-container}: Back-off pulling image "dockerhubuser/trend-app"
Warning    Failed              3s (x14 over 3m56s) kubelet           spec.containers{trend-container}: Error: ImagePullBackOff
ubuntu@ip-172-31-5-35:~/Trend/k8s$
```

```
    app: trend
template:
  metadata:
    labels:
      app: trend
  spec:
    containers:
      - name: trend-container
        image: deepesh79/trend-app
```

```
Events:
  Type      Reason          Age    From          Message
  ----      -
Warning    FailedScheduling 43s    default-scheduler 0/2 nodes are available: 2 Too many pods.
preemption: 0/2 nodes are available: 2 No
preemption victims found for incoming pod.
ubuntu@ip-172-31-5-35:~/Trend$
```



```
ubuntu@ip-172-31-5-35:~/Trend/k8s$ kubectl get nodes
NAME                                                    STATUS    ROLES    AGE   VERSION
ip-192-168-22-247.ap-south-1.compute.internal          Ready    <none>    9h   v1.32.9-eks-ecaa3a6
ip-192-168-56-12.ap-south-1.compute.internal           Ready    <none>    9h   v1.32.9-eks-ecaa3a6
ip-192-168-83-173.ap-south-1.compute.internal          Ready    <none>    9h   v1.32.9-eks-ecaa3a6
ubuntu@ip-172-31-5-35:~/Trend/k8s$ cd ..
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
trend-app-b4f86468f-596jh           1/1     Running    0           9h
trend-app-b4f86468f-jfc9f           1/1     Running    0           9h
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get svc
NAME                                TYPE                CLUSTER-IP      EXTERNAL-IP      PORT(S)          AGE
kubernetes                         ClusterIP            10.100.0.1       <none>           443/TCP          9h
trend-service                      LoadBalancer        10.100.149.46    a6150c9a4e36f40788fe8514c6cf8fbb-576434722.ap-south-1.elb.amazonaws.com 80:30178/TCP     9h
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get svc
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
kubernetes	ClusterIP	10.100.0.1	<none>	443/TCP	9h
trend-service	LoadBalancer	10.100.149.46	a6150c9a4e36f40788fe8514c6cf8fbb-576434722.ap-south-1.elb.amazonaws.com	80:30178/TCP	9h

```
ubuntu@ip-172-31-5-35:~/Trend$
```



This site can't be reached

a6150c9a4e36f40788fe8514c6cf8fbb-576434722.ap-south-1.elb.amazonaws.com
took too long to respond.

Try:

- Checking the connection
- [Checking the proxy and the firewall](#)
- [Running Windows Network Diagnostics](#)

ERR_CONNECTION_TIMED_OUT

Reload

Details

```
apiVersion: v1
```

```
kind: Service
```

```
metadata:
```

```
  name: trend-service
```

```
spec:
```

```
  type: LoadBalancer
```

```
  selector:
```

```
    app: trend
```

```
  ports:
```

```
    - port: 3000
```

```
      targetPort: 3000
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl apply -f k8s/service.yml
```

```
service/trend-service configured
```

```
ubuntu@ip-172-31-5-35:~/Trend$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
trend-app-b4f86468f-596jh           1/1     Running   0           9h
trend-app-b4f86468f-jfc9f           1/1     Running   0           9h
ubuntu@ip-172-31-5-35:~/Trend$ kubectl get svc
NAME                                TYPE                CLUSTER-IP      EXTERNAL-IP      PORT(S)          AGE
kubernetes                         ClusterIP            10.100.0.1       <none>            443/TCP           9h
trend-service                      LoadBalancer        10.100.149.46    a6150c9a4e36f40788fe8514c6cf8fbb-576434722.ap-south-1.elb.amazonaws.com 3000:30178/TCP    9h
ubuntu@ip-172-31-5-35:~/Trend$
```



Not secure a6150c9a4e36f40788fe8514c6cf8fbb-576434722.ap-south-1.elb.amazonaws.com:3000



New Chrome available



HOME

COLLECTION

ABOUT

CONTACT



— OUR BEST SELLERS

Latest Arrivals

SHOP NOW —



Activate Windows

```
ubuntu@ip-172-31-5-35:~/Trend$ git pull origin main
remote: Enumerating objects: 8, done.
remote: Counting objects: 100% (8/8), done.
remote: Compressing objects: 100% (6/6), done.
remote: Total 6 (delta 3), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (6/6), 2.05 KiB | 1.02 MiB/s, done.
From https://github.com/deepeshchandnani/trend-app
* branch                main                -> FETCH_HEAD
   b630326..16f2b47      main                -> origin/main
Updating b630326..16f2b47
Fast-forward
 jenkinsfile | 45 ++++++-----
 1 file changed, 20 insertions(+), 25 deletions(-)
ubuntu@ip-172-31-5-35:~/Trend$
```



```
ubuntu@ip-172-31-5-35: ~/Trends$ git add k8s/
```

```
ubuntu@ip-172-31-5-35: ~/Trends$ 
```

```
ubuntu@ip-172-31-5-35: ~/Trends$ git add terraform
```

```
ubuntu@ip-172-31-5-35: ~/Trends$
```

```
ubuntu@ip-172-31-5-35:~/Trend$ git status
```

```
On branch main
```

```
Changes to be committed:
```

```
(use "git restore --staged <file>..." to unstage)
```

```
new file:   k8s/deployment.yml
```

```
new file:   k8s/service.yml
```

```
new file:   terraform/.terraform.lock.hcl
```

```
new file:   terraform/main.tf
```

```
new file:   terraform/main.tf.save
```

```
new file:   terraform/main.tf.save.1
```

```
new file:   terraform/outputs.tf
```

```
new file:   terraform/provider.tf
```

```
new file:   terraform/variables.tf
```

```
Untracked files:
```

```
ubuntu@ip-172-31-5-35:~/Trend$ git commit -m "kubernetes and tensorflow files"
```

```
9 files changed, 268 insertions(+)
create mode 100644 k8s/deployment.yml
create mode 100644 k8s/service.yml
create mode 100644 terraform/.terraform.lock.hcl
create mode 100644 terraform/main.tf
create mode 100644 terraform/main.tf.save
create mode 100644 terraform/main.tf.save.1
create mode 100644 terraform/outputs.tf
create mode 100644 terraform/provider.tf
create mode 100644 terraform/variables.tf
ubuntu@ip-172-31-5-35:~/Trend$
```