Ex. NO: 13

Date: 10/9/2026

Implement your own ping program.

Aim:

To implement a ping program using python to check the connectivity between two computers and measure the response time.

Program:

```
import os
import platform
import subprocess
def ping(host = "google.com", count = 4):
    param = "-n" if platform.system().lower() ==
                                    "windows" else "-c"
    command = ["ping", param, str(count), host]
    try:
        output = subprocess.check_output(command,
                                    universal_newlines: True)
        Print(output)
    except Exception as e:
        Print(f"Ping failed: {e}")
if __name__ == "__main__":
    ping("8.8.8.8")
```

Output:

```
Pinging 8.8.8.8 with 32 bytes of data:
Reply from 8.8.8.8: bytes = 32 time = 6ms TTL = 119
Reply from 8.8.8.8: bytes = 32 time = 9ms TTL = 119
Reply from 8.8.8.8: bytes = 32 time = 5ms TTL = 119
Reply from 8.8.8.8: bytes = 32 time = 9ms TTL = 119

Ping statistics for 8.8.8.8:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 5ms, Maximum = 9ms, Average = 7ms
```

Result:

Thus, the ping program was implemented successfully, and the connectivity between the computers was checked.