

AEGIS

Agentic Engine for Global Investigation & Safety

Complete Supabase SQL Reference

Project: UiPath Hackathon 2026

Database: Supabase PostgreSQL — mtbfgbyzgqenkzfejbvr

Total Files: 15 SQL files

Tables: 17 tables across 4 domains

Folder: AI Human Trafficking Detection & Prevention Network / AEGIS

Overview

AEGIS uses Supabase (PostgreSQL) as its backend database. Below is a complete reference of all 15 SQL files used throughout the project, organized by domain.

File	Purpose
schema.sql	7 core KPI tables (metrics, countries, sources, threats, etc.)
seed.sql	Full seed: 176 countries, 22 sources, 23 threats, 22 PAR, 21 PPR, 22 ops
cases-schema.sql	cases + case_documents tables + 7 India seed cases
cases-seed-extended.sql	Cases 0008–0013+ (international victims)
criminals-schema.sql	criminals table with 40+ JSONB fields + GIN indexes
settings-schema.sql	platform_config, agent_status, platform_users, dashboard_tiles
security-fix.sql	Hardened RLS: platform_config/users/agents = authenticated-only
fix-rls.sql	Cases made publicly readable for Police Portal
storage-setup.sql	case-documents storage bucket (50MB, public)
20240001_criminals.sql	4 international criminals (Sokolov, Okafor, Yilmaz, Tsang)
20240002_criminals_india.sql	9 India criminals across 6 cities
20260624_police_portal.sql	police_officers, police_cases, case_notifications + triggers
20260624_police_superadmin.sql	mkhan@tsp.tech as Director General (AEGIS-SA-0001)
20260624_police_full_setup.sql	Combined full police setup with updated_at triggers
20260625_aegis_case_results.sql	11 Maestro analysis columns added to police_cases

1. schema.sql — Core KPI Tables

Run first. Creates the 7 public-read KPI tables that power the AEGIS intelligence dashboard.

SQL

```
CREATE EXTENSION IF NOT EXISTS "pgcrypto";

CREATE TABLE IF NOT EXISTS metrics (
  id          BIGSERIAL PRIMARY KEY,
  slug        TEXT UNIQUE NOT NULL,
  label       TEXT NOT NULL,
  display_count TEXT NOT NULL,
  count_value BIGINT DEFAULT 0,
  subtitle    TEXT,
  color       TEXT DEFAULT '#3b82f6',
  updated_at  TIMESTAMPTZ DEFAULT NOW()
);

CREATE TABLE IF NOT EXISTS countries (
  id          BIGSERIAL PRIMARY KEY,
  country     TEXT NOT NULL,
  region      TEXT,
  status      TEXT CHECK (status IN ('Alert', 'Monitor', 'Active', 'Resolved')),
  risk_level  TEXT CHECK (risk_level IN ('Critical', 'High', 'Medium', 'Low')),
  active_cases INTEGER DEFAULT 0,
  monitored_since INTEGER,
  updated_at  TIMESTAMPTZ DEFAULT NOW()
);

CREATE TABLE IF NOT EXISTS sources (
  id          BIGSERIAL PRIMARY KEY,
  source_name TEXT NOT NULL,
  type        TEXT,
  category    TEXT,
  signals_count TEXT,
  last_ingested TIMESTAMPTZ,
  status      TEXT CHECK (status IN ('Live', 'Degraded', 'Offline')),
  updated_at  TIMESTAMPTZ DEFAULT NOW()
);

CREATE TABLE IF NOT EXISTS threats (
  id          BIGSERIAL PRIMARY KEY,
  case_ref    TEXT UNIQUE NOT NULL,
  threat_type TEXT,
  severity    TEXT CHECK (severity IN ('Critical', 'High', 'Medium', 'Low')),
  location    TEXT,
  detected_at DATE,
  status      TEXT CHECK (status IN ('Escalated', 'Open', 'Under Review', 'Resolved')),
  updated_at  TIMESTAMPTZ DEFAULT NOW()
);

CREATE TABLE IF NOT EXISTS persons_at_risk (
  id          BIGSERIAL PRIMARY KEY,
  case_ref    TEXT UNIQUE NOT NULL,
  age_group   TEXT CHECK (age_group IN ('Child', 'Minor', 'Adult', 'Senior')),
  gender      TEXT,
  location    TEXT,
  risk_level  TEXT CHECK (risk_level IN ('Critical', 'High', 'Medium', 'Low')),
```

```

    flagged_at      DATE,
    assigned_agent  TEXT,
    updated_at      TIMESTAMPTZ DEFAULT NOW()
);

CREATE TABLE IF NOT EXISTS persons_protected (
    id              BIGSERIAL PRIMARY KEY,
    case_ref        TEXT UNIQUE NOT NULL,
    outcome         TEXT CHECK (outcome IN ('Rescued', 'Shelter', 'Repatriated', 'Legal
Aid', 'Medical')),
    ngo_partner     TEXT,
    location        TEXT,
    resolved_at     DATE,
    support_duration TEXT,
    updated_at      TIMESTAMPTZ DEFAULT NOW()
);

CREATE TABLE IF NOT EXISTS operations (
    id              BIGSERIAL PRIMARY KEY,
    operation_name  TEXT NOT NULL,
    lead_agency    TEXT,
    region         TEXT,
    status         TEXT CHECK (status IN ('Active', 'Completed', 'Planned', 'Suspended')),
    team_size      INTEGER DEFAULT 0,
    started_at     DATE,
    mission_type    TEXT,
    updated_at      TIMESTAMPTZ DEFAULT NOW()
);

-- Enable RLS with public read on all 7 tables
ALTER TABLE metrics          ENABLE ROW LEVEL SECURITY;
ALTER TABLE countries        ENABLE ROW LEVEL SECURITY;
ALTER TABLE sources          ENABLE ROW LEVEL SECURITY;
ALTER TABLE threats          ENABLE ROW LEVEL SECURITY;
ALTER TABLE persons_at_risk  ENABLE ROW LEVEL SECURITY;
ALTER TABLE persons_protected ENABLE ROW LEVEL SECURITY;
ALTER TABLE operations       ENABLE ROW LEVEL SECURITY;

CREATE POLICY "public_read" ON metrics          FOR SELECT USING (true);
CREATE POLICY "public_read" ON countries        FOR SELECT USING (true);
CREATE POLICY "public_read" ON sources          FOR SELECT USING (true);
CREATE POLICY "public_read" ON threats          FOR SELECT USING (true);
CREATE POLICY "public_read" ON persons_at_risk  FOR SELECT USING (true);
CREATE POLICY "public_read" ON persons_protected FOR SELECT USING (true);
CREATE POLICY "public_read" ON operations       FOR SELECT USING (true);

```

2. seed.sql — KPI Seed Data

Populates the 7 KPI tables with realistic intelligence data. Run after schema.sql.

Table	Records
metrics	6 KPI counters (countries, sources, threats, PAR, PPR, operations)
countries	24 countries (Southeast Asia, West Africa, Eastern Europe, South/North America, South Asia)

sources	22 intelligence feeds (TikTok, Telegram, SWIFT, Interpol, UNHCR, Dark Web, etc.)
threats	23 threat records (THR-2024-00891 through THR-2024-00913)
persons_at_risk	22 records (PAR-2024-04521 through PAR-2024-04542)
persons_protected	21 records (PPR-2024-01201 through PPR-2024-01221)
operations	22 operations (Safe Harbor, Dark Shield, Horizon Blue, Chain Break, etc.)

SQL

```
INSERT INTO metrics (slug, label, display_count, count_value, subtitle, color) VALUES
('countries',      'Countries Monitored', '176',    176,    '...', '#3b82f6'),
('sources',        'Sources Analyzed',   '2.89M+', 2890000, '...', '#8b5cf6'),
('threats',        'Threats Detected',   '48,932', 48932,   '...', '#ef4444'),
('persons_at_risk', 'Lives At Risk',      '12,845', 12845,   '...', '#f97316'),
('persons_protected', 'Lives Protected',    '7,341',  7341,   '...', '#22c55e'),
('operations',     'Operations Supported', '3,287',  3287,   '...', '#0ea5e9')
ON CONFLICT (slug) DO UPDATE SET
  display_count = EXCLUDED.display_count,
  count_value   = EXCLUDED.count_value,
  updated_at    = NOW();
```

3. cases-schema.sql — Cases Table

Creates the AEGIS cases tracking table and case_documents. Includes 7 India-based seed cases (AEGIS-2024-0001 through 0007).

SQL

```
CREATE TABLE IF NOT EXISTS cases (  
  id                BIGSERIAL PRIMARY KEY,  
  case_id           TEXT UNIQUE NOT NULL,  
  victim_name       TEXT NOT NULL,  
  victim_alias      TEXT,  
  victim_age        INTEGER,  
  victim_gender     TEXT,  
  victim_nationality TEXT,  
  victim_description TEXT,  
  status            TEXT DEFAULT 'open',  
  risk_level        TEXT DEFAULT 'medium',  
  rescue_status     TEXT DEFAULT 'not_started',  
  last_known_location TEXT,  
  country           TEXT,  
  source_police     BOOLEAN DEFAULT FALSE,  
  source_ngo        BOOLEAN DEFAULT FALSE,  
  source_dark_web   BOOLEAN DEFAULT FALSE,  
  source_social_media BOOLEAN DEFAULT FALSE,  
  source_surveillance BOOLEAN DEFAULT FALSE,  
  source_htca       BOOLEAN DEFAULT FALSE,  
  source_other      BOOLEAN DEFAULT FALSE,  
  assigned_agent    TEXT,  
  assigned_officer  TEXT,  
  notes            TEXT,  
  date_reported     DATE DEFAULT CURRENT_DATE,  
  created_at        TIMESTAMPTZ DEFAULT NOW(),  
  updated_at        TIMESTAMPTZ DEFAULT NOW()  
);  
  
CREATE TABLE IF NOT EXISTS case_documents (  
  id          BIGSERIAL PRIMARY KEY,  
  case_id     TEXT REFERENCES cases(case_id),  
  doc_name    TEXT NOT NULL,  
  doc_type    TEXT,  
  doc_url     TEXT,  
  uploaded_at TIMESTAMPTZ DEFAULT NOW()  
);  
  
ALTER TABLE cases          ENABLE ROW LEVEL SECURITY;  
ALTER TABLE case_documents ENABLE ROW LEVEL SECURITY;  
CREATE POLICY "public_read" ON cases          FOR SELECT USING (true);  
CREATE POLICY "public_read" ON case_documents FOR SELECT USING (true);
```

4. criminals-schema.sql — Criminals Table

Comprehensive criminal profile table with 40+ fields including JSONB arrays for aliases, phone numbers, associates, organizations, fake identities, and travel history.

SQL

```
CREATE TABLE IF NOT EXISTS criminals (  
  criminal_id      UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  name             TEXT NOT NULL,  
  aliases          JSONB DEFAULT '[]',  
  face_image_url   TEXT,  
  face_images      JSONB DEFAULT '[]',  
  date_of_birth    DATE,  
  gender           TEXT,  
  nationality       TEXT,  
  physical_description JSONB DEFAULT '{}',  
  mental_status    TEXT DEFAULT 'unknown'  
    CHECK (mental_status IN ('fit', 'mentally_challenged', 'unknown')),  
  address_current  TEXT,  
  address_history  JSONB DEFAULT '[]',  
  phone_numbers   JSONB DEFAULT '[]',  
  email_addresses JSONB DEFAULT '[]',  
  family_members  JSONB DEFAULT '[]',  
  associates       JSONB DEFAULT '[]',  
  organizations   JSONB DEFAULT '[]',  
  social_media_handles JSONB DEFAULT '[]',  
  crime_types      JSONB DEFAULT '[]',  
  organ_trafficking BOOLEAN DEFAULT FALSE,  
  organ_trafficking_details TEXT,  
  crime_areas      JSONB DEFAULT '[]',  
  victim_profile   JSONB DEFAULT '{}',  
  tracking_history TEXT,  
  case_history     JSONB DEFAULT '[]',  
  linked_cases     JSONB DEFAULT '[]',  
  travel_history   JSONB DEFAULT '[]',  
  current_status   TEXT DEFAULT 'unknown'  
    CHECK (current_status IN ('in_jail', 'parole', 'fugitive', 'deceased', 'unknown', 'released')),  
  current_location TEXT,  
  political_connections TEXT,  
  government_connections TEXT,  
  fake_identity_records JSONB DEFAULT '[]',  
  identity_changes      JSONB DEFAULT '[]',  
  risk_score             INTEGER DEFAULT 50 CHECK (risk_score BETWEEN 0 AND 100),  
  threat_level           TEXT DEFAULT 'medium'  
    CHECK (threat_level IN ('low', 'medium', 'high', 'critical')),  
  ai_analysis            TEXT,  
  created_at             TIMESTAMPTZ DEFAULT NOW(),  
  updated_at             TIMESTAMPTZ DEFAULT NOW(),  
  created_by             TEXT  
);  
  
-- Trigger: auto-update updated_at  
CREATE OR REPLACE FUNCTION set_updated_at()  
RETURNS TRIGGER AS $$ BEGIN NEW.updated_at = NOW(); RETURN NEW; END; $$ LANGUAGE plpgsql;  
  
CREATE TRIGGER trg_criminals_updated_at  
  BEFORE UPDATE ON criminals FOR EACH ROW EXECUTE FUNCTION set_updated_at();  
  
-- RLS  
ALTER TABLE criminals ENABLE ROW LEVEL SECURITY;  
CREATE POLICY "anon_select" ON criminals FOR SELECT TO anon USING (true);  
CREATE POLICY "auth_all" ON criminals FOR ALL TO authenticated USING (true) WITH CHECK (true);  
  
-- Indexes  
CREATE INDEX IF NOT EXISTS idx_criminals_name ON criminals (name);  
CREATE INDEX IF NOT EXISTS idx_criminals_threat_level ON criminals (threat_level);
```

```
CREATE INDEX IF NOT EXISTS idx_criminals_current_status ON criminals (current_status);
CREATE INDEX IF NOT EXISTS idx_criminals_risk_score      ON criminals (risk_score DESC);
CREATE INDEX IF NOT EXISTS idx_criminals_organ          ON criminals (organ_trafficking) WHERE
organ_trafficking = TRUE;
CREATE INDEX IF NOT EXISTS idx_criminals_aliases_gin    ON criminals USING gin (aliases);
CREATE INDEX IF NOT EXISTS idx_criminals_crimes_gin     ON criminals USING gin (crime_types);
```


5. settings-schema.sql — Platform Config & Agent Status

Platform configuration, agent status monitoring, user management, and dashboard tile configuration.

SQL

```
CREATE TABLE IF NOT EXISTS platform_config (  
  id          BIGSERIAL PRIMARY KEY,  
  key         TEXT UNIQUE NOT NULL,  
  value       TEXT,  
  label       TEXT,  
  category    TEXT,  
  is_secret   BOOLEAN DEFAULT FALSE,  
  updated_at  TIMESTAMPTZ DEFAULT NOW()  
);  
  
CREATE TABLE IF NOT EXISTS agent_status (  
  id          BIGSERIAL PRIMARY KEY,  
  agent_id    TEXT UNIQUE NOT NULL,  
  agent_name  TEXT NOT NULL,  
  status      TEXT DEFAULT 'operational',  
  last_run    TIMESTAMPTZ,  
  jobs_today  INTEGER DEFAULT 0,  
  description TEXT,  
  updated_at  TIMESTAMPTZ DEFAULT NOW()  
);  
  
CREATE TABLE IF NOT EXISTS platform_users (  
  id          BIGSERIAL PRIMARY KEY,  
  user_id     TEXT UNIQUE NOT NULL,  
  name        TEXT,  
  role        TEXT DEFAULT 'analyst',  
  email       TEXT,  
  last_login  TIMESTAMPTZ,  
  status      TEXT DEFAULT 'active',  
  created_at  TIMESTAMPTZ DEFAULT NOW()  
);  
  
CREATE TABLE IF NOT EXISTS dashboard_tiles (  
  id          BIGSERIAL PRIMARY KEY,  
  tile_key    TEXT UNIQUE NOT NULL,  
  title       TEXT,  
  enabled     BOOLEAN DEFAULT TRUE,  
  position    INTEGER DEFAULT 0,  
  config      JSONB DEFAULT '{}'  
);
```

6. security-fix.sql — Harden RLS

Restricts platform_config, platform_users, and agent_status to authenticated users only. Removes service key from DB.

SQL

```
-- Restrict sensitive tables to authenticated users only  
DROP POLICY IF EXISTS "public_read" ON platform_config;
```

```
CREATE POLICY "auth_read" ON platform_config FOR SELECT USING (auth.uid() IS NOT NULL);

DROP POLICY IF EXISTS "public_read" ON platform_users;
CREATE POLICY "auth_read" ON platform_users FOR SELECT USING (auth.uid() IS NOT NULL);

DROP POLICY IF EXISTS "public_read" ON agent_status;
CREATE POLICY "auth_read" ON agent_status FOR SELECT USING (auth.uid() IS NOT NULL);
```

7. fix-rls.sql — Make Cases Publicly Readable

Allows the Police Portal to read cases without authentication.

```
SQL
DROP POLICY IF EXISTS "auth_read" ON cases;
CREATE POLICY "public_read" ON cases FOR SELECT USING (true);

DROP POLICY IF EXISTS "auth_read" ON case_documents;
CREATE POLICY "public_read" ON case_documents FOR SELECT USING (true);
```

8. storage-setup.sql — Case Documents Bucket

Creates the Supabase Storage bucket for victim photos and case documents (50MB limit, publicly readable).

```
SQL
INSERT INTO storage.buckets (id, name, public, file_size_limit, allowed_mime_types)
VALUES (
  'case-documents',
  'case-documents',
  true,
  52428800, -- 50 MB
  ARRAY['image/jpeg', 'image/png', 'image/gif', 'image/webp',
        'application/pdf', 'application/msword',
        'application/vnd.openxmlformats-officedocument.wordprocessingml.document']
) ON CONFLICT (id) DO NOTHING;

CREATE POLICY "Public read access" ON storage.objects
FOR SELECT USING (bucket_id = 'case-documents');

CREATE POLICY "Auth upload" ON storage.objects
FOR INSERT WITH CHECK (bucket_id = 'case-documents' AND auth.uid() IS NOT NULL);
```

9. 20240001_criminals.sql — International Criminal Profiles

Seeds 4 high-priority international criminal profiles with full JSONB intelligence data.

Name	Nationality Status Risk Crimes
Viktor Dragomir Sokolov	Russian Fugitive 92/Critical Human trafficking, document fraud, money laundering
Amara Ngozi Okafor	Nigerian Fugitive 81/High Sex trafficking, domestic servitude, recruitment fraud
Dr. Hasan Ferhat Yilmaz	Turkish Fugitive 88/Critical Organ trafficking — 23+ illegal kidney extractions
Liang Wei Tsang	HK SAR Released 74/High Labor trafficking, debt bondage, immigration fraud

10. 20240002_criminals_india.sql — India Criminal Profiles (9 records)

Seeds 9 criminal profiles covering 6 major Indian cities with real investigation details.

Name / City	Crime Type Threat Status
Rajesh Kumar Sharma — New Delhi	Human trafficking, child trafficking, drugs Critical Fugitive
Priya Malhotra — Noida/NCR	Matrimonial fraud, domestic servitude High Fugitive
Mohammed Iqbal Ansari — Delhi	Hawala operations, terror financing, drugs Critical Fugitive
Sunita Rawat — Gurugram	Labor trafficking, domestic servitude High Released on bail
Vikram Desai — Mumbai	Meth distribution, arms smuggling, money laundering Critical Fugitive
Dr. Arun Nair — Bengaluru	Organ trafficking — 14+ illegal kidney extractions Critical Fugitive
Tapas Biswas — Kolkata	India–Bangladesh trafficking corridor, child trafficking High Fugitive
Cyrus Mehta — Hyderabad	Ransomware-as-a-service, banking fraud, dark web High Released on bail
Selvaraj Murugan — Chennai	Sea-route drug/arms smuggling, migrant smuggling High Fugitive

11. 20260624_police_portal.sql — Police Portal Tables

Creates the complete Police Portal database schema with automatic case number generation and AEGIS notification triggers.

SQL

```
-- Police Officers table
CREATE TABLE IF NOT EXISTS public.police_officers (
  id          UUID DEFAULT gen_random_uuid() PRIMARY KEY,
  user_id     UUID REFERENCES auth.users(id) ON DELETE SET NULL,
  police_id   VARCHAR(50) UNIQUE NOT NULL,
  name        VARCHAR(255) NOT NULL,
  rank        VARCHAR(100) DEFAULT 'Constable',
  station_name VARCHAR(255),
  station_code VARCHAR(50),
  district    VARCHAR(100),
  state       VARCHAR(100),
  phone       VARCHAR(20),
  email       VARCHAR(255),
  status      VARCHAR(20) DEFAULT 'pending',
  created_at  TIMESTAMPTZ DEFAULT NOW(),
  updated_at  TIMESTAMPTZ DEFAULT NOW()
);

-- Police Cases table (key fields only)
CREATE TABLE IF NOT EXISTS public.police_cases (
  id          UUID DEFAULT gen_random_uuid() PRIMARY KEY,
  case_no     VARCHAR(60) UNIQUE,
  title       VARCHAR(500) NOT NULL,
  description  TEXT,
  category    VARCHAR(100) DEFAULT 'missing_person',
  status      VARCHAR(50) DEFAULT 'open',
  priority    VARCHAR(20) DEFAULT 'normal',
  officer_id  UUID REFERENCES public.police_officers(id),
  victim_name VARCHAR(255),
  victim_age  INTEGER,
  victim_gender VARCHAR(20),
  victim_photo_url TEXT,
  father_name VARCHAR(255),
  mother_name VARCHAR(255),
  aadhaar_no  VARCHAR(30),
  suspect_name VARCHAR(255),
  suspect_description TEXT,
  last_seen_location TEXT,
  lat         DECIMAL(10,7),
  lng         DECIMAL(10,7),
  date_of_incident TIMESTAMPTZ,
  images      JSONB DEFAULT '[]',
  documents   JSONB DEFAULT '[]',
  surveillance_details JSONB DEFAULT '{}',
  call_history JSONB DEFAULT '[]',
  aegis_acknowledged BOOLEAN DEFAULT FALSE,
  aegis_case_ref VARCHAR(100),
  aegis_ack_at TIMESTAMPTZ,
  aegis_note  TEXT,
  created_at  TIMESTAMPTZ DEFAULT NOW(),
  updated_at  TIMESTAMPTZ DEFAULT NOW()
);
```

```

-- Case Notifications
CREATE TABLE IF NOT EXISTS public.case_notifications (
  id                UUID DEFAULT gen_random_uuid() PRIMARY KEY,
  case_id           UUID REFERENCES public.police_cases(id) ON DELETE CASCADE,
  notification_type VARCHAR(50) DEFAULT 'new_case',
  title             VARCHAR(500),
  message           TEXT,
  officer_name      VARCHAR(255),
  station_name      VARCHAR(255),
  read_by_aegis     BOOLEAN DEFAULT FALSE,
  acknowledged      BOOLEAN DEFAULT FALSE,
  acknowledged_at   TIMESTAMPTZ,
  created_at        TIMESTAMPTZ DEFAULT NOW()
);

-- Auto-generate case_no: PC-2026-01000
CREATE SEQUENCE IF NOT EXISTS public.case_no_seq START 1000;

CREATE OR REPLACE FUNCTION public.generate_case_no()
RETURNS TRIGGER LANGUAGE plpgsql AS $$
BEGIN
  IF NEW.case_no IS NULL OR NEW.case_no = '' THEN
    NEW.case_no := 'PC-' || TO_CHAR(NOW(), 'YYYY') || '-' ||
      LPAD(NEXTVAL('public.case_no_seq')::TEXT, 5, '0');
  END IF;
  RETURN NEW;
END;
$$;

CREATE TRIGGER trg_case_no
BEFORE INSERT ON public.police_cases
FOR EACH ROW EXECUTE FUNCTION public.generate_case_no();

-- Auto-notify AEGIS on new case
CREATE OR REPLACE FUNCTION public.notify_aegis_new_case()
RETURNS TRIGGER LANGUAGE plpgsql AS $$
BEGIN
  INSERT INTO public.case_notifications(case_id, title, message, officer_name, station_name)
  VALUES (
    NEW.id,
    'New Case: ' || NEW.title,
    'Category: ' || NEW.category || ' | Priority: ' || NEW.priority ||
    ' | Victim: ' || COALESCE(NEW.victim_name, 'Unknown'),
    (SELECT name FROM public.police_officers WHERE id = NEW.officer_id),
    NEW.station_name
  );
  RETURN NEW;
END;
$$;

CREATE TRIGGER trg_notify_aegis
AFTER INSERT ON public.police_cases
FOR EACH ROW EXECUTE FUNCTION public.notify_aegis_new_case();

```

12. 20260624_police_superadmin.sql — Super Admin Seed

Creates the Director General account for mkhan@tsp.tech linked to the Supabase auth user.

SQL

```
INSERT INTO public.police_officers (
  user_id, police_id, name, rank,
  station_name, station_code, district, state, email, status
)
SELECT
  au.id,
  'AEGIS-SA-0001',          -- Badge / Login ID
  'M. Khan',
  'Director General',
  'AEGIS Central Command',
  'AEGIS-HQ',
  'Central',
  'National',
  'mkhan@tsp.tech',
  'active'
FROM auth.users au WHERE au.email = 'mkhan@tsp.tech'
ON CONFLICT (police_id) DO UPDATE
  SET user_id = EXCLUDED.user_id, status = 'active', updated_at = NOW();
```

13. 20260625_aegis_case_results.sql — Maestro Analysis Columns

Adds 11 columns to police_cases for storing AEGIS Maestro AI analysis results.

SQL

```
ALTER TABLE public.police_cases
  ADD COLUMN IF NOT EXISTS maestro_case_key      TEXT,
  ADD COLUMN IF NOT EXISTS maestro_status        TEXT,
  ADD COLUMN IF NOT EXISTS overall_intent        TEXT,
  ADD COLUMN IF NOT EXISTS confidence_score      DECIMAL(5,2),
  ADD COLUMN IF NOT EXISTS web_intelligence_summary TEXT,
  ADD COLUMN IF NOT EXISTS criminal_analysis    TEXT,
  ADD COLUMN IF NOT EXISTS recommended_alert_level TEXT,
  ADD COLUMN IF NOT EXISTS threat_level        TEXT,
  ADD COLUMN IF NOT EXISTS analysis_status      TEXT DEFAULT 'pending',
  ADD COLUMN IF NOT EXISTS case_decision       TEXT,
  ADD COLUMN IF NOT EXISTS aegis_completed_at  TIMESTAMPTZ;

CREATE INDEX IF NOT EXISTS idx_police_cases_maestro_key
  ON public.police_cases(maestro_case_key) WHERE maestro_case_key IS NOT NULL;

CREATE INDEX IF NOT EXISTS idx_police_cases_analysis_status
  ON public.police_cases(analysis_status);
```


Recommended Execution Order

Run these SQL files in Supabase SQL Editor (Dashboard → SQL Editor → New Query) in this order:

1	schema.sql	Creates core KPI tables
2	seed.sql	Populates KPI data
3	cases-schema.sql	Creates cases table + 7 seed cases
4	cases-seed-extended.sql	Additional cases 0008–0013+
5	criminals-schema.sql	Creates criminals table + indexes
6	settings-schema.sql	Creates platform_config, agent_status, etc.
7	security-fix.sql	Hardens RLS on sensitive tables
8	fix-rls.sql	Makes cases publicly readable
9	storage-setup.sql	Creates case-documents storage bucket
10	20240001_criminals.sql	Seeds 4 international criminals
11	20240002_criminals_india.sql	Seeds 9 India criminals
12	20260624_police_portal.sql	Creates police portal tables + triggers
13	20260624_police_superadmin.sql	Creates Director General account
14	20260624_police_full_setup.sql	Full police setup (updated_at triggers)
15	20260625_aegis_case_results.sql	Adds Maestro analysis columns